GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ HOZ/1185

Dated: 07/07/15

FIRE SAFETY CERTIFICATE

Certified that the White House Tourist Lodge located at 8177-78, Arakashan Road, Pahar Ganj, New Delhi- 110055.comprised of Ground + 4 Upper Floors (Ground floor – reception + office + cabin & 1st to 3rd floor 10 guest rooms at each floor & terrace – hall & kitchen for staff total 30 guest rooms) was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/3264 dated 07/09/2012. The premise was re-inspected by the officer concerned of this department on 25/06/15 in the presence of Mr. Niranjan (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 27 1 for 30 guest rooms only at 1st to 3rd floor as above with effect from - 2rd floor as above floor floor

Issued -07/07/15—at New Delhi by.

(Dr.G.Č.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,White House Tourist Lodge,8177-78, Arakashan Road, Pahar Ganj, New Delhi- 110055.

.Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSPF	ECTION REPOR	RT			
1. Name & address of the building:- White House Tourist Lodge,817						,
1.1	ame & address of the building.	Arakashan R	load,	Pahar Ganj,Ne	w De	elhi-
		110055.				
2	Type of occupancy:-			A-1 Ground		
2.	Type of occupanty.	+ 4 Upper Floors.(30 guest rooms)				
3.	Type of case:-	Renewal				
4.	Details of previous FSC:-	No. F6/MS/DFS/GH/2012/3264 dated				
	•	07/09/2012.				
5.	Fire safety directives No	N/A				
6.	Date of inspection:- 25/06/15					
7.	Name of the inspecting officer:-	D.O. Gurmu	kh Si	ngh		
8.	Name & designation of officer	7.6 NI:	(N.I.			
	From the building side:-	Mr. Niranja	n (IVI	anager)		
	Year of construction:-	500/Jaint C	DI	(U) Dated (2/06/1	5
10.	Applicant's letter No:-	300/Joint.C	.F.L10	e (H) Dated 02	Old	Case
0.31) C	Requirement	Pro	vided at site		narks
S.No.	Minimum Standards on fire	(PSS Area)	PS:	100 m		/NMR
	Prevention and fire safety U/R 33	(1 bb Alca)	101			
1	Access to Building					
1.		N/A	6 n	atr.	MR	!
	1) Road width	N/A	N/A		N/A	
	2) Gate width				N/A	
	3)Width of internal road	N/A	N/A	A	IN/I	1
2.	Number, Width Type & Arran	gement of Exits				
	A. Number of staircases	01.37	02	No	MF)
	1. Upper floors	01 No.		2 No. MR N/A N/A		
	2. Basements	N/A	IN)	A	11/2	1
	B. Width of staircase	0.0	1.0	1.20 mtr. & MR		?
	1. Upper floors	80 cms.		cms.	IVII	
		>T/A	N/	100701000100	N/	Δ
	2. Basements	N/A	IN/	A	1 4/ 2	. 1
	C. Protection of exits	NI/A	NI/	N/A		A
	1. Fire check door	N/A			N/	
	2. Pressurization	N/A N/A	N/A N/A		N/	
	D. No. of continuous	IN/A	14/	<i>1</i> 1	14/	
	staircase to terrace	N/A	N	/Δ	N/	A
	E. Width of corridor	1 mtr.		mtr.	M	
	F. Door size	1 11111.	1.		1,1	
3.	Compartmentation	NT/A	N	/A	N/	Ά
	1) Fire check door	N/A		/A /A	N/	N 91 31
	2) Sealing of electrical shafts	N/A		/A /A	N	
	3) Fire rating of shaft door	N/A N/A		/A	N	
	4) Water curtain	N/A N/A		/A	N.	
	5) Fire Dampers	IN/A	11	/ 1 1	14/	
4.	Smoke Management System	30 ACPH		N/A		N/A
	1) Basements	20 2 20 2 2 2		Natural		
	2) Upper floors	12 ACFII		raturar		MR
5.	Fire Extinguishers					

IN

1 . 1 . 1

	1) Total numbers	10 Nos.	10 Nos.	M			
	2) Types	ABC & CO2	ABC &CO2	MR			
	3) ISI marking	Required	Provided	MR			
ó.	First-Aid Hose Reel	1					
0.	1)Total number at each	01 no.	01 no.	MR			
	floor		factorial factor				
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	5 mm.	5 mm.	MR			
7.	Automatic Fire Detection & A	larming System					
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling						
11.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor						
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	pump						
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pum	p N/A	N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump outpu	t N/A	N/A	.N/A			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual	N/A	N/A	N/A			
	stopping						
	2) Terrace level						
	a) Discharge of pump	450 LPM	450 LPM	MR			
	b) Head of pump	30 Mtr.	30 Mtr.	MR			
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump		Provided	MR			
14.	Captive Water Storage for Fi						
	1) Under ground tank	N/A	N/A	N/A			

	• • • • • • • • • • • • • • • • • • • •				
	capacity	27/4	27/1		
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
30.078	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:				

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/MS/DFS/GH/2012/3264 dated 07/09/12, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

DY. CFO (NDZ)

Lapon