GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/ MOZ/1195 FIRE SAFETY CERTIFICATE

Dated : 7/7//5

Certified that the Sea Bird Guest House located at 4229, Tel Mandi, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (02 guest rooms + reception + STD shop), 1st floor (03 guest rooms + owner's residence), 2nd floor (04ruest rooms + 01 store), 3rd floor (04 guest rooms + 01 store) and 4th floor (01 staff room + 01 store & DG set room), total 13 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/3304 dated 11/09/12. The premises was re-inspected by the officer concerned of this department on 01/07/15 in the presence of Sh. Chandar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 13 guest rooms only with effect from -------- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -7-17-15---at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333

Ole

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. letter No. 427/Joint C.P./Lic.(H) dated 22/05/2015.

2. Sh. Chandar (Manager), Sea Bird Guest House located at 4229, Tel Mandi, Pahar Gani, New Delhi

3. The Commissioner NDMC with a request to get height of the building measured and send intimation to this department. Reply of letter No. F.6/DFS/MS/GH/2008/1071 dated 25/04/2008 is still awaited.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		INCRECTION	D.E.P.	ži.				
	1. Name & address of the bu	INSPECTION Salding:	REPORT					
•	2. Type of occupancy:-	Residential, Sub Division A. 1						
	3. Type of case:-	OI. + 04 Upper floors (total 13 Guest rooms)						
	4. Details of previous FSC:-	Reflewal						
	57 57 157 GT1/2012/3304 dated							
	5 Fire safety direction 21							
	6. Date of inspection:	nspection:-						
Nome of the								
	o. Name & designation of off	icer Sn. M	Ianoj Kumar Shar	ma (ADO/CC)				
Fro	om the building side:-		h1 0 s					
	9. Year of construction:	SII. C	handar (Manager))				
	10. Applicant's letter No:-	No. 427/1	oint C.D./I: (IV)					
			omt C.P./Lic.(H)	dated 22/05/2015.				
S.N	Standards on fire	e Requirem	ont Durill	Old Case				
	Prevention and fire safety	Existing		No. of the second				
	U/R 33	Daisting	PSS	MR/NMR				
1.	Access to Building							
	1) Road width	N/A	N/A	27/				
	2) Gate width	N/A	N/A	N/A				
	3)Width of internal road	N/A	27/4	N/A				
2.	Number, Width Type & A	rrangement	N/A	N/A				
	A. Number of staircases	Tangement o	I Exits					
6	1. Upper floors	01 Nos.	0127					
	2. Basements	N/A	01 Nos.	MR				
	B. Width of staircase	IVA	N/A	· N/A				
	1. Upper floors	0.80 mtr.	0.00					
		0.80 mtr.	0.99 mtr. 12	1.03 MR				
	2. Basements	N/A	mtr.	2.71				
	C. Protection of exits		IN/A	N/A				
	1. Fire check door	N/A	N/A	221				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous	01	01	N/A				
	staircase to terrace		01	MR				
	E. Width of corridor	N/A	N/A	27/4				
	F. Door size	1 mtr.	1 mtr.	N/A				
.	Compartmentation		T IIII.	MR				
	1) Fire check door	N/A	N/A					
	2) Sealing of electrical shafts	N/A	N/A	N/A				
	3) Fina mati C 1 a 1		N/A	N/A				
	3) The rating of shaft door	N/A		1 N 1 / A				
	3) Fire rating of shaft door4) Water curtain	N/A N/A		N/A				
	4) Water curtain5) Fire Dampers	N/A	N/A	N/A				
,	4) Water curtain5) Fire DampersSmoke Management System							
	 4) Water curtain 5) Fire Dampers Smoke Management System 1) Basements 	N/A N/A	N/A N/A	N/A N/A				
	4) Water curtain5) Fire DampersSmoke Management System	N/A N/A 30 ACPH	N/A N/A	N/A N/A				
	 4) Water curtain 5) Fire Dampers Smoke Management System 1) Basements 	N/A N/A	N/A N/A	N/A N/A				

	1) Total 1			
	1) Total numbers	10 Nos.		MR
	2) Types	ABC &	CO2 ABC & (CO2 MR
6.	3) ISI marking	Required		17111
0.	Thist-Aid Hose Reel		- Taba	MR
	1) Total number of eachflo	or 01	01	MD
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
7.	3) Nozzle diameter	05		MR
/.	Automatic Fire Detection 1) Type of detectors	& Alarming	System	MR
		N/A	N/A	1374
	2) Location of main panel	NI/A	N/A	N/A
	3) Location of repeater pane	1 NI/A	N/A	N/A
	4) Alternate source of nowe	r N/A	N/A	N/A
-	3) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A		N/A
9.	Public Address System	Dogwing 1	N/A	N/A
10.	Automatic Sprinkler System	required	Provided	MR
	1) Basement	N/A	27/1	
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	IN/A	N/A	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A		
	2) Number of hydrants per		N/A	N/A
	floor	N/A	N/A	N/A
	3) Hose box	77/4		
12.	Yard Hydrants	N/A	N/A	N/A
	1) Total number of hydrants	27/		
	2) Hose box	N/A	N/A	N/A
3.	Pumping Arrangement	N/A	N/A	N/A
	1) Ground level			
	- Cana icvci	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	b) Head of main nump			IVA
	of main pulli	N/A	N/A	N/A
		N/A	N/A	N/A
	pullip out bill	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A N/A
	f) Stand by pump output	N/A	N/A	N/A N/A
	g) Stand by pump head	N/A	N/A	N/A N/A
	h) Auto starting/Manual	N/A	N/A	N/A N/A
	stopping			IVA
	2) Terrace level			
	a) Discharge of pump	180 LPM	180 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Dogwing 1	Provided	MR
	Captive Water Storage for Fire	e Fighting	TTOVIUCU	MR
	1) Under ground tank	V/A	N/A	27//
	capacity		IVA	N/A
				27.13
			M	

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
12/21	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		Tiovided	IVIK
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
17.	e) Lift signage	N/A	N/A	N/A
New York Control of the Control of t	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any:	NA		

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/3304 dated 11/09/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

20(0)

Jehn 27715