GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ MDZ 1317

Dated: 22/07/15

FIRE SAFETY CERTIFICATE

Certified that the City Height Guest House located at 4769, Main Bazar Pahar Ganj New Delhi comprised of Ground + 3 Upper Floors (Ground floor reception +1 hall, Offices, 1st to 3rd floor 13 guest rooms each floor total 39 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/2012/GH/2513 dated 12/07/2012. The premise was reinspected by the officer concerned of this department on 13/07/15 in the presence of. Mr Manoj Kumar (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 (39 guest rooms at 1st to 3rd floor) with effect from 2000 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 27/07/15—at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee, City Height Guest House 4769, Main Bazar Pahar Ganj New Delhi Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

1. Name & address of the building:- City Height Guest House 4769, Main Bazar Pahar Ganj New Delhi

Residential Group A-1 Ground+ 3 Upper Floors (39 guest rooms)

Renewal

No. F6/DFS/MS/2012/GH/2513 dated 12/07/2012.

N/A

13/07/15

D.O. Gurmukh singh

Mr. Manoj Kumar (Manager)

2010

	rppheant's letter No:-	711/Joint.	C.P./Lic. (H) Dated	1 26/06/15		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement (PSS Area)		Old Case		
1.	Access to Building					
	1) Road width	Required	0.7.6			
	2) Gate width	N/A	9 Mtr.	MR		
	3)Width of internal road	NI/A	N/A	N/A		
2.	Number, Width Type & Arr	IN/A	N/A	N/A		
	Number, Width Type & Arrangement of Exits A. Number of staircases					
	1. Upper floors	01) !	i			
	2. Basements	01 No.	01No.	MR		
	B. Width of staircase	N/A	N/A	N/A		
	1. Upper floors	1.7.7.6				
	2. Basements	1.5 Mtr.	1.5 Mtr.	MR		
	C. Protection of exits	N/A	N/A	N/A		
	1. Fire check door	27/				
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
*	staircase to terrace	N/A	N/A	N/A		
	E. Width of corridor	27/1		11/11		
	F. Door size	N/A	N/A	N/A		
	Compartmentation	1 mtr.	1 mtr.	MR		
	1) Fire check door			1,110		
,	2) Seeling of 1	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	NT/A	N/A		
4	4) Water curtain	N/A	NT/A	N/A		
0	5) Fire Dampers	N/A	>T/4			
1	Smoke Management System 1) Basements 30 A CPU					
		30 ACPH	N/A	NI/A		
	Upper floors	12 ACPH	Natural	N/A		
1	Fire Extinguishers		- ward	MR		
1	Total numbers	10 Nos.	12 Nos.	MD		
) Types	ABC & CO2	ABC, CO2 &	MR		
			ABC, COZ &	MR		

			W.CO2			
	3) ISI marking	ISI	Yes	MR		
),	First-Aid Hose Reel					
0.	1)Total number of each	01 No.	01 No.	MR		
	floor					
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	5 mm	5 mm.	MR		
7.	Automatic Fire Detection & A					
•	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
9. 10.	Automatic Sprinkler System	1 2 22 -1 2200 2 22				
10.	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	10/11				
11.	Internal Hydrants	χ.				
11.	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor	11/12	4			
		N/A	N/A	. N/A		
10	3) Hose box N/A N/A N/A Yard Hydrants					
12.	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
1.2		14/11				
13.	Pumping Arrangement 1) Ground level	N/A	N/A	N/A		
		N/A	N/A	N/A		
	a) Discharge of main	IN/A	14/11			
	pump	N/A	N/A	N/A		
	b) Head of main pump		N/A	N/A		
	c) Number of main pum	1	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head		N/A	N/A		
	f) Stand by pump outpu	N/A	N/A	N/A		
	g) Stand by pump head		N/A	N/A		
	h) Auto starting/Manual	I N/A	IV/A	11/11		
	stopping					
	2) Terrace level	450 LPM	450 LPM	MR		
	a) Discharge of pump	30 Mtr.	30 Mtr.	MR		
	b) Head of pump	COLUMN TO THE REAL PROPERTY OF THE PARTY OF	Provided	MR		
	c) Power supply	Required Required	Provided	MR		
	d) Auto starting of pum	Provided	IVII			
14.	Captive Water Storage for F	ire Fighting N/A	N/A	N/A		
	1) Under ground tank		I IV/A	IN/A		

M

. .

	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
Tigar.	d) Over head tank capacity	5,000 Ltrs.	5,000 Ltr.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
ic .	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:				

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/2012/GH/2513 dated 12/07/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

DY. CFO (NDZ)