

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/ NO2 1322

Dated: 22/07/15

FIRE SAFETY CERTIFICATE

Certified that the Maurya Assam Guest House located at 7963, Arakashan Road Road, Pahar Ganj, New Delhi comprised of Ground + 02 Upper floors, Ground floor (reception + 01 guest room), 1st floor (03 guest rooms), 2nd floor (03 guest rooms), total 07 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/2126 dated 12/06/12. The premises was re-inspected by the officer concerned of this department on 03/07/15 in the presence of Sh. Prakash Sharma (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 07 guest rooms only with effect from --22-157-1-5----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 22/07/15 at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph -011-23414333

of e Me

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

Sh. Prakash Sharmar (Manager),
Maurya Assam Guest House located at 7963, Arakashan Road Road, Pahar Ganj,
New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-N/12-

INSPECTION REPORT

1. Name & address of the building:- Maurya Assam Guest House located at

7963, Arakashan Road Road, Pahar Ganj,

New Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

Gr. + 02 Upper floors (total 07 Guest rooms)

3. Type of case:- Renewa

4. Details of previous FSC:- No. F6/DFS/MS/GH/2012/2126 dated

12/06/12.

5. Fire safety directives No.- N/A

6. Date of inspection: 03/07/15

7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

From the building side:- Sh. Prakash Sharma (Manager)

9. Year of construction:-

10. Applicant's letter No:- No. Nil dated 12/06/2015.

Old Case S.No. Minimum Standards on fire Requirement Provided at site Remarks Prevention and fire safety Existing PSS MR/NMR U/R 33 1. Access to Building 1) Road width N/A 06 mtr. N/A 2) Gate width N/A N/A N/A 3) Width of internal road N/A N/A N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 01 Nos. 01 Nos. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 0.80 mtr. 0.93 mtr. MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous N/A N/A N/A staircase to terrace E. Width of corridor N/A N/A N/A F. Door size 1 mtr. 1 mtr. MR 3. Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A Smoke Management System 4. 1) Basements 30 ACPH N/A N/A 2) Upper floors 12 a/c per Natural MR hour 5. Fire Extinguishers 1) Total numbers 08 Nos. 08 Nos. MR 2) Types ABC & CO2 ABC & CO2 MR 3) ISI marking Required Provided MR First-Aid Hose Reel 6. 1) Total number of eachfloor 01 01 MR 2) Length of hose reel hose 30 mtr. 30 mtr. MR

-11/19-

	1111			
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	& Alarming S	ystem	1
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System		14/11	IN/A
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	IVA	IN/A	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	77/1
	2) Number of hydrants per	N/A		N/A
	floor	IN/A	N/A	N/A
	3) Hose box	N/A) NT/ 4	
12.	Yard Hydrants	IN/A	N/A	N/A
	1) Total number of hydrants	N/A	27/4	
	2) Hose box		N/A	N/A
13.		N/A	N/A	N/A
13.	Pumping Arrangement	3.7/1		
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			1
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			, 1,1,1
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
4.	Captive Water Storage for Fi	ire Fighting	TTOVICE	IVIIX
	1) Under ground tank	N/A	N/A	N/A
	capacity			IN/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	
	d) Over head tank	2500 ltr.	2500 ltr.	N/A
	capacity	2500 Iti.	2500 Itr.	MR
j	Exit Signage.	Required	Droxidad	MD
	Provision of Lifts.	required	Provided	MR
		27/1		
		N/A	N/A	N/A
	shaft			
		N/A	N/A	N/A
	lobby	Second stars to		
	c) Communication in	N/A	N/A	N/A

		¥		2
	lift car			
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst Risk, if any:	NA		

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/GH/2015/1240 dated 10/06/2015 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/2126 dated 12/06/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC