GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ ND2 | 1376

Dated: 30/07/15

FIRE SAFETY CERTIFICATE

Certified that the Hotel Prince Palace located at 5117-18, Gali Thanedar Wali, Main Bazar Pahar Ganj, New Delhi comprised of Ground + 3 Upper Floors (Ground floor – reception + 07 guest rooms, 1st to 2nd floor - 09 guest rooms each floor, 3rd floor – 07 guest rooms & terrace floor 02 canteen rooms total 32 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/2012/GH/2663 dated 23/07/2012. The premise was reinspected by the officer concerned of this department on 13/07/15 in the presence of Mr. Janak Ray (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 32 guest rooms only as above with effect from --3-0-107/11------- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 30/07/15—at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,
Hotel Prince Palace
5117-18 Gali Thanedar Wali Main Ba

5117-18, Gali Thanedar Wali, Main Bazar Pahar Ganj, New

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT 1. Name & address of the building:-Hotel Prince Palace 5117-18, Gali thanedar Wali, Main Bazar Pahar Gani, New Delhi. Residential Group A-1 Ground 2. Type of occupancy:-+ 3 Upper Floors.(32 guest rooms) 3. Type of case:-Renewal No. F6/DFS/MS/2012/GH/2663 dated 4. Details of previous FSC:-23/07/2012. 5. Fire safety directives No.-N/A 6. Date of inspection:-13/07/15 7. Name of the inspecting officer:-D.O. Gurmukh Singh 8. Name & designation of officer Mr. Janak Ray (Manager) From the building side:-9. Year of construction:-10. Applicant's letter No:-618/Joint.C.P.Lic (H) Dated 15/06/15 Old Case Provided at site Remarks Minimum Standards on fire Requirement S.No. (PSS Area) PSS MR/NMR Prevention and fire safety U/R 33 Access to Building N/A N/A 1) Road width 2.0 Mtr. N/A 2) Gate width N/A N/A N/A N/A N/A 3) Width of internal road Number, Width Type & Arrangement of Exits A. Number of staircases 01 No. 01 No. MR 1. Upper floors N/A 2. Basements N/A N/A B. Width of staircase 1.27 mtr. MR 80 cms. 1. Upper floors 2. Basements N/A N/A N/A C. Protection of exits N/A N/A N/A 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A D. No. of continuous N/A staircase to terrace N/A N/A N/A E. Width of corridor MR 1 mtr. 1 mtr. F. Door size 3. Compartmentation N/A N/A N/A 1) Fire check door 2) Sealing of electrical shafts N/A N/A N/A N/A N/A N/A 3) Fire rating of shaft door N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A Smoke Management System 4. N/A N/A 30 ACPH 1) Basements Natural MR 2) Upper floors 12 ACPH Fire Extinguishers 5.

08 Nos.

MR

08 Nos.

1.

2.

1) Total numbers

M-12

	2) Types		M					
	3) ISI most:		ABC & CO	02	ADC	000	MR	
6.	First A: J. I.				Uired ABC &C Provided			
	THU THUSE REEL					d	MR	
4	1)Total number at each floor		01 no.		01			
	2) I anoth 61				01 no.		MR	
2	2) Length of hose reel hos	se	30 mtr.		20			
7.	3) Nozzle diameter				30 mtr. 5 mm.		MR	
	Automatic Fire Detection	ratolialic Fire Detection 0- 11					MR	
	1) Type of detectors	2) Locations N/A N/A						
	2) Location of main panel		N/A		N/A		N/A	
	3) Location of repeater par	- 1	N/A		N/A		N/A	
	T) Alternate source of normal		V/A		N/A		N/A	
8.	5) Hooter's Location		V/A		N/A		N/A	
9.	MOEFA		Pagui 1		N/A		N/A	
10.	Public Address System	T	Pagui 1		Provided		MR	
10.	Automatic Sprinkler System	n	quiled		Provided		MR	
	1) Dasement		/A					
	2) Upper floors		/A		N/A		N/A	
	3) Sprinkler above false		/A		N/A		N/A	
11.	Celling	11/11			N/A		N/A	
11.	Internal Hydrants							
	1) Size of riser/down-comer	N/	A					
	2) Number of hydrants non	N/A			N/A		N/A	
	11001	1 1/.			N/A		N/A	
12.	3) Hose box	N/2	4					
12.	Yard Hydrants	1 1/1	7		N/A		N/A	
	1) Total number of hydrants	N/A	1					
13.	2) Hose box	N/A		N/A			N/A	
13.	Pumping Arrangement	11/1			N/A		N/A	
	1) Ground level	N/	Λ					
	a) Discharge of main		7/A	N/A			N/A	
	Dump	11/2			N/A		N/A	
- 1	b) Head of main pump	N/A					11/21	
	c) Number of main pump	NI/A]	V/A		N/A	
	u) Jockey pump out put				N/A		N/A	
	e) Jockey pump head	N/A		1	N/A		N/A	
	f) Stand by pump output	N/A		N/A			N/A	
	g) Stand by pump head	N/A		N	N/A		N/A	
	h) Auto starting/Manual	N/A		N/A		N/A N/A		
	stopping	N/A		N	N/A		V/A	
	2) Terrace level						VA	
	a) Discharge of pump	100	Disc					
	D) Head of	180 LPM		180 LPM		N	1R	
-	C) Power and 1	30 Mtr.			Mtr.			
	d) Auto starting of my	*	equired P		Provided		MR MR	
	Captive Water Storage for Fire F	Requ	ired		ovided			
	1) Under ground tank	ightin	g			M	K	
	capacity N	J/A		N/A	4	NT	(A	
	- spacity					N/	A	

	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A			
	c) Access to tank	N/A	N/A	N/A		
1.5	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	N/A MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.		Tiovided	MR		
	a) Pressurization of lift shaft	N/A	N/A	N/A		
17	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A			
	Total area location	N/A	N/A	N/A N/A		
9.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A N/A		
0	e) Building floor plan	N/A	N/A	N/A		
0.	Special Fire Protection System for Protection of special Risk, if any:					

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/2012/GH/2663 dated 23/07/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

28-7-15

Gurmukh Singh
Divisional Officer