## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/ MO2 1373

Dated: 30/07/15

## FIRE SAFETY CERTIFICATE

Certified that the Rest Point Guest House located at 7923, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (01 guest room + reception), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (03 guest rooms at each floor), 4<sup>th</sup> floor (02 guest rooms) and Terrace floor DG set, (kitchen for staff + 01 staff room found sealed), total 12 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/3290 dated 10/09/12. The premises was re-inspected by the officer concerned of this department on 20/06/15 in the presence of Sh. Dinesh Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 12 guest rooms only with effect from - 30 so for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 30/22/15-at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph -011-23414333

ofc Mu

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. Rest Point Guest House located at 7923, Arakashan Road, Pahar Ganj, New Delhi.

3. The Commissioner NDMC with a request to get height of the building measured and send intimation to this department. Reply of letter No. F.6/DFS/MS/GH/2009/2655 dated 27/08/2009 is still awaited.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

F .				
	INSP	ECTION REPO	RT	
1.	Name & address of the building	g:- Rest Point C	Guest House located	
2.	Type of occupancy:-  Arakashan Road, Pahar Ganj, New Delhi Residential, Sub Division-A-1			
	Gr. + 04 Upper floors (total 12 Guest rooms)			
	Type of case:- Renewal			
4.	Details of previous FSC:- No. F6/DFS/MS/GH/2012/3290 dated 10/09/12.			
5	Fire safety directives No	N/A		
	Date of inspection:-	20/06/15		
	Name of the inspecting officers		Kumar Sharma (AI	)O/CC)
	Name & designation of officer	on. Island	Xumai Shaima (112	00,00)
	he building side:-	Sh. Dinesh	Kumar (Manager)	
	Year of construction:-		(	
10.	Applicant's letter No:-	No. 267/Joint C	C.P./Lic.(H) dated 1	14/05/2015. Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site PSS	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	05 feet.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arr			11/11
	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 mtr.	0.90 to 0.92 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01	01	MR
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1 mtr.	1 mtr.	MR
3.	Compartmentation			
	T		· · · · · · · · · · · · · · · · · · ·	

	1) I He elleek door	1 1/1 1	14/11	14/11
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			00
	1) Basements	30 ACPH	N/A	N/A
*	2) Upper floors	12 a/c per	Natural	MR
		hour	The state of the s	
5.	Fire Extinguishers			

N/A

N/A

N/A

1) Fire check door

	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
6	First-Aid Hose Reel				
6.	1) Total number of eachfloor	01 no.	01no.	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	5 mm.	5 mm.	MR	
7.	Automatic Fire Detection & A				
1.	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
0	MOEFA	N/A	N/A	N/A	
8.	Public Address System	Required	Provided	MR	
9.	(Inter com)	110401100			
10.	Automatic Sprinkler System				
10.	1) Basement	N/A	N/A	N/A	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling				
11.	Internal Hydrants				
11.	1) Size of riser/down-comer	N/A	N/A	N/A	
-	2) Number of hydrants per	N/A	N/A	N/A	
	floor				
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants				
12.	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement		8		
15.	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump			Tr. Andrews	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump		N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output		N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping		v v		
	2) Terrace level			- 2 2 2	
	a) Discharge of pump	NA	180 LPM	NA	
	b) Head of pump	NA	30 mtr.	NA	
	c) Power supply	NA	Provided	NA	
	d) Auto starting of pump		Provided	NA	
14.	Captive Water Storage for				
17.	1) Under ground tank	N/A	N/A	N/A	

	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	NA	1000 ltr.	NA
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	em for Protec	tion of special	NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/3290 dated 10/09/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma\S
Designation: - ADO (CC)