GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/MD2/1440

Dated: 67/98/15

FIRE SAFETY CERTIFICATE

Certified that the Millenium 2000 Dx. Guest House, located at 3695, Dariba Pan, Pahar Ganj, New Delhi comprised of Basement, Ground + 4 Upper Floors (Basement storage, Ground floor Rec. + 02 guest rooms, 1st floor to 3rd floor 10 guest rooms & 01 store room at each floor 4th floor rooms found sealed, total 32 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/2012/GH/3400 dated 18/09/2012. The premise was reinspected by the officer concerned of this department on 29/07/15 in the presence of Sh. Ramesh chhopra (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 32 guest rooms only as above with effect from - 107/15 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 07/98/15--at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,
Millenium 2000 Dx. Guest House,
3695, Dariba Pan, Pahar Ganj, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INS	PECTION REPO)RT				
1	.Name & address of the building	:- Millenium 2	2000 Dx. Guest Ho	use, located at			
2	. Type of occupancy:-	Residentia	3695, Dariba Pan, Pahar Ganj, New Delhi. Residential Group A-1 Basement, Ground				
3	. Type of case:-	Floors.(32 guest rooms)					
4		(DEG/GIJ/0010/0400 1)					
	Details of previous FSC:- No. F6/MS/DFS/GH/2012/3400 dated 18/09/2012.						
5.	. Fire safety directives No						
6.	. Date of inspection:-	29/07/15					
7.	Name of the inspecting officer:- D.O. Gurmukh Singh						
8.	Name & designation of officer						
12	From the building side:-	Sh. Ramesh Chhopra (Manager)					
	Year of construction:-	2002	pra (Manager)				
	. Applicant's letter No:-	888/Joint.C	C.P.Lic (H) Dated 1	0/07/15 Old Case			
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks			
	Prevention and fire safety	(PSS Area)	PSS	MR/NMR			
	U/R 33						
1.	Access to Building						
	1) Road width	N/A	6 mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrangement of Exits						
	A. Number of staircases						
	1. Upper floors	01 No.	01 No.	MR			
	2. Basements	01 No.	02 Nos	MR			
	B. Width of staircase						
	1. Upper floors	80 cms.	1.20 mtr. to 1.22 mtr.	MR			
	2. Basements	80 cm	1.00 mtr. &1.20 mtr.	MR			
	C. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	N/A	N/A	N/A			
	staircase to terrace		3.000	11/11			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1 mtr.	1 mtr.	MR			
3.	Compartmentation						

N/A

N/A

N/A

N/A

N/A

30 ACPH

12 ACPH

N/A

N/A

N/A

N/A

N/A

Exhaust fan

Natural

1) Fire check door

4) Water curtain

5) Fire Dampers

1) Basements

2) Upper floors

Fire Extinguishers

4.

5.

2) Sealing of electrical shafts

3) Fire rating of shaft door

Smoke Management System

1

N/A

N/A

N/A

N/A

N/A

MR

MR

	1) Total numbers	12 Nos.	12 Nos.	MR		
	2) Types	ABC & CO2	ABC &CO2	MR		
	3) ISI marking	Required	Provided Provided	MR		
6.	First-Aid Hose Reel	required	Tiovided	IVIK		
	1)Total number at each	01 no.	01 no.	MR		
	floor	or no.	or no.	IVIIX		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	5 mm.	5 mm.	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System /	Required	Provided	MR		
	Intercom	required	Trovided	IVIIC		
10.	Automatic Sprinkler System					
	1) Basement	Required	Provided	MR		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	1771	14/74	IN/A		
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor	11/11	IV/A	IV/A		
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants		14/11	IVA		
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement	14/71	IVA	IN/A		
	1) Ground level	N/A	N/A	NI/A		
	a) Discharge of main	N/A	N/A N/A	N/A		
	pump	IN/A	IN/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A N/A		
	d) Jockey pump out put	N/A	N/A	N/A N/A		
	e) Jockey pump head	N/A	N/A N/A	N/A N/A		
	f) Stand by pump output	N/A	N/A N/A			
	g) Stand by pump head	N/A	N/A N/A	N/A		
	h) Auto starting/Manual	N/A	N/A N/A	N/A		
	stopping	IV/A	IN/A	N/A		
	2) Terrace level					
	a) Discharge of pump	450 LPM	450 I DM	MD		
			450 LPM	MR		
	1 1	30 Mtr.	30 Mtr.	MR		
	c) Power supply d) Auto starting of pump	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		

- N-19

	1) Under ground tank	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	5,000 ltrs.	5,000 ltrs.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
13	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:				

The fire protection system provided in the guest house were tested, checked at random

and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/2012/GH/3400 dated 18/09/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer