GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2015/ W2 / 1443

Dated: 10 /08 /2015

FIRE SAFETY CERTIFICATE

Certified that Narindra Fabrication Industries Pvt. Ltd. at Plot No. H-50, Udyog Nagar Industrial Area, Rohtak Road, New Delhi-41 comprised of Ground Floor, Mezzanine Floor and First Floor only owned and occupied by Narindra Fabrication Industries Pvt. Ltd., was issued Fire Safety Certificate vide letter No. No.F6/DFS/MS/BP/87/2061 dated 23.12.1987. The Premises was re-inspected by the officer concerned of Fire Service on 09.07.2015 in the presence of Mr.Sanjeev Kumar and found that building / premises have deem complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building / premises is fit for occupancy class **Industrial Group (G)** with effect from 10 / 58 /2015 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010. 2010.

Issued on 10 08 115 at New Delhi by.

(SANTOKH SINGH) CHIEF FIRE OFFICER. Phone No.-23414250.

Copy to :-

1. Sh. Sanjeev Kumar, Narindra Fabrication Industries Pvt. Ltd., Plot No.H-50, Udyog Nagar Industrial Area, Rohtak Road. New Delhi-41

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on www.dfs.delhigovt.nic.in

1119 **INSPECTION REPORT**

1. Name & address of the building: Narindra Fabrication Industries Pvt. Ltd., Plot No.

H-50, Udyog Nagar Industrial Area, Rohtak Road, New Delhi-41

Type of Occupancy

: Industrial

Plot Area – 1052m²

Type of Case

: Renewal

(GF, Mezz. Floor & 1st Floor)

Details of previous NOC

: No.F6/DFS/MS/BP/87/2061 dated 23.12.1987

Fire Safety directives Letter No.: F6/DFS/MS/BP/85/565 dated 13.06.1985

Date of inspection

: 09/07/2015

Name of the Inspecting Officer: A. K.-Jaiswal

8. Name and designation of Officer

from the building side

: Mr. Sanjeev Kumar

9. Year of Construction

: 1986-87

10. Applicant's letter No. :-Nil

S No	Minimum standards on fire prevention and fire safety U/R 33			Provided at site		Remarks MR/NMR			
1.	Access of building								
0.00	Road width	06 mtr		15 mtr.		MR			
	Gate width	• Gate width 5 mtr		Provided		MR			
	Width of internal road	3 mtr.		Provided		MR			
2.	Number, width, Type & Arran	gements of exits	5						
	a. Number of staircases								
	Upper floors	1 (As per sanctione) 2		MR				
	Basements	No Basement No B		Basement	No	Basement			
	b. Width of staircases								
	Upper floors	1.20	Provided		MR				
	• Basements	N/A	N/A		N/A				
	c. Protection of exits								
	Fire check door	N/A		N/A		N/A			
	Pressurization	N/A		N/A		N/A			
	d. No of continuous	As per sanctioned		1		MR			
	staircase to terrace	plan							
	e. Width Of Corridor	N/A		N/A		N/A			
	f. Door Size	1.20 mtr.	Provided		MR				
3.	Compartmentation								
	Fire check door	N/A		N/A		N/A			
	Sealing of electrical shafts	Required		Provided		MR			
	Fire Rating of shaft door	N/A N/A		N/A		N/A			
	Water Curtain			N/A		N/A			
	Fire Dampers	N/A		N/A		N/A			
4.	Smoke managements System			S. Jako -	0.6351				
	Basements	No Basement No B		Basement No		Basement			
	Upper floors	Required		Provided		MR			
5.	Fire Extinguishers								
	• Total numbers	10	- 14	15		MR			

	The Hose Kee	ls		-	-			
	 Total numbers 	on	2	-				
	each floor		*			Provided		MR
	 Length of hose 	reel	30Mtr.	30Mtr				
	hose		o o tricir.	SOIVILI.		Provided		MR
Nozzle diameter		er	5mm.		Dravit			
7.	- recomand the detection	n and	l alarming great			Provided		MR
	or detecto	1	N/A	ystem				
 Location of Mai 			in N/A			V/A		N/A
	Panel					V/A		N/A
• Location of		eater	N/A	N/A		N/A		
	Panel					V/A		N/A
	 Alternate source 	of	N/A					
	power supply	oply		17/4		N/A		N/A
	Hooters' Location							
8.	MOEFA			N/A N,		I/A		N/A
9.	Public Add		N/A		N/A			
10.	Public Address System Automatic Sprinkler System		N/A		-	V/A		V/A
	Basements	em		the second secon	14/			V/A
	Upper Floor		N/A		N/A	N/A		1/0
	• Sprinkler -1		N/A		N/A	11/4		/A
	 Sprinkler above fal ceiling 	lse	se N/A		N/A			/A
11							IN.	/A
11.	Internal Hydrants					and the same of th		
	• Size of riser/down-comer		N/A		1			
					N/A		N/	A
	 Number of hydrants 	N	I/A		NI/A			
	per floor				N/A		N/	4
	 Hose Box 	N	/A		N/A			
12. Y	ard Hydrants				IV/A		N/A	
	• Total number of		1					
	hydrants	N/	/A		N/A		N/A	
	 Hose Box 	NI /	٨				,,,	
13. Pu	imping Arrangements	N/	A		N/A		N/A	
• (round Level	N/A	٨					Andrew Control of the
• [Discharge of main pump	N/A						The second secon
	lead of main pump	N/A			N/A			
- N	lumber of main pumps	N/A			I/A		N/A	
Jockey pump out put N//		N/A		N/A		N/A		
> Jo	ockey pump head	N/A		N/A N/A		N/A		
> St	tandby Pump out put	N/A		The same of the sa			N/A	
- St	Standby Pump Head N/			N/A N/A		N/A		
Al	uto Staring/Manual	N/A		-	COLUMN TO SERVICE AND ADDRESS OF THE PARTY O		N/A	
stopping Pump House According				N/A		N/A		
Pump House AccessTerrace level		N/A		N/A		N/A		-
					West Street Street or Street 1979		, V/ A	
Head of the		The same of the same of	t/min.	nin. Provided		MR		
Power supply			0 mtr.		Provided		MR	
		Requi	red		vided		ИR	
1. Capti	to starting of pump	Requi	red		vided		1R	The state of the s
Capir	ve water Storage for fire fig	ghting				10	711	
	Underground tank capacity	50,000 I guidelin	ts. (As per	Prov	vided	I N	1/R	manufactor and property
>							1	
	or connection	Not Rec	quired as per	ND	and the state of t	TABLE AND A STREET STREET, AND ASSESSED ASSESSED.	-	14.04.11.014

		NIB					
1:	- I Shage	Required					
16	- ISIOII OI LIIIS		Provided	M/R			
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of lift lobby	N/A	N/A	N/A			
	Communication in lift		N/A	N/A			
	Fireman's Grounding Switch	N/A	N/A	N/A			
17.	Lift SignageStandby power supply	N/A	N/A	N/A			
18.	Refuge Area	required	Provided	MR			
	> Total area	N/A	N/A	1711(
	> Location	N/A	N/A	N/A			
19.	Fire control room	N/A	N/A	N/A			
	Detector system panelFlow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
	Building Floor Plans	N/A	N/A	N/A			
20.	Special Fire Protection	N/A	N/A	N/A			
	Systems for Protection of special Risks, if any;	N/A	N/A	N/A			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. No.F6/DFS/MS/BP/87/2061 dated 23.12.1987 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)