GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ NO2/1477

Dated: 14/ 58/15

FIRE SAFETY CERTIFICATE

Certified that the Paramount Guest House located at 4230, Tel Mandi, Pahar Ganj, New Delhi comprised of Ground + 02 Upper floors, Ground floor (Reception + 01office + 12 guest rooms), 1st floor (08 guest rooms) and 2nd floor (06 guest rooms +DG set + temp. Shed for servant), total 26 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/3525 dated 25/09/12. The premises was re-inspected by the officer concerned of this department on 31/07/15 in the presence of Sh. Virendar Arora (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division A-1 as above 26 guest rooms only with effect from -1-4/158/15------ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 14/08/15---at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333

Copy to:-

The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. No. 775/Joint C.P./Lic. (H) dated New Delhi 08/07/2015

2. Sh. Virendar Arora (Owner),
Paramount Guest House located at 4230, Tel Mandi, Pahar Ganj, New Delhi
Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

1	Ī	NSPECTION RE	PORT			
1	. Name & address of the build			e located at 422		
2	Tel Mandi Pahar Cari N. D. II.					
2	. Type of occupancy:-	Reside	ential, Sub Division	-A-1		
	Type of a	Gr. + 02 U	pper floors (total 26 C	Suest rooms)		
_	3. Type of case:-	Renewal				
	4. Details of previous FSC:- No. F6/DFS/MS/GH/2012/3525 dated					
5	Fire cofoty dinasting N	25/09/12				
6	Fire safety directives No	N/A				
7	Date of inspection:	31/07/15				
Q Q	. Name of the inspecting office	cer:- Sh. Man	oj Kumar Sharma (ADO/CC)		
From	. Name & designation of office the building side:-	cer				
0	Von of anatative	Sh. Vire	ndra Arora (Owner	(Owner)		
10	Year of construction:- Applicant's letter No:-					
10	. Applicant's letter No:-	No. 775/Joint (C.P./Lic. (H) dated New	Delhi 08/07/2015		
S.No.	Minimum Standards on fire			Old Case		
~1110.	Prevention and fine and	Requirement	The art of Ditte	Remarks		
	Prevention and fire safety U/R 33	Existing	PSS	MR/NMR		
1.	Access to Building					
	1) Road width	N/A	02 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3) Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Al	rangement of F	exits	IVA		
	A. Number of staircases	8				
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A			
	B. Width of staircase		14/11	N/A		
	1. Upper floors	0.80 mtr.	1.15 mtr.	MD		
		and and	1.13 mu.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits			IN/A		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace			IVIK		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
	Compartmentation		T HILL.	IVIK		
	1) Fire check door	N/A	N/A	21/4		
	2) Sealing of electrical shafts	N/A	N/A N/A	N/A		
	3) Fire rating of shaft door	N/A		N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
	Smoke Management System	11/14	N/A	N/A		
	1) Basements	20 A CDII	NI/A			
-	2) Upper floors	30 ACPH 12 a/c per	27 . 1	N/A		
	-) - bber 110012	1/ 2/c ner	Natural Ventilation	MR		

5.	Fire Extinguishers					
	1) Total numbers	12 Nos.	12 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling			1,111		
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor		And the state of t	W. 100 M 100		
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump					
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping					
	2) Terrace level			1 1		
	a) Discharge of pump	225 LPM	225 LPM	MR		
	b) Head of pump	30 mtr	30 mtr	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fi	re Fighting				
	1) Under ground tank	N/A	N/A	N/A		

	capacity			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		Trovided	IVIIX
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
-	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any:	m for Protect	ion of special	NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/3525 dated 25/09/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)