GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/MD2/1472

Dated: 14/08/15

FIRE SAFETY CERTIFICATE

Certified that the "Rama Deluxe" Guest House, 8488, Arya, Nagar, Pahar Ganj, New Delhi comprised of Ground + 4 Upper Floors (Ground floor Rec. +03 guest rooms, 1st floor to 3rd floor 07 guest rooms at each floor 4th floor 05 guest rooms +Pantry for staff total 29 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/2012/GH/2746 dated 27/07/2012. The premise was re-inspected by the officer concerned of this department on 06/08/15 in the presence of Mr. Sohan (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 29 guest rooms only as above with effect from -14-1-08-1/11 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 14/58/15 at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,
"Rama Deluxe" Guest House,
8488, Arya, Nagar, Pahar Ganj, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

- N-12

INSPECTION REPORT

1.Name & address of the building:-

"Rama Deluxe" Guest House, 8488, Arya.

Nagar, Pahar Ganj, New Delhi.

2. Type of occupancy:-

Residential Group A-1 Ground + 4 Upper Floors.(29 guest rooms)

3. Type of case:-

Renewal

4. Details of previous FSC:-

No. F6/MS/DFS/GH/2012/2746 dated

27/07/2012.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

06/08/15

7. Name of the inspecting officer:-

D.O. Gurmukh Singh

8. Name & designation of officer From the building side:-

Mr. Sohan (Manager)

9. Year of construction:-

2001

10. Applicant's letter No:-

1073 Joint C.P./Lic.(H) dated 27.07.2015

Old Case Remarks Requirement Provided at site Minimum Standards on fire S.No. MR/NMR PSS (PSS Area) Prevention and fire safety U/R 33 Access to Building 1. MR N/A 04 mtrs 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3) Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 01 No. 01 No. 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase 1.20 Mtr.. MR 80 cm. 1. Upper floors N/A N/A N/A 2. Basements C. Protection of exits N/A N/A N/A 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace N/A N/A N/A E. Width of corridor MR 1 mtr. 1 mtr. F. Door size Compartmentation 3. N/A N/A N/A 1) Fire check door N/A N/A 2) Sealing of electrical shafts N/A N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers Smoke Management System 4. N/A 30 ACPH N/A 1) Basements MR Natural 2) Upper floors 12 ACPH Fire Extinguishers 5. MR 10 Nos. 10 Nos. 1) Total numbers ABC &CO2 MR ABC & CO2 2) Types

					1.4	MR		
3) ISI marking R		Requ	iired	Provided		IVIIC		
LITT	ose Reel		01 N		MR			
6. First-Aid Ho	ber at each	01 N	lo.	01 N	0.	1411		
1)Total number at each floor				20 4		MR		
2) Length of hose reel hose		30 mtr.		30 mtr.		MR		
2) 31 1- 1	a) I la diameter		5 mm.		5 mm.		IVIIC	
	Fire Detection & Al	larmi	ng System	>T/A		N/A	A	
7. Automatic	1) Type of detectors		N/A		N/A		N/A	
2) Location	2) Location of main panel		N/A		N/A		N/A	
2) Location	3) Location of repeater panel		N/A		N/A		N/A	
4) Alternat	4) Alternate source of power		N/A		N/A		N/A	
5) Hooter'	5) Hooter's Location		N/A		N/A		MR	
			Required		Provided		MR	
8. MOEFA	dress System/	Required		Pro	Provided		IX	
9. Public Add	aress e y = -							
	Sprinkler System			1		N	/ ^	
1) Pagement	10. Automatic Sprinkler System 1) Basement		N/A		N/A		N/A N/A	
2) Upper	floors	N/	N/A		N/A		N/A N/A	
2) Opper	ler above false	N/	N/A		A	IN/A		
3) Sprink	ici above imi		¥					
1 T	ceiling 11. Internal Hydrants						N/A	
11. Internal I	11. Internal Hydrams1) Size of riser/down-comer		N/A		N/A		N/A	
1) Size 0	2) Number of hydrants per			N/A		IN/A		
					77/4		N/A	
floor 3) Hose box N/A				N/A		IN/IX		
1 7 7	drants			- 1		1	N/A	
12. Yard Hydrants1) Total number of hydrants		s N/A		N/A				
1) Total	hov		N/A	N	I/A	-	N/A	
2) Hose	~ Arrangement						>T/A	
13. Pumpin	g Arrangement		N/A		N/A		N/A	
1)	Ground level		N/A		N/A		N/A	
a)	Discharge of main				*		NI/A	
b) Head of main pump c) Number of main pur		2	N/A		N/A		N/A	
				N/A			N/A	
	Number of main pe	nit	1		N/A		N/A	
<u>d)</u>	e) Jockey pump head f) Stand by pump outp g) Stand by pump head		N/A		N/A		N/A	
					N/A		N/A	
			N/A	N/A			N/A	
			N/A		N/A		N/A	
h)	Auto starting/Man	luai	11/12					
	stopping						1	
2) Terrace levela) Discharge of pumpb) Head of pump		n	225 LPM		225 LPM		MR	
		30 Mtr.		30 mtr.			MR	
			Required		Provided		MR	
0,	c) Power supply			Turred D · 1		3 (T)		
	Power suppry		Deguired		and the second s			
C)	Auto starting of r	ump	Required		Y			
c)	Auto starting of prive Water Storage for	or Fir	e Fighting		N/A		N/A	
14. Capt	Auto starting of r	or Fir		9	N/A		N/A	

	a) Draw-off connection	N/A	N/A	N/A		
	a) Draw-off connection b) Fire service inlet	N/A	N/A	N/A		
		N/A	N/A	N/A		
d) Over head tank		2,500 ltrs.	2,500 ltrs.	MR		
1.7	capacity Exit Signage.	Required	Provided	MR		
15.	Provision of Lifts.	1				
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
10.	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
17.	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	-	N/A	N/A	N/A		
	c) PA system panel d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A N/A		
20.	Special Fire Protection System for Protection of special Risk, if any:					

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/2012/GH/2746 dated 27/07/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer