GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/2015/CNG/ 52/1533

Dated:

21/08/15

FIRE SAFETY CERTIFICATE

Certified that M/s Bhai Oil Petrol Pump located at Nizamuddin West, New Delhi-110013 owned/occupied by Bhai Oil Petrol Pump was granted NOC by this department vide letter No. F.5/3A/DFS/2005/135 dated 01-04-2005. The patrol pump was re-inspected by the officer concerned of this department on 12-08-2015 in presence of Mr. Raghubir Singh, Manager and found that the said fuel station have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010, and that the building/premises is fit for occupancy class J (Hazardous) with effect from The Service Rules 2010 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 2/08/15 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

5:
1. The Manager, Bhai Oil Patrol Pump, Nizamuddin West, New Delhi-110013.

2. The Joint C.P.(Lic.), Police Station, Defence Colony, 1st floor, New Delhi..

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time.
- b. Loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- c. The trained fire fighting staff should be available round the clock.
- d. Good house keeping shall be ensured.
- e. Nothing contravention of the Explosive act-1984 & Rules their under 1983 and static & mobile pressure vessels (unfired) Rules-1981 as modified up to date and the comments of Chief Controller of Explosive should be permitted/followed.
- f. No trade susceptible to cause ignition to Patrol/Diesel by generating heat, mechanical/electrical spark, shall be allowed within the licensed premises.
- g. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building :Bhai Oil Patrol Pump, Nizamuddin West, New Delhi-110013

2. Type of Occupancy

: Hazardous (Class - J)

3. Type of Case

: Renewal

4. Details of previous NOC

: F.5/3A/DFS/2005/135 dated 01-04-2005

5. Fire Safety directives letter No : F.5/(3A)/DFS/2003/683 dated 07/11/2003

6. Date of inspection

: 12.08.2015

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

from the building side

: Mr. Raghubir Singh, Manager

9. Year of Construction

: 2000-01

10. Applicant's letter No.

: nil dated 28.07.2015

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road width	06 mts	Provided	MR	
	Gate width		Directly accessible from the road	MR	
	Width of internal road	N/A	N/A	N/A	
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	-	-		
	• Upper Floors	N/A	N/A	N/A	
	• Basements	N/A	N/A	N/A	
	b. Width of staircases			-	
	• Upper Floors	N/A	N/A	N/A	
	• Basements	N/A	N/A	N/A	
	c. Protection of exits				
	Fire check door	N/A	N/A	N/A	
	 Pressurization 	N/A	N/A	N/A	
	e. No. of continuous staircases to terrace				
	g. Width of Corridor	N/A	N/A	N/A	
ì	h. Door Size	N/A	N/A	N/A	
	Compartmentation.				
	Fire check door	N/A	N/A	N/A	
	Sealing of electrical shafts	N/A	N/A	N/A	
	Fire Rating of shaft door	N/A	N/A	N/A	

		NY/A	N/F	
Water Curtain	N/A		N/A	
• Fire Dampers	N/A	N/A	***	
Smoke Management System.			> 7 / 4	
 Basements 	30 a/c per hour	N/A	N/A	
 Upper floors 	12 a/c per hour	N/A	N/A	
Fire Extinguishers				
angui salaisti tura ann an achdaile an ann achdaile ann an	14	Provided	MR	
• Types		Provided	MR	
	151 marked	Provided	MR	
First-Aid Hose Reels.			D.T./ A	
	45 m		N/A	
			N/A N/A	
Nozzle diameter	3 111111	11/71		
	system.	2.11	NT/A	
	N/A	N/A	N/A	
20, 50	N/A	N/A	N/A	
	N/A	N/A	N/A	
Location of Repeater Panel		•	NI/A	
Alternate source of power	N/A		N/A	
Hooters' Location	N/A	N/A	N/A	
	N/A	N/A	N/A	
2 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	N/A	N/A	N/A	
Public Address System.				
	N/A	N/A	N/A	
			N/A	
1 1	N/A			
• Sprinkler above false certifig	N/A	N/A	N/A	
Internal Hydrants				
Size of riser/down-comer	N/A	N/A	N/A	
 Number of hydrants per floor 	N/A	N/A	N/A	
Hose Box	N/A	N/A	N/A	
Vord Hydrants				
	N/A	N/A	N/A	
 Hose Box 	N/A	N/A	N/A	
	• Fire Dampers Smoke Management System. • Basements • Upper floors Fire Extinguishers • Total numbers • Types • IS marking First-Aid Hose Reels. • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarming • Type of detectors • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. • Basement • Upper Floor • Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants. • Total number of hydrants	• Fire Dampers Smoke Management System. • Basements • Upper floors Fire Extinguishers • Total numbers • Types • IS marking First-Aid Hose Reels. • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarming system. • Type of detectors • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. • Basement • Upper Floor • Sprinkler above false ceiling N/A Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor N/A • Hose Box N/A Vard Hydrants. • Total number of hydrants N/A N/A N/A N/A N/A N/A N/A N/	• Water Curtain • Fire Dampers N/A N/A N/A N/A N/A N/A N/A N/	



	Pumping Arrangements.			
	Ground Level	-	-	_
1	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual stopping	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace level	-	_	_
	Discharge of pump	N/A	N/A	N/A
	➤ Head of the pump	N/A	N/A	N/A
58	Power Supply	N/A	N/A	N/A
	> Auto Starting of pump	N/A	. N/A	N/A
14	Captive Water Storage for fire fighting.			
	Underground tank capacity	N/A	N/A	N/A
	Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	N/A	N/A	N/A
15	Exit Signage.	N/A	N/A	N/A
16	Provision of Lifts.			1
	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	N/A	N/A	N/A
	Fireman's Grounding Switch	N/A	N/A	N/A
	• Lift Signage	N/A	N/A	N/A
17	Standby power supply	N/A	N/A	N/A
18	Refuge Area.			



	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room	-		. A
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	 Building Floor Plans 	N/A	N/A	N/A
20	Special Fire Protection Systems for	Required	Provided	MR
	Protection of special Risks, if any:			

The fire protection systems such as "No Smoking" sign board, fire extinguishers, sand buckets etc. provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.5/3A/DFS/2005/135 dated 01-04-2005, renewal under the Delhi Fire Service Act-2007 & Rules-2010 is recommended.

Accordingly DFA is put up for signature please.

DOGSE

17/8/15

M.K.CHATTOPADHYAY Asstt. Div. Officer (M.Road)