GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:-011-23414333

No. F.6/DFS/MS/GH/2015/ 52/1532

Dated: 21/08/15

FIRE SAFETY CERTIFICATE

Certified that M/s. R.K.G. Divine Inn Guest House located at 7 B, Taimoor Nagar, Maharani Bagh, New Friends Colony, New Delhi comprised of basement, ground and three upper floors was granted Fire Safety Certificate by this department vide letter No. F6/DFS/MS/GH/2012/2204 dated 20.06.2012. The premises was re-inspected by the officer concerned of Delhi Fire Service on 14.08.2015 in presence of Mr. Ravinder Kumar Gupta, Director of the guest house and observed that the management have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class residential (Guest house) with effect from 21 38 15 for a period of 03 years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 2/8/15 at New Delhi by

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Manager, M/s. R.K.G. Divine Inn Guest House, 7 B, Taimoor Nagar, Mahar Bagh, New Friends Colony, New Delhi.

2. The Joint C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

Conditions for the validity of fire safety certificate

a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.

b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.

c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s. R.K.G. Divine Inn Guest House, 7 B, Taimoor Nagar,

Maharani Bagh, New Friends Colony, New Delhi

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2012/2204 dated 20.06.2012

5. Fire Safety directives letter No: Nil

6. Date of inspection

: 14.08.2015

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M. Road)

8. Name and designation of officers

from the building side

: Mr. Ravinder Kumar Gupta, Director

9. Year of Construction

: 2011

10. Applicant's letter No.

: nil dated 24.07.2015

R.K.G. Divine Inn is comprised of basement, ground and three upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	 Road width 	06 mts	Provided	MR	
	Gate width		Directly accessible from the road	MR	
	Width of internal road	N/A	N/A	N/A	
	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	-	-	-	
	Upper Floors	02	02	MR	
	• Basements	02	02	MR	
	b. Width of staircases	-	-	_	
	• Upper Floors	1.25 mts	1.25 mts, 0.76 mt	MR	
	• Basements	1.25 mts	1.25 mts, 1.10 mts	MR	
	c. Protection of exits	_	_	-	
	Fire check door	Required	Provided	MR	
	 Pressurization 	N/A	N/A	N/A	
	e. No. of continuous staircases to terrace	02	02	MR	
	g. Width of Corridor	1.25 mt	Provided	MR	
	h. Door Size	1.0 mt	Provided	MR	
	Compartmentation.			The second secon	
	Fire check door	Required	Provided	MR	

N	12	
---	----	--

		MI		
	Sealing of electrical shafts	Required	Provided	MR -
	 Fire Rating of shaft door 	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	• Fire Dampers	N/A	N/A	N/A
	Smoke Management System.			
	Basements	30 a/c per hour	Provided	MR
	• Upper floors	12 a/c per hour	N/A	N/A
	Fire Extinguishers			
	Total numbers	16	Provided	MR
	• Types	ABC, CO_2	Provided	MR
	IS marking	ISI marked	Provided	MR
	First-Aid Hose Reels.			
	Total numbers on each floor	01	Provided	MR
	 Length of hose reel hose 	30 m	Provided	MR
	 Nozzle diameter 	5 mm	Provided	MR
7	Automatic fire detection and alarming	g system.		
	Type of detectors	Smoke/Heat	Provided	MR
	 Location of Main Panel 	Ground Floor	Provided	MR
	 Location of Repeater Panel 	N/A	N/A	N/A
	Alternate source of power	Required	Provided	MR
	Hooters' Location	Each Floor	Provided	MR
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.		-9	
10	Basement	Required	Provided	MR
	Upper Floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-comer	100 mm	Provided	MR
	Number of hydrants per floor	01 No.	Provided	MR
	• Hose Box	01 No.	Provided	MR

N٦		
1	-	1
	•	1

12	Yard Hydrants.			1980-1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1981 - 1		
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	Standby Pump Head	N/A	N/A	N/A		
	Auto Starting/ Manual stopping	N/A	N/A	N/A		
	Pump House Access	N/A	N/A	N/A		
	Terrace level					
	Discharge of pump	900 LPM	Provided	MR		
	Head of the pump	40 mts	Provided	MR		
	Power Supply	Required	Provided	MR		
or the second second second	Auto Starting of pump	Required	Provided	MR		
4	Captive Water Storage for fire fighting.					
	Underground tank capacity	N/A	N/A	N/A		
	Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	N/A	N/A	N/A		
	> Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	5,000 lts	Provided	MR		
5	Exit Signage.	Required	Provided	MR		
<u></u>	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	Required	Provided	MR		
	• Fireman's Grounding Switch	Required	Provided	MR		

		N-14		
a digentina di	Lift Signage	Required	Provided	MR
17	Lift Signage Standby power supply	Required	Provided (140 KVA)	MR
18	Refuge Area.			and the second s
	> Total Area	N/A	N/A	N/A
	Location	N/Λ	N/A	N/A
10	Fire Control Room			and the second s
19	Detector System Panel	Required	Provided	MR
	Flow Switch PanelPA System PanelBatter backup	N/A	N/A	N/A
		Required	Provided	MR
		N/A	N/A	N/A
		N/A	N/A	N/A
20	 Building Floor Plans Special Fire Protection Systems for Protection of special Risks, if any: 	Required	02 ABC type fire extinguisher found provided near elect. panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2012/2204 dated 20.06.2012, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

20(82) 17/8/15 Who: 52/1/

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (M.Rd)