GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

Fax:-011-23412593 No. F.6/DFS/MS/GH/2015/ HD2/957 E-mail ID: cfohq.dlfire@ nic.in Dated:

09/06/15

FIRE SAFETY CERTIFICATE

Certified that the M/s Hotel Kochar Continental located at 59/28, New Rohtak Road, Karol Bagh, New Delhi-110005 comprises of Basement, Ground floor + Four Upper floors, using basement as hall/storage, Ground floor as reception, office and one guest room, first, second & third floor each having six guest rooms and two rooms for personal use respectively (Total 19 guest rooms) and a pantry for staff with one staff room in temporary shed on fourth floor was granted NOC by this department vide letter No.F.6/DFS/MS/GH/2012/3006 dated 17-08-2012. The premises was reinspected by the officer concerned of this department on 03-06-2015 in the presence of Mr. Hari Singh Kochar (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 Guest House for 19 guest rooms with effect from ---49/06/-2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on oslocity at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph-011-23414333

Copy to:-

1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049 w.r.t. letter No. 286/Joint C.P./Lic.(H) dated New Delhi 18-05-2015

2. Mr. Hari Singh Kochar (Owner), M/s Hotel Kochar Continental, 59/28, New Rohtak Road, Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

-		CCTION REPORT		
	1. Name & address of the building	: M/s Kochar Contine	ental, 59/28. New R	ohtak Road, Karol
	and an analysis of the ballaning	Bagh, New Delhi-11		
	2. Type of Occupancy	: Residential (G.H) B		uest rooms-19
	3. Type of Case	: Renewal	O.	
	4. Details of Previous NOC	: F.6/DFS/MS/GH/20	12/3006 dated 17/	/08/2012
	5. Fire Safety directives letter No	: N/A		
	6. Date of inspection	: 03/06/2015		
	7. Name of Inspecting Officer	: Dy. C.F.O Rajesh Pa	nwar	
	8. Name and designation of officers			
	From the building side	: Sh. Hari Singh Koch	ar (Owner)	
	9. Year of Construction	2006-07		0= /004=
C N	10. Applicant's letter No.	: 286/Joint C.P/Lic (F		
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	on NBC/BBL Requirement	Provided at site special area	Remarks MR/NMR
1.	Access to building			
	Road width	Accessible	30 mtr	MR
	Gate width	NA	NA	NA
	Width of internal road	NA	NA	NA
2.	Number, Width, Type & Arrangemen	nt of Exits		
	a. Number of staircases			
	 Upper Floors 	One	One	MR
	• Basements	One	One	MR
	b. Width of staircases			
	Linnar Floor	125 cms	125 cms	MR
	Upper FloorBasements	125 cms	150 cms	MR
	Dasements			
	c. Protection of exits	NA	NA	NA
	Fire check door	NA	NA	NA
	 Pressurization 	11/1	11/1	14/1
	d. No. of continuous staircases to	Ona	Ona	MD
	terrace	One	One	MR
	e. Width of Corridor	1.0 Mtr	1.25, 1.90 Mtr	MR
	f. Door Size			
	I. Door Size	1.0 Mtr.	86cm X 235 cm	MR, Old Case
3.	Compartmentation			
	Fire check door	NA	NA	NA
	 Sealing of electrical shafts 	NA	Sealed	MR
	Fire Rating of shaft door	NA	NA	NA
	Water Curtain			
	Fire Dampers	NA NA	NA NA	NA NA
4.	Smoke Management System	INA	INA	INA
-T•		20 A CDII	Exhaust Fans are	MD
	 Basements 	30 ACPH	provided	MR
	a Unper floors	12 ACPH	Natural	MR
	Upper floors	12 ACI II	Ventilation	
5.	Fire Extinguishers			3
J.	Total numbers	Two at each floor	Provided	MR
	• Types	ABC, Water Co2	Provided	MR
	IS marking			
		ISI marked	ISI marked	MR
6.	First-Aid Hose Reels		D '11'	100
	Total numbers on each floor	One	Provided	MR
	• Length of hose reel hose	30 m 5 mm	Provided	MR
	Nozzle diameter	JIIIII	Provided	MR

	Automatic fire detection and alarming sy			
	Type of detectors	NA	NA	NA
	Location of Main Panel	NA	NA	NA
	Location of Repeater Panel	NA	NA	NA
	Alternate source of power	NA	NA	NA
		NA NA	NA	NA
	Hooters' Location	Required	Provided	MR
9.	MOEFA Public Address System	Required	Provided	MR
0.	Automatic Sprinkler System	required	110,144	2100
	Basement	Required	Provided	MR
		NA	NA	NA
	Ground Floor	NA	NA	NA
	 Sprinkler above false ceiling 			= "
11.	Internal Hydrants			
	Size of riser/down-comer	NA	NA	NA
	 Number of hydrants per floor 	NA	NA	NA
	Hose Box	NA	NA	NA
2.	Yard Hydrants			
	 Total number of hydrants 	NA	NA	NA
	Hose Box	NA	NA	NA
13.	Pumping Arrangements			
	Ground Level			
	Discharge of main Pump	NA	NA	NA
	> Head of Main pump	NA	NA	NA
	> Number of main pumps	NA	NA	NA
	> Jockey Pump out put	NA	NA	NA
	Jockey pump headStandby Pump out put	NA	NA	NA
	> Standby Pump Head	NA	NA	NA
	> Auto Starting/Manual	NA	NA	NA
	Stopping	NA	NA	NA
	Pump House Access	INA	INA	IVA
	Terrace level	450 7 77 6	450 X DV 5	N/D 0110
	Discharge of pump	450 LPM	450 LPM	MR, Old Case
	Head of the pump	30 M	30 M	MR
	Power Supply	Required	Provided	MR
	Auto Starting of pump	NA	NA	NA
14.	Captive Water Storage for fire fighting			
	Underground tank capacity	NA	NA	NA
	> Draw-off connection	NA	NA	NA
	Fire service inlet	NA	NA	NA
	Access to tank	NA	NA	NA
	Overhead Tank capacity	5000 ltr	5000 ltr	MR, Old Case
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
10.	Pressurization of Lift Shaft	NA	NA	NA
	Pressurization of Lift Inaby	NA	NA	NA
	Communication In lift Car	Required	Provided	MR
	Fireman's Grounding Switch		Provided	MR
	Lift Signage	Required		
		Required	Provided	MR

17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area.					
	> Total Area	NA	NA	NA		
	Location	NA	NA	NA		
19.	Fire Control Room					
	Detector System Panel	NA	NA	NA		
	• Flow Switch Panel	NA	NA	NA		
	PA System PanelBatter backup	NA	NA	NA		
	Jacket Backup	NA	NA	NA		
	Building Floor Plans	NA	NA	NA		
20.	Special Fire Protection System for Protection of special Risks, if any:	NA	NA	NA		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2012/3006 dated 17.08.2012 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting

Name:- Rajesh Panwar

Designation:- Dy. C.F.O (NDZ)

Signature of Inspecting Officer

Name

Designation