GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ MD2 /1561

Dated :-28-1-15

FIRE SAFETY CERTIFICATE

Certified that the Tourist International Guest House 8197/6, A. K. Road, Pahar Ganj, New Delhi comprised of Basement, Ground + 4 Upper Floors (Basement used for office, Ground floor reception +02 guest rooms, 1st floor +06 guest room, 2nd floor & 3rd floor + 05 guest rooms at each floor, 4th floor has 02 staff rooms + staff kitchen total 18 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/2230 dated 21/06/2012. The premise was re-inspected by the officer concerned of this department on 14/08/15 in the presence of Sh. Girish Kumar Arora (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for total 18 guest rooms only as above with effect under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -18/-08-175---at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

- Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.
 - The Licensee, (2)Tourist International Guest House, 8197/6, A. K.Road, Pahar Gani, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building:- Tourist International Guest House 8197/6,

A.K.Road, Pahar Ganj, New Delhi.

2. Type of occupancy:-Residential Group A-1Basement, Ground, +

4 Upper Floors (Total 18 Guest Rooms)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2012/2230 dated

21/06/2012.

5. Fire safety directives No.-N/A

6. Date of inspection:-14/08/15

7. Name of the inspecting officer:-D.O. Gurmukh Singh

8. Name & designation of officer From the building side:-

Sh. Girish Kumar Arora (Manager)

9. Year of construction:-

10. Applicant's letter No:-1134/Joint CP/Lic (H). dated 30/07/15

				Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	6 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	NA	NA	NA		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases	V.				
	1. Upper floors	01 No	01 No.	MR		
	2. Basements	01 No.	01No.	MR		
	B. Width of staircase		_			
	1. Upper floors	80 cms	120 cms.	MR		
	2. Basements	80 cms.	120 cms	MR		
	C. Protection of exits		× ×			
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 Mtr.	1 Mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
124	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	12 Nos.	12 Nos.	MR		
	2) Types	ABC & CO2	ABC, CO2 &	MR		

-M-15

6.	3) ISI marking First-Aid Hose Reel	Required	Provided	MR
	1)Total number C			, III
	1)Total number of each floor	01 no.	01 no.	MR
		*		
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR
7.	3) Nozzle diameter	5 mm	_	MR
, .	Automatic Fire Detection &	Alarming System	m	1711(
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power		N/A	N/A
8.	5) Hooter's Location	N/A	N/A	N/A
9.	MOEFA	N/A	N/A	N/A
J.	Public Address System	Required	Provided	MR
10.	/Intercom	v =	- 10 (Idea	IVIK
10.	Automatic Sprinkler System			
	1) Basement	Required	Provided	MD
	2) Upper floors	N/A	N/A	MR
	3) Sprinkler above false	N/A	N/A	N/A
1 1	ceiling		1 1/11	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	NA	NA	NIA
	2) Number of hydrants per	NA	NA	NA
	floor		1 17 1	NA
10	3) Hose box	NA	NA	NIA
12.	Yard Hydrants		1111	NA
	1) Total number of hydrants	N/A	N/A	NT/A
•	2) Hose box	N/A	N/A	N/A
3.	Pumping Arrangement		TV//A	N/A
	1) Ground level	N/A	N/A	
	a) Discharge of main	N/A	N/A N/A	N/A
	pump	11/11	IN/A	N/A
	b) Head of main pump	N/A	NI/A	
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	IN/A	N/A	N/A
	2) Terrace level			
	a) Discharge of pump	225 I D) (
	b) Head of pump	225 LPM	225 LPM	MR
	c) Power supply	30 Mtr.	30 Mtr.	MR
		Required	Provided	MR
		Required	Provided	MR
	Captive Water Storage for Fire I			
	1) Under ground tank	N/A	N/A	N/A
	capacity			

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 Ltr.	2,5,00 Ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			IVII.
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			



The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2012/2230 dated 21/06/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer