GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. f6/0F5/ms/school/2015/ MOZ/1575

Dated: 01/09/15

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by

(Dr. G.C. Misra) Chief Fire Officer Ph -011- 23414333

0/c 8km

To,

The Principal

Adarsh Vidya Niketan Public School, 25, Shiv Mandir Gali, Maujpur, Delhi-53 Copy to:-.

The Director of Education,

East Delhi Municipal Corporation,

419, Udyog Sadan, Patparganj Industrial Area, Delhi-92

CONDITIONS:

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT : Adarsh Vidya Niketan Public School, 25, Shiv Mandir Gali 1. Name & address of the building Maujpur, Delhi-53. : G+1 2. Building is comprised of : Educational 3. Type of Occupancy 4. Type of Case : Renewal 5. Details of Previous NOC : F.6/MS/DFSS/2008/407 dated 15.02.2008 : Old requirements 6. Fire Safety direction letter No (Circular No. 262-362 dated 17.01.2005) : 25.08.2015 7. Date of Inspection 8. Name of the Inspecting Officers: : Suresh Singh (ADO) 9. Name of the designation of Officer : Headmaster from the building side : 1991 10. Year of Construction : Dated 22.07.2015 11. Applicant's letter No Provided Remarks Minimum Standards on fire safety Old at S.No requirements as per circular no. 262-362 | Requirement Site MR/NMR dated 17.01.2005 1 Access to building MR/Old Case 5 m Road width 6 m NA N.A. N.A. Gate width N.A. Width of internal road N.A. N.A. Number, Width, Type and Arrangement of Exits 2 a. Number of Staircases MR 2 no. Upper Floor 1 no. N.A. N.A N.A. Basement B. Width of Staircases MR Upper Floor 1.5 m 1.25 m, 0.95 m Basement N.A. N.A. N.A c. Protection of exits N.A. N.A. N.A Fire check door N.A. N.A. N.A. Pressurization N.A. N.A. N.A. e. No. of continuous staircases to terrace MR 1 no. 1 no. g. Width of Corridor MR 1.5 m 1.5 m h. Door Size 1 m MR 1 m 3 Compartmentation N.A. N.A. N.A. Fire check door N.A. N.A. N.A. Sealing of electrical shafts N.A. N.A. N.A. Fire rating of shaft door Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A.

N.A.

N.A.

N.A.

N.A.

N.A.

N.A.

Smoke Management System.

Basement

Upper floor

4

| 5. | Fire Extinguisher Total numbers | 04 no. | 06 no. | MR | | | |
|----|---|-----------------------|-----------------------|------|--|--|--|
| | types | CO ₂ & ABC | CO ₂ & ABC | MR | | | |
| | IS marking | ISI marked | ISI marked | MR | | | |
| 6 | First-aid-Hose Reels. | | | | | | |
| 0 | Total numbers of each floor | 01 no. | 01 no. | MR | | | |
| | Length of hose reel hose | 30 m | 30 m | MR | | | |
| | Nozzle diameter | 5 mm | 5 mm | MR | | | |
| 7 | Automatic fire detection and alarming system. | | | | | | |
| | Type of detectors | N.A. | N.A. | N.A. | | | |
| | Location of main panel | N.A. | N.A. | N.A. | | | |
| | Location of repeater panel | N.A. | N.A. | N.A. | | | |
| | Alternate source of power | N.A. | N.A. | N.A. | | | |
| | Hooters's location | N.A. | N.A. | N.A. | | | |
| 0 | MOFFA | N.A. | NA | NA | | | |
| 8 | MOEFA Dublic address System | N.A. | NA | NA | | | |
| 9 | Public address System. N.A. NA | | | | | | |
| 10 | basement | N.A. | N.A. | N.A. | | | |
| | upper floor | N.A. | N.A. | N.A. | | | |
| | sprinkler above false ceiling | N.A. | N.A. | N.A. | | | |
| 11 | Internal Hydrants | | | | | | |
| 11 | size of riser/down-comer | N.A. | N.A. | N.A. | | | |
| | Number of hydrants per floor | N.A. | N.A. | N.A. | | | |
| | Hose Box | N.A. | N.A. | N.A. | | | |
| 10 | Yard Hydrants. | | | | | | |
| 12 | Total number of hydrants | N.A. | N.A. | N.A. | | | |
| | Hose Box | N.A. | N.A. | N.A. | | | |
| 12 | Pumping Arrangements. | | | | | | |
| 13 | Ground Level | N.A. | N.A. | N.A. | | | |
| | > Discharge of main Pump | N.A. | N.A. | N.A. | | | |
| | > Head of Main Pump | N.A. | N.A. | N.A. | | | |
| | > Number of main pumps | N.A. | N.A. | N.A. | | | |
| | > Jockey pump out put | N.A. | N.A. | N.A. | | | |
| | > Jockey pump head | N.A. | N.A. | N.A. | | | |
| | > Standby pump out put | N.A. | N.A. | N.A. | | | |
| | > Standby pump Head | N.A. | N.A. | N.A. | | | |
| | Auto Starting /Manual stopping | N.A. | N.A. | N.A. | | | |
| | > Pump House Access | N.A. | N.A. | N.A. | | | |
| | Terrace Level | 0 | | | | | |
| | > Discharge of pump | 220 LPM | 220 LPM | MR | | | |
| | > Head of the Pump | 40 m | 40 m | MR | | | |
| | > Power supply | Required | Provided | MR | | | |
| | Auto Starting of pump | Required | Provided | MR | | | |

NY

| 14 | Captive Water Storage for Fire Fighting | 5. | | | |
|----|---|-------------|-------------|------|--|
| | Underground tank capacity | N.A. | N.A. | N.A. | |
| | Draw-off connection | N.A. | N.A. | N.A. | |
| | Fire service inlet | N.A. | N.A. | N.A. | |
| | Access to tank | N.A. | N.A. | N.A. | |
| | Overhead Tank capacity | 2500 Liters | 2500 Liters | MR | |
| 15 | Exit Signage. | N.A. | N.A. | N.A. | |
| 16 | Provision of Lifts. | | | | |
| | Pressurization of Lift Shaft | N.A. | N.A. | N.A. | |
| | Pressurization of Lift lobby | N.A. | N.A. | N.A. | |
| | Communication in lift car | N.A. | N.A. | N.A. | |
| | Firemen's grounding switch Lift Signage | N.A. | N.A. | N.A. | |
| | | N.A. | N.A. | N.A. | |
| 17 | Standby power supply | N.A. | N.A. | N.A. | |
| 18 | Refuge Area. | | | | |
| | Total area | N.A. | N.A. | N.A. | |
| | Location | N.A. | N.A. | N.A. | |
| 19 | Fire Control Room | | | | |
| 5 | Detector system panel | N.A. | N.A. | N.A. | |
| | Flow switch panel | N.A. | N.A. | N.A. | |
| | PA system panel | N.A. | N.A. | N.A. | |
| | Batter backup | N.A. | N.A. | N.A. | |
| | Building Floor Plans | N.A. | N.A. | N.A. | |
| 20 | Special Fire Protection systems for | N.A. | N.A. | N.A. | |
| | protection of special Risks, if any: | | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the NOC issued vide letter no. F.6/MS/DFSS/2008/407 dated 15.02.2008 under the circular No. 262-362 dated 17.01.2005 It is recommended to grant Fire Safety Certificate.

Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

DO (EAST)

Submitted for approval please. Wingle