GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/MD2 11622

Dated :- 08 / 6-8-1-1

FIRE SAFETY CERTIFICATE

Issued -3/0-9-175---at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee, Star Villa Guest House, 98-99, Krishana Gali, Pahar Ganj, New Delhi..

Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-N/11-

INSPECTION REPORT

1.Name & address of the building:- Star Villa Guest House 98-99, Krishana Gali,

Pahar Ganj, New Delhi.

2. Type of occupancy:- Residential Group A-1 Ground + 3 Upper

Floors (Total 31 Guest Rooms)

3. Type of case:- Renewal

4. Details of previous FSC :- No. F6/DFS/MS/GH/2012/3253 dated

07/09/2012.

5. Fire safety directives No.-

N/A 27/08/15

6. Date of inspection:-7. Name of the inspecting officer:-

D.O. Gurmukh Singh

8. Name & designation of officer

Mr. Arun Mittal

From the building side:-

2008

9. Year of construction:-

Nil-dated Nil

10.	Applicant's letter No:-	Nil- dated Ni	1.	Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	4 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	NA	NA	NA	
2.	Number, Width Type & Arran				
	A. Number of staircases				
	1. Upper floors	01 No	01 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	80 cms	125 cms.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits		5		
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 Mtr.	1 Mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	08 Nos.	08 Nos.	MR	
	2) Types	ABC & CO2	ABC, CO2 &	MR	

	3) ISI marking	Required	Provided	MR			
6.	First-Aid Hose Reel	2					
	1)Total number of each floor	01 no.	01 no.	MR			
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR			
	3) Nozzle diameter	5 mm	5 mm	MR			
7.	Automatic Fire Detection & Alarming System						
- 43	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System /Intercom	Required	Provided	MR			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling						
11.	Internal Hydrants						
	1) Size of riser/down-comer	NA	NA	NA			
	2) Number of hydrants per	NA	NA	NA			
	floor						
	3) Hose box	NA	NA	NA			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	pump	м					
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pum	p N/A	N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump output	t N/A	N/A	N/A			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual		N/A	N/A			
	stopping						
	2) Terrace level	*					
	a) Discharge of pump	180 LPM	180 LPM	MR			
	b) Head of pump	30 Mtr.	30 Mtr.	MR			
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump		Provided	MR			
14.	Captive Water Storage for Fi						
11.	Under ground tank capacity	N/A	N/A	N/A			

	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank	2,500 Ltr.	3,000 Ltr.	MR	
	capacity				
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.	2			
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:				

Shortcoming issued vide letter No. F6/DFS/MS/GH/2015/1595 dated 17.07.15 found rectified.

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2012/3253 dated 07/09/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer