GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110 001**

No. F6/Dfs/ans/2015/MDZ/1626

Dated 68/69/15

FIRE SAFETY CERTIFICATE

Certified that the Aggarwal Fun City Mall at Plot No. 29-31, CBD Shahdara Delhi , comprised of two basemens, ground plus two upper floors owned/occupied by Aggarwal Plaza Pvt. Ltd., was granted FSC by this department vide letter No. F6/DFS/MS/2012/1455 dated 23.04.12. The Premises was inspected by the officers concerned of this department on 13.08.2015 in the presence of Sh.Arun Kumar (Incharge) and found that the premises have deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules, 2010 and found that the Mercantile building is fit for three years in accordance with Rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule 2010, subject to conditions printed overleaf.

Issued on.....at New Delhi by

(Dr.G.C.Misra) Chief Fire Officer Ph- 011- 23414333

of Sec

To.

Sh.Sunil Kumar Jain M/S Aggarwal Plaza Pvt. Ltd 287, Aggarwal City Plaza, Plot no. 17, Manglam Place, Sector-3, Rohini, Delhi.

Conditions

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 6 This FSC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8 Basements shall be used as per BBL

1. Name & address of the building: Aggarwal Fun City Mall at Plot No. 29-31, CBD Shahdara, Delhi

2. Type of Occupancy

: Mercantile

3. Type of Case

: Renewal

4. Details of Previous FSC 5. Fire Safety directives No : F.6/DFS/MS/2012/1455 dated 23.04.12 : F.6/DFS/MS/BP/2005/1448 dated 08.07.05

6. Date of Inspection

:13.08.15

7. Name of the Inspecting Officer: DO Virendra Singh and ADO Suresh Singh

8. Name of the designation of Officer

From the building side

: Sh.Arun Kumar (Incharge)

9. Year of Construction

: 2005

10 Applicant's letter No

S.NO.	Minimum Standards on fire prevention and fire safety U/R33	NBC Provided at Site Requirement		Remarks			
1	Access to building Requirement MR/NMR						
	Road width	12 Mtrs	26 Mtrs.	MR			
	Gate width	4.5 Mtrs.	5 Mtrs.	MD			
	 Width of internal road 	N/A	N/A	MR			
2	N/A Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	 Upper Floor 	05 Nos	05 Nos.	MR			
	 Basement 	05 Nos	05 Nos.+1Ramp	MR			
	B. Width of Staircases		oo rros. Inamp	1411			
	 Upper Floor 	1.5 M	1.5 M	MR			
	 Basement 	1.5 M	1.5 M	MR			
	c. Protection of exits			TVIIL			
	 Fire check door 	Required	Provided	MR			
	 Pressurization 	Required	Provided	MR			
	e. No. of continuous staircases to terrace	2 Nos.	2 Nos.	MR			
	g. Width of Corridor	2.5 Mtrs	2.5 Mtrs	MR			
	h. Door Size	1.5 Mtr.	1.5 Mtr.	MR			
3	Compartmentation. Required Provided						
	Fire check door	Required	Provided	MR			
	 Sealing of electrical shafts 	Required	Sealed	MR			
	 Fire rating of shaft door 	2 hrs.	2 hrs.	MR			
	 Water curtain 	N/A	N/A	N/A			
	 Fire Dampers 	Required	Provided	MR			
ļ.	Smoke Management System.			45345 6760			
	 Basement 	30a/c per hour	Provided	MR			
	 Upper floor 	12 a/c per hour	Provided	MR			
i.	Fire Extinguisher						
	 Total numbers 	60 no.	60 No.	MR			
	• types	ABC & Co2	ABC & Co2	MR			
	IS marking	ISI marked	ISI marked	MR			
	First-aid-Hose Reels.						
V	Total numbers of each floor	6 no.	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			

/	Automatic fire detection and alarming s Type of detectors			1
		Heat & smoke		MR
	Location of main panel	Control Room	- Dascillett	MR
	Location of repeater panel Alternate source of payers	Security Room	n Provided	MR
	Alternate source of power	Battery & DG Set	Provided	MR
	 Hooters's location 	Different Location	Different Location	MR
8	MOEFA	Required	Provided	
9	Public address System.	Required	Provided	MR
10	Automatic Sprinkler System.	Required	Provided	MR
	• basement	Required	Provided in entre basement	MR
	upper floor	Required	Provided	MR
	 sprinkler above false ceiling 	Required	Provided	MR
11	Internal Hydrants		riovided	IVIR
	 size of riser/down-comer 	100 mm	100 mm	MR
	 Number of hydrants per floor 	06 nos.	06 nos.	MR
	Hose Box	06 nos.	06 nos.	
12	Yard Hydrants.		00 1105.	MR
	 Total number of hydrants 	3 nos.	3 nos.	NAD
	Hose Box	3 nos.	3 nos.	MR
13	Pumping Arrangements.	3 1103.	3 1105.	MR
	Ground Level	Required	Provided	NAC.
V	Discharge of main Pump	2280 LPM	2280 LPM	MR
	> Head of Main Pump	60 Mtrs.		MR
	Number of main pumps	1 nos.	60 mtrs	MR
	> Jockey pump out put	450 LPM	1 nos. 450 LPM	MR
	> Jockey pump head	60 Mtrs.	60 mtrs.	MR
	Standby pump out put	2280 LPM	2280 LPM	MR
	Standby pump Head	60 Mtrs	60 Mtrs.	MR
	Auto Starting / Manual stopping	Auto	Provided	MR MR
	Pump House Access	Required	Provided	MR
	Terrace Level	N/A	N/A	N/A
	Discharge of pump	N/A	N/A	N/A
	Head of the Pump	N/A	N/A	N/A N/A
	Power supply	N/A	N/A	N/A
	Auto Starting of pump	N/A	N/A	N/A
14	Captive Water Storage for Fire Fighting.			
	Underground tank capacity	2,00,000 Ltrs.	2,00,000 Ltrs.	MR
	> Draw-off connection	Required	Provided	MR
	Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	MR
Г	Overhead Tank capacity Fight 6:	25000 Ltrs.	25000 Ltrs.	MR
.5	Exit Signage.	Required	Provided	MR
.6	Provision of Lifts.			
	Pressurization of Lift Shaft	Required	Provided	MR
	Pressurization of Lift lobby	Required	Provided	MR
	Communication in lift car	Required	100	MR
	 Firemen's grounding switch 	Required		MR
	Lift Signage			MR
.7	Standby power supply			MR

	2		1	
1		′	-	
,	1			

18	Refuge Area.	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	• Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector system panel	Required	Provided	MR
	Flow switch panel	Required		MR
	PA system panel	Required		MR
	Batter backup	Required		MR
	Building Floor Plans	Required	Provided	MR
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested checked and found functional at the of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the FSC issued vide letter .F.6/DFS/MS/2012/ 1455 dated 23.04.12 renewal under the rule 35 of the Delhi Fire Service rules 2010 is recommended.

Submitted please.

Sengh 20.8-15

Signature of the Inspecting Officer

Name :Suresh Singh

Designation: ADO (Shah.)

Signature of the Inspecting Officer

Name: Virendra Singh Designation: DO(ED)