## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ MDZ //693

Dated: 16/09/15

## FIRE SAFETY CERTIFICATE

Certified that M/s Samar Samrat Lodge located at 5963, 5977, Gali Kumharan, Ballimaran, Delhi comprised of Basement floor (storage), Ground floor (commercial use), Mezzanine floor (reception), 1<sup>st</sup> floor (14 guest rooms + office + store), 2<sup>nd</sup> floor (16 guest rooms), 3<sup>rd</sup> & 4<sup>th</sup> floor (owner residence) total 30 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/2460 dated 10/07/2012. The premise was re-inspected by the officer concerned of this department on 14/07/15 in the presence of Shri Iqbal (owner) of the guest house and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 30 guest rooms at 1<sup>st</sup> to 2<sup>nd</sup> floor only with effect from --1-6-1-0-1-1-1-1---- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 1-6-1-6-7-45--- at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Pn: - 011

## Copy to: -

1 The Joint. C.P.(Lic.), Police Station, Defence colony, 1st floor, New Delhi

- 2 The Manager, M/s Samar Samrat Lodge 5963,5977, Gali Kumharan, Ballimaran, Delhi Conditions:-
  - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
  - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
  - 3. The trained fire fighting staff should be available round the clock.
  - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
  - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
  - 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
  - 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

## **INSPECTION REPORT**

1. Name & address of the building: - M/s Samar Samrat Lodge 5963,5977, Gali

Kumharan, Ballimaran, Delhi

2. Type of occupancy:- Residential Group A-1 (Basement + Ground +

Mezzanine + 4 upper floors) Total 30 guest rooms

3. Type of case:- Renewal

4. Details of previous FSC: - No. F6/DFS/MS/GH/2012/2460 dated

10/07/2012.

5. Fire safety directives No.- N/A

6. Date of inspection:- 14/07/15

7. Name of the inspecting officer:- A. D.O. Mehmood

8. Name & designation of officer

From the building side:- Shri Iqbal (owner)
9. Year of construction:- 1988

10. Applicant's letter No:- 520/Joint C.P./Lic.(H)Dated 1/06/15

S No	M C. I I			Old cas
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks
	Prevention and fire safety U/R 33	(Existing)		MR/NMR
1.	Access to Building	¥		
		*	χ	
	1) Road width	N/A	11.58 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arran	ngement of Exits		11.11.1
	A. Number of staircases			
	1. Upper floors	01 No	01 No.	MR
	2. Basements	01 No	01 No.	MR
	B. Width of staircase			IVIIC
	1. Upper floors	0.90 mtr.	1.06 mtr.	MR
	2. Basements	0.90 mtr.	1.06 mtr.	MR
	C. Protection of exits			IVIIC
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	01 No.	01 No.	M/R
	staircase to terrace	,		111/10
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	0.80 mtr.	0.81 mtr.	MR
3.	Compartmentation			IVIIC
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
1.	Smoke Management System		- 1/12	14/11
	1) Basements	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	Fire Extinguishers			11//1
	1) Total numbers	07 Nos.	07 Nos.	MR

de

_	N		1
	7/	1	
/	/		

	2) Types	ABC & CO2	Provided	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel	required	Tioviaca	IVIIC	
	1)Total number of each	01 No	01 No.	MR	
	floor		01110.	IVIIC	
	2) Length of hose reel hose	30 m	30 m	MR	
	3) Nozzle diameter	5 mm	5 mm.	MR	
7.	Automatic Fire Detection & A			17110	
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	N/A	N/A	N/A	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	1		1111	
	1) Basement	Required	Provided	MR	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling	W. S. C.		11/11	
11.	Internal Hydrants				
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per	N/A	N/A	N/A	
	floor			11/12	
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement				
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump		1.1.1.2	11/11	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump		N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping	1,111	1 1/1 1	14/21	
	2) Terrace level				
	a) Discharge of pump	225 LPM	225 LPM	MR	
	b) Head of pump	35 mtr.	35 mtr.	MR	
	c) Power supply	Required	Provided Provided	MR	
	d) Auto starting of pump	Required	Provided	MR	
14.	Captive Water Storage for Fire		TTOVICCO	IVIIC	
	1) Under ground tank	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A	
	a) Dian on connection	T 1/ L X	14/11	IVA	

BOX.

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 Ltrs.	2,500 Ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	n for Protection o	of special Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2012/2460 dated 10/07/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

D.O. (Central)

lohm

Assistant Divisional Officer