GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2015/ MOZ/1773

Dated : 01/0//5

FIRE SAFETY CERTIFICATE

Issued 01/10/15 at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. No. 1178/Joint C.P. /Lic.(H) dated 04/08/2015
- 2. Sh. Sonu (Manager),

Ravina Palace Guest House 962, Gali Kumharan, Main Bazar, Pahar Ganj, New Delhi Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

Name & address of the building:-

2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Ravina Palace Guest House located at 962, Gali Kumharan, Main Bazar, Pahar Ganj, New Delhi

Residential, Sub Division-A-1

B + Gr. + 04 Upper floors (total 32 Guest rooms)

Renewal

No. F6/DFS/MS/GH/2012/2885 dated

07/08/12. N/A

18/09/15

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Sonu (Manager)

1994

No. 1178/Joint. C.P. /Lic.(H) dated 04/08/2015

| S.No. | Minimum Standards on fire | Requirement | Provided at site | Old Case | | |
|-------|---|-------------|---|----------|--|--|
| | Prevention and fire safety | Existing | PSS PSS | | | |
| | U/R 33 | Daisting | 133 | MR/NMR | | |
| 1. | Access to Building | | | | | |
| | 1) Road width | N/A | 02 mtr. | N/A | | |
| | 2) Gate width | N/A | N/A | N/A | | |
| | 3) Width of internal road | N/A | N/A | N/A | | |
| 2. | Number, Width Type & Arrangement of Exits | | | | | |
| | A. Number of staircases | | | | | |
| | 1. Upper floors | 01 Nos. | 01 Nos. | MR | | |
| | 2. Basements | 01 Nos. | 01 Nos. | MR | | |
| | B. Width of staircase | | | TVIIC | | |
| | 1. Upper floors | 0.80 mtr. | G.F to F.F – 1.29 to 1.54 mtr. 2 nd F to 4 th F – 0.96 to 1.01 mtr. | MR | | |
| | 2. Basements | 0.80 mtr | 1.0 mtr. | MR | | |
| | C. Protection of exits | | | | | |
| | 1. Fire check door | N/A | N/A | N/A | | |
| | 2. Pressurization | N/A | N/A | N/A | | |
| | D. No. of continuous staircase to terrace | 01 | 01 | MR | | |
| | E. Width of corridor | N/A | N/A | N/A | | |
| | F. Door size | 1 mtr. | 1 mtr. | MR | | |
| | Compartmentation | | | | | |
| | 1) Fire check door | N/A | N/A | N/A | | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | | |
| | 4) Water curtain | N/A | N/A | N/A | | |
| | 5) Fire Dampers | N/A | N/A | N/A | | |
| | Smoke Management System | | | - 11 - 1 | | |
| | 1) Basements | 30 ACPH | Exhaust fans | MR | | |

| | 2) Hanar floors | 12 a/c per | Natural Ventilation | MR | |
|-----------|--|------------|---------------------|-----|--|
| | 2) Upper floors | hour | | | |
| 5. | Fire Extinguishers | | | | |
| 3. | 1) Total numbers | 10 Nos. | 10 Nos. | MR | |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | |
| | 3) ISI marking | Required | Provided | MR | |
| 5. | First-Aid Hose Reel | | | | |
|). | 1) Total number of eachfloor | 01 | 01 | MR | |
| | 2) Length of hose reel hose | 30 m | 30 m | MR | |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR | |
| 7. | Automatic Fire Detection & | em | | | |
| • | 1) Type of detectors | N/A | N/A | N/A | |
| | 2) Location of main panel | N/A | N/A | N/A | |
| | 3) Location of manipulated 3) Location of repeater panel | N/A | N/A | N/A | |
| | 4) Alternate source of power | N/A | N/A | N/A | |
| | 5) Hooter's Location | N/A | N/A | N/A | |
| 2 | | Required | Provided | MR | |
| 8. | MOEFA Public Address System | Required | Provided | MR | |
| 9. | Intercom | Required | | | |
| 10 | Automatic Sprinkler System | | | | |
| 10. | 1) Basement | Required | Provided | MR | |
| | 2) Upper floors | N/A | N/A | N/A | |
| | 3) Sprinkler above false | N/A | N/A | N/A | |
| | | 1077 | | | |
| 11 | ceiling Internal Hydrants | | | | |
| 11. | 1) Size of riser/down-comer | N/A | N/A | N/A | |
| | 2) Number of hydrants per | N/A | N/A | N/A | |
| | floor | 1 1/1 2 | | | |
| | 3) Hose box | N/A | N/A | N/A | |
| 10 | | 1072 | Y | | |
| 12. | Yard Hydrants 1) Total number of hydrants | N/A | N/A | N/A | |
| | | N/A | N/A | N/A | |
| | 2) Hose box | 1771 | | | |
| 13. | Pumping Arrangement | N/A | N/A | N/A | |
| | 1) Ground level | N/A | N/A | N/A | |
| * | a) Discharge of main | IVA | 1,472 | | |
| | pump | N/A | N/A | N/A | |
| | b) Head of main pump | | N/A | N/A | |
| | c) Number of main pum | 1 | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head | | N/A | N/A | |
| | f) Stand by pump outpu | | N/A | N/A | |
| | g) Stand by pump head | | N/A | N/A | |
| | h) Auto starting/Manua | I IN/FI | 1021 | | |
| | stopping | | | | |
| | 2) Terrace level | 180 LPM | 180LPM | MR | |
| | a) Discharge of pump | 30 mtr | 30 mtr | MR | |
| | b) Head of pump | Required | Provided | MR | |
| | c) Power supply Require | | 11071404 | | |

Mr

| 14. | Captive Water Storage | o for E | Require | d Provided | 1 | MR | |
|-----|--|------------|----------|------------|-------|--------|--|
| | | nk | N/A | | | 14111 | |
| | capacity | | IV/A | N/A | | N/A | |
| | a) Draw-off connec | tion | N/A | | | IVA | |
| | b) Fire service inlet | | N/A | N/A | | N/A | |
| | c) Access to tank | - | | N/A | | N/A | |
| | d) Over head tank | | V/A | N/A | | N/A | |
| 15. | capacity | 3 | 000 ltr. | 5000 ltr. | 7. 7. | MR | |
| | Exit Signage | | | | | IVIK | |
| 16. | Provision of Lifts. | R | equired | Provided | N | MR | |
| | a) Pressurization of li | :0 | | | I | ATIC | |
| | shaft | ift N | /A | N/A | | | |
| | b) Pressurization of li | 0 | | | N | N/A | |
| | lobby | ft N/ | A | N/A | | 4 | |
| | c) Communication in | | | | N | /A | |
| | lift car | N/. | A | N/A | | | |
| | d) Fireman's switch | | | - " - " | N/ | 'A | |
| | e) Lift signage | N/A | | N/A | 7.7 | | |
| 17. | Stand by Power Supply | | 1 | N/A | | N/A | |
| 18. | Refuge Area Total area location | | uired | Provided | N/ | | |
| | | | | N/A | MF | | |
| | | | | | N/A | | |
| 19. | E: | N/A | | N/A | N/A | N/A | |
| | Fire Control Room | | | | 1 111 | - 1/12 | |
| | a) Detector system | N/A N/A | 7 | N/A | N/A | | |
| | panel | | | N/A | N/A | | |
| | b) Flow switch panel | 77/1 | | | IN/A | | |
| | c) PA system panel | N/A N/A | | N/A | N/A | | |
| | d) Battery backup | | | N/A | | N/A | |
| | | | | N/A | | | |
| | e) Building floor plan | | | | N/A | N/A | |
| . 5 | Special Fi | | | N/A | NT/A | | |
| 1 | Special Fire Protection System for Protection of special Risk, if any: | | | | | N/A | |
| | | | | | | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/GH/2012/2885 dated 07/08/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharman Of Designation: - ADO (CC)