FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/Sehool/2015/W2/1790

FIRE SAFETY CERTIFICATE

Dated: 07/10/15

Certified that the New Shalimar Public School located at BM Block (Pashcimi), Shalimar Bagh Delhi - 110088 comprised of Ground, Mez plus one upper floor was issued FSC vide Letter No. F6/DFS/MS/2008/553 Dated 11-06-2008. The premises was re inspected by the officer concerned of this department on 08-09-2015 in the presence of Sh. RD Malothra (AO) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance Circular 262-362 Dated 17-01-2005 and that the premises is fit for occupancy class "Educational" Group B with effect from o7/10/15 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Santokh) Singh) Chief/Fire Officer PH 011-23414250

Copy to:

The Principal, New Shalimar Public School BM Block (Pashcimi), Shalimar Bagh Delhi -110088.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if
- 6. All the exit route shall be kept free from any obstruction.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

Ground + Mez. + One Upper Floor

1. Name & address of the building

: New Sahalimar Public School, B M-Block (Pashemi)

Shalimar Bagh, New Delhi-110088

2. Type of Occupancy

: Educational

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/2008/1553 date 11/06/2008

5. Fire Safety directives letter No

: Direction of Education dated 17/01/2005

6. Date of inspection

: 08/09/2015

7. Name of the Inspecting Officers

: ADO (WP)

8. Name and designation of officers

from the building side

: Sh. R. D. Malhotra (AO)

9. Year of Construction

: 1987

10. Applicant's letter No.

: Nil dated 19/08/2015

Plot Area- 1130 Sq mtr Covered Area- 680 Sq. mtr NOS- 318 No of Class Room-17

	Minimum Standards on fire prevention and fire safety U/R 33	Dir. of Edu. Requirement	Provided at site	Remarks MR/NMR		
1	Access to building					
T. V.	Road width	Accessible	Provided	MR		
	Gate width	Accessible	Provided	MR		
	Width of internal road	-		-		
2	Number, Width, Type & Arrangement of Exits					
18	a. Number of staircases					
	Upper Floors	01	Provided	MR		
	Basements	N/A	N/A	N/A		
	b. Width of staircases					
	• Upper Floors	1.5 m x 1	2 X 108cm	MR		
	• Basements					
	c. Protection of exits			0		
	Fire check door	N/A	N/A	N/A		
	 Pressurization 	-				
	e. No. of continuous staircases to terrace	01	Provided	MR		
	g. Width of Corridor	N/A	N/A	N/A		
	h. Door Size	01 mtr	Old case (Class room having less than 45 students)	MR (being old case)		

3	Compartmentation.			T			
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire Rating of shaft door	N/A	N/A				
	Water Curtain	N/A	1942 1945 (1927)	N/A			
	Fire Dampers		N/A	N/A			
4	•	N/A	N/A	N/A			
4	Smoke Management System.						
	• Basements	30 a/c per hour	N/A	N/A			
	Upper floors	12 a/c per hour	N/A	N/A			
5	Fire Extinguishers						
	Total numbers	. 11	Provided	MR			
	• Types	v .	ABC + co2	MR			
	IS marking	ISI marked	Yes	MR			
)	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	NI/A			
	Location of Main Panel	N/A	N/A	N/A N/A			
	Location of Repeater Panel	N/A	N/A				
			1005300 003	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooters' Location	N/A	N/A	N/A			
	MOEFA	N/A	N/A	N/A			
	Public Address System.	Required	Provided	MR			
0	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
	Internal Hydrants						
	Size of riser/down-comer	100 mm	Provided	MR			
	 Number of hydrants per floor 	01	Provided	MR			
	Hose Box	01	Provided	MR			

1 - 9

	12.	Yard Hydrants			
		• Total number of	(
		• Total number of hydrants	NA	NA	NA
		Hose Box	27.4		
	13.	Pumping Arrangements:	NA	NA	NA
		• Ground Level			
			3.7.1	,	
		Discharge of main	NA	NA	NA
		> Head of main pump	77.4		
		Number of main	NA	NA	NA
		pumps	NA	NA	NA
		Jockey pump out put	NIA		
		Jockey pump head	NA NA	NA	NA
		Standby Pump out pu		NA	NA
		Standby Pump Head		NA	NA
		> Auto Staring/Manual	NA	NA	NA
		stopping	NA	NA	NA
		Pump House Access	NIA		
		• Terrace level	NA	NA	NA
		Discharge of pump	1374501		1
		2 Fermb	1X450 lp	om Provided	MR
		> Head of the pump	1X220 lp		
		Power supply	40Mtr	Provided	MR
		> Auto starting of pump	Required	21011404	MR
14	. (Captive water Storage for fire		Provided	MR
		 Under ground tank 			
		capacity	NA	NA	NA
		> Draw off connection	D.T.A.		asp
		Fire service inlet	NA	NA	· NA
		Access to tank	NA	NA	NA
		 Overhead Tank 	NA	NA	NA
		capacity	5000Ltr	Provided	MR
15	E	kit Signage	D 1		
16.	Pr	ovision of Lifts	Required	Provided	MR
		> Pressurization of Lift	NIA		
		Shaft	NA	NA	NA
		Pressurization of lift	NIA		
		lobby	NA	NA	NA
		Communication in lift	D : 1	2 - 1	
		Car	Required	Provided	MR
		Fireman's Grounding	D		
		Switch	Required	Provided	MR
		Lift Signage	Dog 1		
17	C		Required	Provided	MR
17.	Sta	ndby power supply	NA	NA	3 2 2
18.	Ref	iuge Area	(Marie 1976)	1111	NA
		Total area	NA	NA	NIA
		> Location	NA	NA	NA
				+ 14 1	NA

			N 10	
19.	Fire control room	T > T A	NA	NA
	> Detector system panel	NA	NA NA	NA
	> Flow Switch Panel	NA	NA	NA
	> PA System Panel	NA	NA	NA
	Battery backup	NA NA	NA	NA
> Building Floor Plans			NA	
0.	Special Fire Protection	the period of	A	
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA NA	NA	NA

Note:-General requirements for schools as per Director of Education circular dated 01/03/2011.

- 2. LPG cylinders in laboratories; NA
- 3. Electric wiring ...canceled Wiring...... MCB and ELCB

Electric circuit

- 4. Electric meter boardNot under the staircase.....
- 5. Basement use as per BBL 1983 ... NA
- 6. Emergency telephone no. boardDisplayed...
- NA 7. Generator set

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2008/553 Dated 11/06/2008 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting

Officer

Name Uda VIE 6 9 h
Designation ADO/WP

Name

Designation