GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/EH/2014/NOL 1783

Dated : 05.10.15

FIRE SAFETY CERTIFICATE

Issued - S. lo. 15at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph. 011-23414333

Copy to:- (1) Medical Officer of Health. New Delhi Municipal Council, Palika Kendra, New Delhi.

> (2) Dunkin Dount's India (Jubilant Food Works Ltd.) N-6, GF & Mezzanine Floor, Connaught Place New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

Dunkin Dount's India Restaurant, N-6, GF 1. Name & address of the building:-

& Mezzanine Floor, Connaught Place New

Group – D Assembly Building 2. Type of occupancy:-Gr.+ Mezzanine+ 2 Upper Floors.

Renewal 3. Type of case:-

No. F6/DFS/MS/EH/2012/3049 dated 4. Details of previous NOC:-

22/08/12. N/A

5. Fire safety directives No.-

16/09/15 6. Date of inspection:-D.O. Gurmukh Singh

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

Old.

Mr.Anuj Sachar.

Nil. Dairy dated 25/08/15 10. Applicant's letter No:-

| 10. | Applicant's letter No:- | Tim. Duniy | | Old Case |
|------|--|-------------------------|------------------|-------------------|
| .No. | VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII | Requirement Existing | Provided at site | Remarks MR/NMR |
| | Access to Building | | | MD |
| | 1) Road width | 6 mtr. | 20 mtr. | MR N/A |
| | 2) Gate width | N/A | N/A | |
| | 2) Width of internal road | N/A | N/A | N/A |
| 2. | Number, Width Type & Arra | ingement of E | xits | |
| 10 | A. Number of staircases | | | MR |
| | 1. Upper floors | 02 Nos. | 02 Nos. | MIK |
| | | | (01 through | ~ |
| | | | Dominos) N/A | N/A |
| | 2. Basements | N/A | N/A | 14/21 |
| | B. Width of staircase | | 1.45 mtr. & | MR |
| | 1. Upper floors | 1.45 mtr. & | 1.45 mtr. | IVIIC |
| | | 1.05 mtr. | N/A | N/A |
| | 2. Basements | N/A | IN/A | |
| | C. Protection of exits | Degrand | Provided at | MR |
| | 1. Fire check door | Required | Mezz floor | |
| | | | between restt. | |
| | • • | N/A | N/A | N/A |
| | 2. Pressurization | N/A | N/A | N/A |
| | D. No. of continuous | 14/21 | | |
| | staircase to terrace | N/A | N/A | N/A |
| | E. Width of corridor F. Door size | 2 mtr. | 2 mtr. | MR |
| | | | | |
| 3. | Compartmentation | N/A | N/A | N/A |
| | 1) Fire check door2) Sealing of electrical shafts | | N/A | N/A |
| | 2) Sealing of electrical share | N/A | N/A | N/A |
| | 3) Fire rating of shaft door 4) Water curtain | N/A | N/A | N/A |
| | 5) Fire Dampers | N/A | N/A | N/A |

| 4. | Smoke Management System | | | 2 |
|-----|-------------------------------|-----------------|-------------|------------|
| | 1) Basements | | NI/A | 27/4 |
| | 1) Basements | 30 a/c per hour | N/A | N/A |
| | 2) Upper floors | 12 a/c per | Exhaust fan | MR |
| | | hour | provided | IVIK |
| 5. | Fire Extinguishers | | provided | |
| | 1) Total numbers | 06 No. | 06 No. | MR |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR |
| | 3) ISI marking | ISI | Yes | MR |
| 6. | First-Aid Hose Reel | | | IVIIC |
| | 1) Total number of each floor | Mezz floor | 01 no. | MR |
| | 2) Length of hose reel hose | 30 m | 30 m |) (D |
| | 3) Nozzle diameter | 5 mm | 5 mm | MR |
| 7. | Automatic Fire Detection & | Alarming Syst | J IIIIII | MR |
| | 1) Type of detectors | Required | Provided | MD |
| | 2) Location of main panel | Required | Provided | MR |
| | 3) Location of repeater panel | N/A | N/A | MR |
| | 4) Alternate source of power | Required | Provided | N/A |
| | 5) Hooter's Location | N/A | N/A | MR |
| 8. | MOEFA | Required | Provided | N/A |
| 9. | Public Address System | N/A | N/A | MR |
| 10. | Automatic Sprinkler System | | IN/A | N/A |
| 10. | 1) Basement | N/A | N/A | NT/A |
| | 2) Upper floors | Required | Provided | N/A |
| | 3) Sprinkler above false | N/A | N/A | MR |
| | ceiling | 1 1/2 1 | IN/A | N/A |
| 11. | Internal Hydrants | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A |
| | 2) Number of hydrants per | N/A | N/A | N/A |
| | floor | | 11/11 | IN/A |
| | 3) Hose box | N/A | N/A | N/A |
| 12. | Yard Hydrants | | 11111 | IVA |
| | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | N/A |
| 13. | Pumping Arrangement | | | 14/71 |
| | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | | 14/14 | IN/A |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual | N/A | N/A | N/A N/A |
| | stopping | | 11/11 | 11//1 |
| | 2) Terrace level | | | |

| | a) Discharge of pump | 450 LPM | 450 LPM | MR |
|-----|---|---------------|------------------|-----|
| | b) Head of pump | 30 mtr. | 30 mtr. | MR |
| | c) Power supply | Required | Provided | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| 14. | Captive Water Storage for F | ire Fighting | | |
| | Under ground tank capacity | N/A | N/A | N/A |
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | 5,000 Ltrs. | 5,000 Ltrs. | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syst Risk, if any: | em for Protec | ction of special | N/A |

The fire protection system provided in the restaurant were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS MS/EH/2012/3049 dated 22/08/12, renewal under rule35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh
Divisional Officer

9-15 1486

Dycho (NDZ)