GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.

F6/ DF3/ms/ Scharl/2015/ND2/ 1847

Dated: 14/10/15

FIRE SAFETY CERTIFICATE

Certified that the Preet Public Secondary School, B- Block, Preet Vihar, Delhi-92, (The Preet Vihar Education Society (Regd.) comprised of basement, ground plus one upper floor was granted NOC by this department vide Letter No- F.6/MS/DFS/2005/828 dated 19.04.2005. The School building was inspected by the officer concerned of this department on 03.10.2015 in the presence of Principal of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with the circular No. 262-362 dated 17.01.2005 issued by the Director of Education and found that the school building having BF+GF+FF is fit for occupancy Group B "Educational Building" with effect from Indicated School Building having Parish School Building Branch Branch School Building Branch Bran

Issued on at New Delhi by

(Dr. G.C. Misra)

Chief Fire Officer

Ph -011- 23414333

of She

To,

The Principal

Preet Public Secondary School, B- Block, Preet Vihar, Delhi-92

The Preet Vihar Education Society (Regd.)

Copy to:-.

The Joint Director of Education

(Land & Estate)

Directorate of Education, Lucknow Road, Delhi -54.

INSPECTION REPORT 1. Name & address of the building : Preet Public Secondary School, B- Block, Preet Vihar, Delhi-92, The Preet Vihar Education Society (Regd.) 2. Building is comprised of : <u>B+G+1</u> 3. Type of Occupancy : Educational 4. Type of Case : Renewal 5. Details of Previous NOC : F.6/MS/DFS/2005/828 dated 19.04.2005 6. Fire Safety direction letter No : Old requirements (Circular No. 262-362 dated 17.01.2005) 7. Date of Inspection : 03.10.2015 8. Name of the Inspecting Officers: : Suresh Singh (ADO) 9. Name of the designation of Officer from the building side : Principal 10. Year of Construction : 1998 11. Applicant's letter No : P.V.E.S/2015 dated 02.09.2015 Minimum Standards on fire safety Old Provided at Remarks requirements as per circular no. 262-362 Requirement Site MR/NMR dated 17.01.2005 1 Access to building Road width 6 m 20 m MR Gate width N.A. N.A. N.A. Width of internal road N.A. N.A. N.A. Number, Width, Type and Arrangement of Exits 2 a. Number of Staircases Upper Floor 2 no. MR 2 no. Basement 1 no. 1 no. MR B. Width of Staircases old care -Upper Floor 1.5 m 1.3 m each MR Basement 1.25 m 1.3 m MR c. Protection of exits N.A N.A. N.A. Fire check door N.A. N.A. N.A. Pressurization N.A. N.A. N.A. e. No. of continuous staircases to terrace 2 no. 2 no. MR g. Width of Corridor 1.5 m 1.5 m MR h. Door Size 1 m 1 m MR 3 Compartmentation Fire check door N.A. N.A. N.A. Sealing of electrical shafts N.A. N.A. N.A. Fire rating of shaft door N.A. N.A. N.A. Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A. Smoke Management System. 4 Basement N.A. N.A. N.A.

it! Old case Hence acceptable & meeting the reguments

N.A.

Upper floor

N.A.

N.A.

| 5. | Fire Extinguisher | | | | | | |
|----|---|-----------------------|-----------------------|------|--|--|--|
| | Total numbers | 08 no. | 08 no. | MR | | | |
| | types | CO ₂ & ABC | CO ₂ & ABC | MR | | | |
| | IS marking | ISI marked | ISI marked | MR | | | |
| 6 | First-aid-Hose Reels. | | | | | | |
| | Total numbers of each floor | 01 no. | 01 no. | MR | | | |
| | Length of hose reel hose | 30 m | 30 m | MR | | | |
| | Nozzle diameter | 5 mm | 5 mm | MR | | | |
| 7 | Automatic fire detection and alarming system. | | | | | | |
| | Type of detectors | N.A. | N.A. | N.A. | | | |
| | Location of main panel | N.A. | N.A. | N.A. | | | |
| | Location of repeater panel | N.A. | N.A. | N.A. | | | |
| | Alternate source of power | N.A. | N.A. | N.A. | | | |
| | Hooters's location | N.A. | Provided | MR | | | |
| 8 | MOEFA | N.A. | N.A. | N.A. | | | |
| 9 | Public address System. | N.A. | Provided | MR | | | |
| 10 | Automatic Sprinkler System. | | | | | | |
| | basement | Required | Provided | MR | | | |
| | upper floor | N.A. | N.A. | N.A. | | | |
| | sprinkler above false ceiling | N.A. | N.A. | N.A. | | | |
| 11 | Internal Hydrants | | | | | | |
| | size of riser/down-comer | N.A. | N.A. | N.A. | | | |
| | Number of hydrants per floor | N.A. | N.A. | N.A. | | | |
| | Hose Box | N.A. | N.A. | N.A. | | | |
| 12 | Yard Hydrants. | | | | | | |
| | Total number of hydrants | N.A. | N.A. | N.A. | | | |
| | Hose Box | N.A. | N.A. | N.A. | | | |
| 13 | Pumping Arrangements. | | | | | | |
| | Ground Level | N.A. | N.A. | N.A. | | | |
| | Discharge of main Pump | N.A. | N.A. | N.A. | | | |
| | ➤ Head of Main Pump | N.A. | N.A. | N.A. | | | |
| | Number of main pumps | N.A. | N.A. | N.A. | | | |
| | Jockey pump out put | N.A. | N.A. | N.A. | | | |
| | Jockey pump head | N.A. | N.A. | N.A. | | | |
| | Standby pump out put | N.A. | N.A. | N.A. | | | |
| | Standby pump Head | N.A. | N.A. | N.A. | | | |
| | Auto Starting / Manual stopping | N.A. | N.A. | N.A. | | | |
| | Pump House Access | N.A. | N.A. | N.A. | | | |
| | Terrace Level | | | | | | |
| | Discharge of pump | 500 LPM | 500 LPM | MR | | | |
| | Head of the Pump | 40 m | 40 m | MR | | | |
| | Power supply | Required | Provided | MR | | | |
| | Auto Starting of pump | Required | Provided | MR | | | |

| 14 | Captive Water Storage for Fire Fighting. | | | | | |
|----|--|--------------|--------------|------|--|--|
| | Underground tank capacity | N.A. | N.A. | N.A. | | |
| | Draw-off connection | N.A. | N.A. | N.A. | | |
| | Fire service inlet | N.A. | N.A. | N.A. | | |
| | Access to tank | N.A. | N.A. | N.A. | | |
| | Overhead Tank capacity | 5,000 Liters | 5,000 Liters | MR | | |
| 15 | Exit Signage. | N.A. | N.A. | N.A. | | |
| 16 | Provision of Lifts. | | | | | |
| | Pressurization of Lift Shaft | N.A. | N.A. | N.A. | | |
| | Pressurization of Lift lobby | N.A. | N.A. | N.A. | | |
| | Communication in lift car | N.A. | N.A. | N.A. | | |
| | Firemen's grounding switch | N.A. | N.A. | N.A. | | |
| | Lift Signage | N.A. | N.A. | N.A. | | |
| 17 | Standby power supply | N.A. | N.A. | N.A. | | |
| 18 | Refuge Area. | | | | | |
| | Total area | N.A. | N.A. | N.A. | | |
| | Location | N.A. | N.A. | N.A. | | |
| 19 | Fire Control Room | | | | | |
| | Detector system panel | N.A. | N.A. | N.A. | | |
| | Flow switch panel | N.A. | N.A. | N.A. | | |
| | PA system panel | N.A. | N.A. | N.A. | | |
| | Batter backup Building Floor Plans | N.A. | N.A. | N.A. | | |
| | | N.A. | N.A. | N.A. | | |
| 20 | Special Fire Protection systems for protection of special Risks, if any: | N.A. | N.A. | N.A. | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the NOC issued vide letter no. F.6/MS/DFS/2005/828 dated 19.04.2005 renewal under the circular No. 262-362 dated 17.01.2005 is recommended.

Stryk 5.10:15

Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

DO (EAST)

Submitted for approval please.