## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ NO2/1918

Dated : 28/10/15

## FIRE SAFETY CERTIFICATE

Certified that the Karam Durga Guest House, T-316, General Market, Pahar Ganj, New Delhi comprised of Ground + 5 Upper Floors (Ground floor shops, 1<sup>st</sup> floor 02 guest rooms + reception, 2<sup>nd</sup> floor 03 guest rooms, 3<sup>rd</sup> floor & 4<sup>th</sup> floor owners residence & 5<sup>th</sup> foor sealed total 05 guest rooms) was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/4334 dated 21/11/2012. The premise was re-inspected by the officer concerned of this department on 10/10/15 in the presence of Sh. Nirmal Sharma (Prop.) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 05 guest rooms only as above with effect from -28-ft - for period of three years in accordance with rule 35 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -28/to/ts----at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1<sup>st</sup> Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,Karam Durga Guest House,T-316, General Market, Pahar Gani, New Delhi

## Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-19/11-

INS	SPF	CTI	MC	RF.	POI	TS

1. Name & address of the building:- Karam Durga Guest House, T-316, Gernal

Market, Pahar Ganj, New Delhi.

2. Type of occupancy:- Residential Group A-1 Ground + 5 Upper

Floors (Total 05 Guest Rooms)

3. Type of case:- Renewal

4. Details of previous FSC :- No. F6/DFS/MS/GH/2012/4334 dated

21/11/2012.

5. Fire safety directives No.- N/A

6. Date of inspection: 10/10/15

7. Name of the inspecting officer:- D.O. Gurmukh Singh

8. Name & designation of officer

From the building side:- Sh. Nirmal Sharma (Prop.)

9. Year of construction:- 2008

10. Applicant's letter No:- 1735/Joint CP/Lic (H) dated 15/09/15

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Old Case Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	05 Feet.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	NA	NA	NA		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 No	01 No.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	80 cms	90 cms.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits		¥			
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace		х.			
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 Mtr.	1 Mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	06 Nos.	06 Nos.	MR		
	2) Types	ABC & CO2	ABC, CO2 &	MR		

-H/17-

	2) ICI morleina	Daguinad	Da: 1 - 1	NAD -	
6	3) ISI marking First-Aid Hose Reel	Required	Provided	MR 🌎	
6.		01 mg	01	MD	
	1)Total number of each floor	01 no.	01 no.	MR	
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR	
	3) Nozzle diameter	5 mm	5 mm	MR	
7.	Automatic Fire Detection & Al		3 111111	IVIK	
1.	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A N/A	N/A	
8.	MOEFA	N/A	N/A	N/A	
9.	Public Address System	N/A	N/A	N/A	
7.	/Intercom	N/A	IN/A	IN/A	
10.	Automatic Sprinkler System				
10.	1) Basement	N/A	N/A	NT/A	
				N/A	
	2) Upper floors 3) Sprinkler above false	N/A N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
11.	ceiling				
11.	Internal Hydrants	NIA	N. D. T. A.	27.4	
	1) Size of riser/down-comer	NA	NA	NA	
	2) Number of hydrants per	NA	NA	NA	
	floor	27.4	N.T.A.	37.	
10	3) Hose box	NA	NA	NA	
12.	Yard Hydrants	27/1			
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement				
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump				
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping				
	2) Terrace level				
	a) Discharge of pump	180 LPM	180 LPM	MR	
	b) Head of pump	30 Mtr.	30 Mtr.	MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of pump	Required	Provided	MR	
14.	Captive Water Storage for Fire		11011404	17111	
	1) Under ground tank	N/A	N/A	N/A	
	capacity	14/11	1 1/1 1	14/71	

H/13-

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 Ltr.	2,500 ltrs.	MR
15.	Exit Signage.	Required	Provided	NMR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2012/4334 dated 21/11/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

Dy. C.F.O. (NDZ)

Noul (