GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. 66/068/05/5/5/52/1932

Dated: 28/10/15

FIRE SAFETY CERTIFICATE

Certified that the M/S The Beaufort Inn Guest House building at 14/746, Main Mathura Road, Jungpura, New Delhi-110014, comprised of basement (storage only), ground floor (reception+4Rooms), 1st floor (06 Rooms), & 2rd floor (06 Rooms), total 16 guest rooms, was granted FSC by this department vide letter No. F6/MS/DFS/GH/2012/67, dated 09-01-2012. The premises was re-inspected by the officer concerned of this department on 17-10-2015 in the presence of Sh. Anil Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential (Guest House 16 guest rooms only) with effect from 28 10 June 2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dr.G.C.Misra)

Chief Fire Officer

T.No.011-23414333

Copy to:- 1. Joint Commissioner of Police, Licensing Branch, 1st floor, P.S. Defence Colony, New Delhi.

 M/S The Beaufort Inn Guest House building at 14/746, Main Mathura Road, Jungpura, New Delhi-110014

Conditions for the validity of fire safety certificate are under:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate on form J, six month prior to its expiry.



			N18				
1	Name & address & fill		INSPECTION F	REPORT			
	Name & address of the buil	ding	ing M/S The Beaufort Inn Guest House In the				
2	Type of Occurs		Tribud, 0	ungpura, New Delhi-1100	119 at 14/746,		
3	Type of Occupancy		residential & I c	Odding House "A"			
	Building Comprised of		Basement=Stora	ge GF=Reception LAD			
			1 .001 011001113, 2	2nd Floor=06 rooms. Total	Ins, 1st		
1	T		Rooms.	Total	- 16 Guest		
4	Type of case		Renewal				
5	Details of previous NOC			CH/2040/07 P			
6	Fire safety directives letter N	lo	Nil.	GH/2012/67, Dated 09.01.2	2012.		
7	Date of inspection						
8	Name of the inspecting Offic		17.10.2015				
			: ADO(S.J.) Vedpal				
9	Name and designation of offi	cers	•				
	from the building side		Mr Anil I				
	5 5145		Mr.Anil Kumar, Ma	anager.			
10	Year of construction						
	rear or construction		2000				
11	Applicant's letter No.						
S. NO.	Minimum Standards on fire		1924-29/ Joint. C.F	P/Lic(H), Dt 30.09.2015.			
	prevention and fire safety U	,_	NBC/ BBL 198;	3 Provided at site	Remarks		
	33	/K	Requirement		MR / NM		
1	Access to building						
	1) Road width		Accessible				
	2) Gate width		N/A	15m Provided	MR		
-	3) Width of internal road		AL/A	N/A	N/A		
2	Number, width Type & arran	geme	nt of exite	N/A	N/A		
	a. Number of staircases	300	III OI GAILS				
	1. Upper floors	-)1no.				
	2. basements		-wo	01no. Provided	MR		
	b. Width of staircase	-	WO	Two Provided	MR		
	1. Upper floors	1	.25 Mtr				
	2. basements	_		1.25m	MR		
	c. Protection of exits	1	.25 Mtr	1.10 & 1.7 Mtr Provide			
	1. Fire check door			- I Will I TOVIGE	UIVIK		
	2. Pressurization		/A	N/A	N/A		
		N	/A	N/A	N/A		
	d. No. of continuous stairca	ase R	equied	1 No. Stairs Provided	MR		
	e. Width of corridor				l'on c		
	f. Door size	N/		N/A	N/A		
3	Compartmentation.	1	Mtr	Provided	MR		
	Fire check door	-			Tivil		
	Sealing of electrical shafts	N/		N/A	N/A		
	3. Fire Rating of shaft door		equired	Provided	MR		
	4. water curtain	N/		N/A	N/A		
	5. Fire dampers	N//		N/A	N/A		
4	Smoke Management system.	N/A	4	N/A	N/A		
	agoment system.	20	-1-		-		
	Basement	30	a/c per hour	Exhaust fone			
	Jpper floors	- 12	a/c per hour	Exhaust fans provided	MR		
	Fire Extinguishers	-		Natural Ventilation	MR		
	Total numbers	+-					
	ypes	-		12 Nos	MR		
	SI marking	ISI		ABC, Co2,	MR		
11.				Yes			



N/19

6	First-Aid Hose Reels.	<u> </u>		1
	Total numbers on each floor	One	01no. Provided	MR
	Lawath of Hann work hann	30 m	Provided	MR
	Length of Hose reel hose	5 mm	Provided	MR
7	Nozzle Diameter Automatic fire detection and ala		Provided	IVIIX
1	Type of detectors	N/A	N/A	N/A
				1
	Location of Main Panel	N/A	N/A	N/A
	Location of Repeater panel	N/A	N/A	N/A
	Alternate source of power	Required	Battary Backup	MR
	hooter's location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	Basement	Required	Provided	MR
	Upper floors	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-corner	N/A	N/A	N/A
	Number of Hydrants per floor	N/A	N/A	N/A
	hose Box	N/A	N/A	N/A
12	Yard Hydrants.			
	total number of hydrants	N/A	N/A	N/A
	hose box	N/A	N/A	N/A
13	Pumping arrangements			
	1. Ground level			11/4
	a. Discharge of main Pump	N/A	N/A	N/A
	b. Head of main pump	N/A	N/A	N/A
	c.Number of main pumps	N/A	N/A	N/A
	d.jockey pump out put	N/A	N/A	N/A
	e.jockey pump head	N/N	N/A	N/A
	f. Standby Pump output	N/A	N/A	N/A
	g.Stanby Pump head	N/A	N/A	N/A
	h.Auto Starting/Manual stopping	N/A	N/A	N/A
	pump house access 2.Terrace level	N/A	N/A	N/A
	a. Discharge of pump	450LPM	450180LPM	MR
	b. head of the pump	40m	40m	MR
	c. Power supply	Required	Provided	MR
	d. Auto starting of pump	Required	Provided	MR
14	Captive water storage for fire			
	fighting 1. Underground tank capacity	N/A	N/A	N/A
	a. Draw-off connection	N/A	N/A	N/A
	b. fire service inlet	N/A	N/A	N/A
	c.Access to tank	N/A	N/A	N/A
	Over head tank Capacity	5,000 ltr	5,000 ltrs. Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of lifts.			
	a. Pressurization of lift shaft	N/A	N/A	N/A
	b. pressurization of lift lobby	N/A	N/A	N/A
	c. communication in lift car	N/A	N/A	N/A
	d. Fireman's grounding switch	N/A	N/A	N/A
	e. Lift signage	N/A	N/A	N/A



NID

47	Standby power supply	Required	Provided	MR
17	Refuge Area.	T TO Quinous	Not Required	
10	total area location			
19	Fire control room		la ital	MR
8	a. Detector system Panel b. Flow switch Panel c. PA system Panel d. Batter backup e. Building floor plans	Required	Provided	
		N/A	N/A	N/A
		N/A	N/A	N/A
		Required	Provided	MR
		N/A	N/A	N/A
	Special Fire Protection system	ama for protection of	fenecial risks if any:	
20	Special Fire Protection system	ems for protection of	i special floke, if any.	

The fire protection systems provided in the building were test checked randomly and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter No.F.6/DFS/MS/GH/2012/67, dated 09.01.12 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name

Vedpal

Designation : Assistant Divisional Officer (S.