GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ 1402 /1979

Dated: 04/11/15

FIRE SAFETY CERTIFICATE

Issued -- 4-14-15 -- at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

de m

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee, Akash Continental Dx. Guest House, 3202, Dispensary Lane, Pahar Ganj, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building:- Akash Continental Dx. Guest House,

3202, Dispensary Lane, Pahar Ganj, New

2. Type of occupancy:-

Residential Group A-1 Basement, Ground, + 3 Upper Floors (Total 13 Guest Rooms)

3. Type of case:-

4. Details of previous FSC :-No. F6/DFS/MS/GH/2012/4078 dated

31/10/2012.

5. Fire safety directives No.-

6. Date of inspection:-N/A 16/10/15

7. Name of the inspecting officer:-

8. Name & designation of officer D.O. Gurmukh Singh

From the building side:-

Sh. S.S.Rawat (Manager)

9. Year of construction:-

10. Applicant's letter No:-1715/Joint C.P/Lic. (H) dated 15/09/15

S.No. Minimum Standards on fire Requirement Old Case Prevention and fire safety Provided at site Remarks U/R 33 1. MR/NMR Access to Building 1) Road width 2) Gate width N/A 6 Mtr. N/A MR 3) Width of internal road N/A Number, Width Type & Arrangement of Exits N/A 2. NA NA A. Number of staircases 1. Upper floors 2. Basements 01 No 01 No. B. Width of staircase 01 No. MR 01 No. MR 1. Upper floors 2. Basements 80 cms 125 cms. C. Protection of exits 80 cms. MR 120 cms. 1. Fire check door MR 2. Pressurization N/A N/A D. No. of continuous N/A N/A N/A staircase to terrace N/A N/A N/A N/A E. Width of corridor F. Door size N/A N/A 3. N/A Compartmentation 1 Mtr. 1 Mtr. MR 1) Fire check door N/A 2) Sealing of electrical shafts N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A N/A N/A 5) Fire Dampers N/A 4. N/A N/A Smoke Management System N/A N/A 1) Basements 30 ACPH 2) Upper floors Exhaust fan 5. 12 ACPH Fire Extinguishers MR Natural 1) Total numbers MR 10 Nos. 10 Nos MR

| | (a) T | | | |
|-----|--------------------------------|----------------|------------|-------|
| | 2) Types | ABC & CO2 | ABC, CO2 & | MA |
| | 3) ISI marking | Required | Provided | MR |
| 6. | First-Aid Hose Reel | 1 | | |
| | 1)Total number of each | 01 no. | 01 no. | MR |
| | floor | 3V | | |
| | 2) Length of hose reel hose | 30 Mtr. | 30 Mtr. | MR |
| _ | 3) Nozzle diameter | 5 mm | 5 mm | MR |
| 7. | Automatic Fire Detection & A | larming System | | |
| | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA | Required | Provided | MR |
| 9. | Public Address System | Required | Provided | MR |
| | /Intercom | | | |
| 10. | Automatic Sprinkler System | | | |
| | 1) Basement | Required | Provided | MR |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false | N/A | N/A | N/A |
| | ceiling | | 11/11 | 14/24 |
| 11. | Internal Hydrants | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A |
| | 2) Number of hydrants per | N/A | N/A | N/A |
| | floor | 1 1/1 1 | IV/A | IN/A |
| | 3) Hose box | N/A | N/A | N/A |
| 12. | Yard Hydrants | 11/11 | IWA | IN/A |
| | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | |
| 13. | Pumping Arrangement | 14/11 | IN/A | N/A |
| 13. | 1) Ground Jevel | NI/A | NI/A | 77/ |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | N/A | N/A | N/A |
| | b) Head of main pump | N/A | DIA | - |
| | | | N/A | N/A |
| | T | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | ** | | |
| | 2) Terrace level | | | |
| | a) Discharge of pump | 450 LPM | 450 LPM | MR |
| | b) Head of pump | 30 Mtr. | 30 Mtr. | MR |
| | c) Power supply | Required | Provided | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| 4. | Captive Water Storage for Fire | Fighting | | |
| | | N/A | N/A | N/A |

| | capacity | | | |
|--------------|--|-----------|------------|-----------------|
| 1 | a) Draw-off connection | N/A | N/A | > T/4 |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | 5000 Ltr. | 5,000 Ltr. | N/A MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | Trovided | IVIK |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| 17. | e) Lift signage | N/A | N/A | N/A |
| EST 000 \$20 | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| 0 | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | | | N/A |

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2012/4078 dated 31/10/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Dy. C.F.O. (NDZ)

Gurmukh Singh Divisional Officer

Laft