FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS (MS/School/2015/W2/1992

Dated: 105 11 15

FIRE SAFETY CERTIFICATE

Certified that the Dropati Davi Memorial Education Society located at Ground pus two upper floors Plot no. NS-2,R Block, Pitam Pura Delhi in a building comprised of Basement + Ground + 02 Upper Floors was issued FSC vide Letter No. F6/MS/DFS/2012/537 Dated 17-02-2012. The premises was re inspected by the officer concerned of this department on 20-10-2015 in the presence of Sh S K Jain (Director) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance NBC and that the premises (Ground + 02 upper floors Except Basement) is fit for occupancy class "Educational" Group B with effect from 65/41/15 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 05/11/15 ... at New Delhi by.

(Santokh Singh) Chief Fire Officer Delhi Fire Service Tel. 011-23424250

Copy to: The Principal, Dropati Davi Memorial Education Society Plot no. NS-2, RP Block, Pitam Pura

Following fire safety directives must be adhered to:

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- Basement shall not be used for any purpose without getting clearance from this department.

INSPECTION REPORT

1. Name & address of the building: Dropati Davi Memorial Education Society located at Plot no. NS-2,R Block,Pitam Pura Delhi

2. Type of Occupancy : Educational at Ground + two upper floors in a building comprised of Basement + Ground + 2 Upper Floor(Basement Sealed & not be used for any purpose)

3. Type of Case : Renewal

4. Details of previous NOC : F6/MS/DFS/2012/537 Dated 17-02-2012

5. Fire Safety directives Letter No.: F-6/DFS/MS/2011/BP/335 dated 18-02-

2011

6. Date of inspection : 20-10-2015

7. Name of the Inspecting Officer: Udaivir Singh, ADO (WP)

8. Name and designation of Officer

from the building side : Sh. SK Jain (Director)

9. Year of Construction : 2012

10. Applicant's letter No. : nil Dated nil

No of students-350 class rooms-14 Plot area – 753m² covered area = 2.53 m²

Upper Floors – 251m²

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR
1.	Access of building Road width Gate width Width of internal road Number, width, Type & Arrange	12 mtrs 4.5m NA	23.5 mtrs Provided NA	MR MR NA
2.	 a. Number of staircases Upper floors Basements b. Width of staircases Upper floors 	2 2 1x1.5m&1x1.25m	Provided 01Provided Provided 1x1.5m	MR NA MR NA
	 Basements c. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 	1.5mtrs NA NA 1x1.5m&1x1.25m 1.5m 100cm	NA NA	NA NA MR MR MR

	ttotion			> Y A	
. (Compartmentation	NA	NA	NA	
	• Fire check door	NA	NA	NA	
	 Sealing of electrical 	NA			
	shafts	NIA	NA	NĄ	
	 Fire Rating of shaft 	NA	NA	NA	
	door	NA	NA	NA	
	 Water Curtain 	NA	1 17 1		
	• Fire Dampers				
4.	Smoke managements System	Required	Not Provided	NA	
	 Basements 	NA	NA	NA	
	• Upper floors	INT			
5.	Fire Extinguishers	10	Provided	MR	
	 Total numbers 	10 nos.	Provided	MR	
	Types	ABC & CO ₂	Provided	MR	
	 IS marking 	ISI marked	110 1100		
6.	First – Aid Hose Reels		Provided	MR	
0.	• Total numbers on each	1	Provided		
	floor	- 1.50 mark 100 mark	Provided	MR	
	 Length of hose reel 	30m	Provided	1111	
	hose		Provided	MR	
	Nazzla diameter	5mm	Provided	11111	
7.	Automatic fire detection and al	arming system	T A	NA	
1.	• Type of detectors	NA	NA	NA	
	Location of Main Pane	NA NA	NA	NA	
	r f Daneater	NA	NA	INT	
	Panel		3.41	NA	
	All mate gourge of	NA	NA	INA	
				NIA	
	powerHooters' Location	NA	NA	NA	
		Required	Provided	MR	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	required		;	
10.		Required	Provided	MR	
	 Basements 	NA	NA	NA	
	• Upper Floor	NA	NA	NA	
	 Sprinkler above false 	11/1			
	ceiling				
11	. Internal Hydrants:	Dagwined	Provided	MR	
	 Size of riser/down- 	Required	Provided	MR	
	comer	1	1101100		
	 Number of hydrants 	per	Provided	MR	
	floor	1	1101100		
	 Hose Box 				
1	2. Yard Hydrants				
1					
			3. T. A	NA	
	Total number of	NA	NA	NA NA	
	hydrants	NA	NA	INL	
	• Hose Box				
	1105¢ D0A				

	amping Arrangements:			
	Ground Level		NIA	NA
	 Discharge of main 	NA	NA	NA
	pump	NA	NA	NA
	Head of main pump	NA	NA	NA NA
	Number of main pumps	NA	NA	NA
	> Jockey pump out put	NA	NA	NA
	Jockey pump head	NA	NA NA	
	> Standby Pump out put	NA	NA	NA
	> Standby Pump Head	NA	NA	NA
	> Auto Staring/Manual) T.A	NIA
	stopping	NA	NA	NA
	> Pump House Access		7 111	MD
	Terrace level	1X450 lpm	Provided	MR
	Discharge of pump	40Mtr	Provided	MR
	> Head of the pump	Required	Provided	MR
	> Power supply	Required	Provided	MR
	> Auto starting of pump	ation or		
14.	Captive water Storage for firefigl	NA	NA	NA
	 Underground tank 	NA	TVI	
	capacity	NA	NA	NA
	> Draw off connection	NA NA	Provided	NA
	> Fire service inlet	NA NA	NA	NA
	Access to tank		Provided	MR
	 Overhead Tank capacity 	10,000Ltr	10,000litres	14110
		Required	Provided	MR
15	Exit Signage	Required	TTOVICE	1111
16.	Provision of Lifts	NA	NA	NA
	> Pressurization of Lift	NA	TVI	1111
	Shaft	NA	NA	NA
	Pressurization of lift	IVA	1471	
	lobby Communication in lift	Required	Provided	MR
	Car	Required	1101100	W. 1997
	Fireman's Grounding	Required	Provided	MR
	Switch	required	1.07.00	
	► Lift Signage	Required	Provided	MR
	Z Litt Signage	Required		
17.	Standby power supply	NA	NA	NA
18.	Refuge Area			
	> Total area	NA	NA	NA
	Location	NA	NA	NA
19.	Fire control room			
	Detector system panel	NA	NA	NA
	> Flow Switch Panel	NA	NA .	NA
	> PA System Panel	NA	NA	NA
	➤ Battery backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA

Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA
Note:-General requirements for			

Note:-General requirements for schools as per Director of Education circular dated 01/03/2011.

- 2. LPG cylinders in laboratories NA
- 4. Electric meter boardNot under the staircase....
- 5. Basement use as per BBL 1983 ... NA
- 6. Emergency telephone no. board ... Displayed....
- 7. Generator setNA...

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/MS/DFS/2012/537 Dated 17-02-2012 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Note.; Earlier FSC was issued for all floors (Basement + Ground + two Upper Floors) Now School management submit undertaking to seal the basement. Hence FSC is recommended for upper floors without basement.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name Way Vir Sing 4
Designation ASolup

Name

Designation

