GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/GH/2015/ NOZ 1886

Dated : 04/11/15

FIRE SAFETY CERTIFICATE

Certified that the M/s Leo Guest House, 3357, Gali Hari Mandir, Pahar Ganj, New Delhi comprised of Ground + 5 Upper Floors (Ground floor reception + 01 guest room + office + 01 store, 1st floor to 4th floor 06 guest rooms at each floor, 5th floor sealed total 25 guest rooms) was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/4167 dated 07/11/2012. The premise was re-inspected by the officer concerned of this department on 20/10/15 in the presence of Sh. Ranbir (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 25 guest rooms only as above with effect from --0-4-4-4-4-5----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 04/11/15—at New Delhi by.

Chief Fire Officer Delhi Fire Service

Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee, M/s Leo Guest House, 3357, Gali Hari Mandir, Pahar Ganj, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		- 17-14				
	127	SPECTION RE	PORT			
	1. Name & address of the buildi	ng:- M/s Leo	Guest House, 3357	Gali Hari		
			Pahar Ganj, New Do	, Gan Hari		
	2. Type of occupancy:-	Resident	ial Group A-1 Group	ziii.		
		+ 5 Unne	er Floors.(25 guest r	ina		
-	3. Type of case:-	Renewal	21 1001s.(25 guest r	ooms)		
4	4. Details of previous FSC:-		(S/DFS/GH/2012/41	(7.1		
		07/11/201	3	6 / dated		
	5. Fire safety directives No	N/A	. 4.			
(b. Date of inspection:-	20/10/15				
7	7. Name of the inspecting officer:- D.O. Gurmukh Singh					
8	3. Name & designation of office	er D.O. Gui	nukn Singn			
	From the building side:-		· () /-			
9	. Year of construction:-	2008	r (Manager)			
10	O. Applicant's letter No:-		1 1 1 22 12 2 1 =			
	11	MII- Dair	y dated 23/09/15			
S.No.	Minimum Standards on fire	Doggi		Old Case		
	Prevention and fire safety	Requirement	Ctc Ditc	Remarks		
	U/R 33	(PSS Area)	PSS	MR/NMR		
1.	Access to Building			1 1		
	1) Road width	N/A	4 mtr.	MD		
	2) Gate width	N/A	N/A	MR		
	3) Width of internal road	N/A		N/A		
2.	Number, Width Type & Arra	ngoment of F	N/A	N/A		
	A. Number of staircases	ingement of Exit	S			
	1. Upper floors	01.37				
	2. Basements	01 No.	01 No.	MR		
	B. Width of staircase	N/A	N/A	N/A		
	1. Upper floors	80 cm.	125 cm.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits			11111		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01 no.	01 no.	MR		
	staircase to terrace		~ I 110.	IVIK		
	E. Width of corridor	N/A	N/A	NI/A		
	F. Door size	1 mtr.	1 mtr.	N/A		
	Compartmentation		1 11111.	MR		
	1) Fire check door	N/A	N/A	NT/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		

N/A N/A 5) Fire Dampers N/A N/A N/A Smoke Management System 4. 1) Basements 30 ACPH N/A N/A 2) Upper floors 12 ACPH Natural MR 5. Fire Extinguishers

N/A

N/A

N/A

N/A

N/A

2) Sealing of electrical shafts

3) Fire rating of shaft door

4) Water curtain

1) Total numbers 10 Nos. 10 Nos. MR 2) Types ABC & CO2 ABC &CO2 MR

N/A

N/A

	3) ISI marking						
6.	3) ISI marking First-Aid Hose Reel	Required	Provided	MR			
0.							
	1)Total number at each floor	01 no.	01 no.	MR			
	2) Length of hose reel hose	20	*				
	3) Nozzle diameter	30 mtr.	30 mtr.	MR			
7.	Automatic Fire Detection &	5 mm.	5 mm.	MR			
	Automatic Fire Detection & Alarming System 1) Type of detectors N/A N/A						
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System	Required	Provided	MR			
0.	Automatic Sprinkler System	Required	Provided	MR			
	Automatic Sprinkler System 1) Basement N/A N/A						
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling	N/A	N/A	N/A			
1.	Internal Hydrants		1				
	1) Size of riser/down-comer	27//					
	2) Number of hydrants per	N/A	N/A	N/A			
	floor	N/A	N/A	N/A			
	3) Hose box	271					
2.		N/A	N/A	N/A			
	Yard Hydrants						
	1) Total number of hydrants 2) Hose box	N/A	N/A	N/A			
		N/A	N/A	N/A			
•	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	pump		The second second	14/11			
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pump	N/A	N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump output	N/A	N/A	N/A			
	g) Stand by pump head	N/A	N/A	N/A N/A			
	h) Auto starting/Manual	N/A	N/A	N/A N/A			
	stopping		- 11.2	IN/A			
	2) Terrace level						
	a) Discharge of pump	225 LPM	Provided	MR			
	b) Head of pump	30 Mtr.	30 Mtr.				
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump	Required	Provided	MR			
	Captive Water Storage for Fire I	Fighting	TTOVICE	MR			
		N/A	NT/A				
	1) Onder ground tank	V/A					
	capacity	N/A	N/A	N/A			

- N-16

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1		1.121
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			

Shortcoming issued vide letter No. F6/DFS/MS/GH/2015/1680 dated 29.07.15 found rectified.

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2012/4167 dated 07/11/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh Divisional Officer

DYC FO(NDZ)