## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001

NO. F6/DFS/MS/CGHS/2015/ SZ/ / 993

Dated: 05 11 15

## FIRE SAFETY CERTIFICATE

Certified that the Ashoka Enclave CGHS Ltd. Plot No. 8A, Sector-11, Dwarka, New Delhi-110075, comprised of basement, ground plus eight upper floors having Five blocks owned / occupied by Ashoka Enclave CGHS Ltd. was granted NOC by this department vide letter no. F6/DFS/MS/CGHS/2005/2613 dated 19.12.2005. The building was re-inspected by the officers concerned of this department on 26.10.2015 in presence of Sh. B.R.Premi (Member) & Sh. Umesh Dutt (Supervisor) and found that premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy of class A-4, Residential Building (Apartment) with effect from for a period of Five years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed everleaf.

(Dr. G C Misra) Chief Fire Officer

Ph.011-23414333

## Copy to:

1 Sh.R K Chaudhary (Secretary), the Ashoka Enclave CGHS Ltd. Plot No. 8A, Sector-11, Dwarka, New Delhi-110075.

## **CONDITIONS**

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering nonfunctional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

			-/		
	<u>IN</u>	SPECTION			
1	Name & address of the building	Ashoka En	clave CGH	S Ltd. Plot No.8A,	Sector-11,
		Dwarka, N	ew Delhi-1	10077.	
2	Type of Occupancy	Residentia	I Buildina '	'A" (Apartment)	
3		Renewal		(- (	
	Type of case	F6/DFS/MS/CGHS/2005/2613 dated 19.12.2005			10.0005
4	Details of previous NOC				
_		The state of the s		002/584 dated 8.4.2	
5	Fire safety directives letter No	F6/DFS/MS/CGHS/BP/2010/2152 dated 20.7.2010			20.7.2010
6	Date of inspection	26.10.2015			
	Name of the inspecting Officers :	DO SK Tor	nar, ADO	SP Bhardwaj	
7					
8	Name and designation of officers	Sh. B R Premi (Member) & Sh. Umesh Dutt			Dutt
	from the building side	(Supervisor)			
	Year of construction	2005			
9		0.000			,
	Applicant's letter No.	4723 Dated.		basement,	Having Five
		18.9.2	2015		Blocks
				upper floors,	
10					
S.	Minimum Standards on fire	NBC Requ	uirement	Provided at site	Remarks
NO.	prevention and fire safety U/R 33				MR / NMR
	1	-			
1	Access to building				
	1) Road width	30 Mtr		30 Mtrs.	MR
	2) Gate width	6 Mtrs.		6 Mtrs.	MR
	3) Width of internal road	Old case		5.30 to 12.70	MR
2	Number, width Type & arrangement	of exits			
	a. Number of staircases				
	1. Upper floors	2 Nos. eac	h block	2 Nos.	MR
	2. basements	3 Nos. + 1	Ramp	3 Nos. + 1 Ramp	MR
	b. Width of staircase				
-	1. Upper floors	1.10 & .85 Mtrs.		1.10 & .85 Mtrs.	MR
					0
		1.17 Mtrs. & 1 Ramp		1. 17 Mtrs. +	
	2. basements			Ramp 6.46 Mtrs.	MR
				ramp o. 10 ivitro.	
	c. Protection of exits				
	1. Fire check door	N/A		N/A	N/A
	2. Pressurization	N/A		N/A	N/A
	d. No. of continuous staircase to	Requied		Provided	MR
	terrace	Requieu		riovided	
	e. Width of corridor	1.01 Mtr.		1.17 to 1.78 Mtrs.	MR
	f. Door size	1 Mtr.		1 Mtr.	MR
3	Compartmentation.				
	1. Fire check door	N/A		N/A	N/A
	Sealing of electrical shafts			Provided	MR
	3. Fire Rating of shaft door			N/A	N/A
	4. water curtain	N/A		N/A	N/A
	5. Fire dampers	N/A		N/A	N/A
4	Smoke Management system.	Α	3		
	*			Exhaust force	MR
	basement	30 a/c per		Exhaust fans	IVIT
		12 a/c per	hour	Natural Ventilation	MD
	upper floors		6- 5	ivatural ventilation	IVIK

	Fire Extinguishers		00 No.	MR
	total numbers	2 Nos. for 1000 Sq.	63 Nos	MR
-	Types	Mtrs.Co2/ABC	ABC	MR
	ISI marking	ISI Marked	ISI Marked	IVIIX
	First-Aid Hose Reels.		One each block	
	total numbers on each floor	1 No.	One each block	MR
			30 Mtrs.	TVII X
	Length of Hose reel hose	30 m	30 10103.	MR
		5 mm	5 mm.	
	Nozzle Diameter	5 111111		MR
	Automatic fire detection and alarm	ing system		
7		N/A	N/A	N/A
	Type of detectors	N/A	N/A	N/A
	location of Main Panel	N/A	N/A	N/A
	location of Repeater panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	hooter's location	Required	Provided	MR
8	MOEFA	Required	Provided	MR
9	Public Address System.  Automatic Sprinkler System.			1.45
10		Required	Provided	MR
	basement	N/A	N/A	N/A
	upper floors	N/A	N/A	N/A
	sprinkler above false ceiling			Lin
11	Internal Hydrants Size of riser/down-corner	150 MM	150 MM	MR
	Size of risel/down-corner	One	One each block	MR
	Number of Hydrants per floor	One	One edem see	
	Number of Frydrams per	Required	One each block	MR
	Hose Box	required		
12	Yard Hydrants.		O h block	MR
14	Total number of hydrants	One each Block	One each block	MR
	Hose box	Required	Provided	IVIIX
13	Pumping arrangements	4.		
	1. Ground level/		1620 LPM	MR
	a. Discharge of main Pump	1620 LPM	70 Mtrs.	MR
	b.Head of main pump	70 Mtrs.		MR
	c.Number of main pumps	One	One 180 LPM	MR
	d.jockey pump out put	180 LPM	70 Mtrs.	MR
	e.jockey pump head	70 Mtrs.	N/A	N/A
	f. Standby Pump output	N/A	N/A	N/A
	g Stanby Pump head	N/A	Provided	MR
	h.Auto Starting/Manual stopping	Required	Provided	MR
	pump house access	Required	FTOVIded	1,3,1,2
	2.Terrace level	000 1 DM	Provided	MD
		900 LPM	Tovidod	MR
	a. Discharge of pump	40 Mtr	Provided	MR
	b. head of the pump		Provided	MR
	c. Power supply	Required		MR
	d. Auto starting of pump	Required	Provided	LIVITY
	Captive water storage for fire	-		
1	4 fighting	, B	Described	MR
- 1	Underground tank capacity	50, 000 Ltrs	Provided	MR
	a. Draw-off connection	Required	Provided	MR
-	b. fire service inlet	Required	Provided	MR
	c.Access to tank	Required	Provided	MR
	Over head tank Capacity	2,000 Ltrs.	Provided	IVIIX

Exit Signage.	Required	Provided	MR	
	N/A	N/A	N/A	
	N/A	N/A	N/A	
c communication in lift car	Required	Provided	MR	
		Provided	MR	
		Provided	MR	
		DG Set	MR	
		Not Required		
PAGE STORY CONTROL OF THE STORY			Total	
	N/A	N/A	N/A	
	N/A	N/A	N/A	
	Required	Provided	MR	
	Required	Provided	MR	
o Building floor plans	N/A	N/A	N/A	
Special Fire Protection systems for protection of special risks, if any: ABC				
Opedia i ii di i rete e ii e i e j	<b>'</b>			
	Exit Signage.  Provision of lifts.  a. Pressurization of lift shaft b. pressurization of lift lobby c. communication in lift car d. Fireman's grounding switch e. Lift signage Standby power supply Refuge Area. total area location Fire control room a. Detector system Panel b. Flow switch Panel c. PA system Panel d. Batter backup e. Building floor plans Special Fire Protection systems for	Provision of lifts.  a. Pressurization of lift shaft b. pressurization of lift lobby c. communication in lift car d. Fireman's grounding switch e. Lift signage Required Standby power supply Refuge Area.  total area location Fire control room a. Detector system Panel b. Flow switch Panel c. PA system Panel d. Batter backup e. Building floor plans Special Fire Protection systems for protection of special	Provision of lifts.  a. Pressurization of lift shaft b. pressurization of lift lobby c. communication in lift car d. Fireman's grounding switch e. Lift signage Standby power supply Refuge Area.  Total area location Fire control room a. Detector system Panel b. Flow switch Panel c. PA system Panel d. Batter backup e. Required N/A N/A N/A N/A N/A N/A N/A N/A N/A Required Provided N/A N/A N/A N/A Required Provided Provided Provided Provided Provided Provided Provided Provided N/A	

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standard on fire prevention fire safety measures required under the rules, renewal of fire safety certificate under rule 35 of Delhi Fire Service Rules 2010 is recommended.

Note: On the date of inspection it was found that no alteration have been done as per directions dated 20.7.2010.

Signature of the Inspecting Officer

Name

S.P Bhardwaj

Designation

ADO (DWARKA)

5. K. Gomar

Bo (sw)