GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2015/ 102/2022

Dated : 09/11/15

FIRE SAFETY CERTIFICATE

Certified that the YMCA Tourist Hostel located at 1, Jai Singh Road, New Delhi. The Tourist Hostel have A and B Block. A Block comprised of Ground + 3 Upper floor, Ground floor (Reception + 02 office), 1st floor to 3rd floor (10 guest rooms at each floor). B Block comprised of Ground + 05 Upper floor, Ground floor (Office + 02 guest rooms), 1st floor (12 guest rooms), 2nd floor (13 guest rooms), 3rd floor(15 guest rooms), 4th floor (15 guest rooms) and 5th floor (13 guest rooms), total 100 guest rooms was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/1213 dated 04/04/12. The premises was reinspected by the officer concerned of this department on 03/11/15 in the presence of Sh. Ivan Philemon (Dy. Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 100 guest rooms only as above with effect from - 29 from for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -69/41-5---at New Delhi by.

(**Dr. G.C. Misra**) Chief Fire Officer Ph-011-23414333

Ofc Me

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Dy. Manager,

YMCA Tourist Hostel located at 1, Jai Singh Road, New Delhi Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT 1. Name & address of the building:-YMCA Tourist Hostel located at 1, Jai Singh Road, New Delhi. Residential, Sub Division-A-1, Hostel 2. Type of occupancy:-(A Block G+ 3floor & B Block Gr. + 05 floors) 3. Type of case:-4. Details of previous FSC:-No. F6/MS/DFS/GH/2012/1213 dated 04/04/12. 5. Fire safety directives No.-N/A 6. Date of inspection:-03/11/15 7. Name of the inspecting officer:-Sh. G.S. Chauhan DO (CD), Sh. Manoj Kumar Sharma (ADO/CC) 8. Name & designation of officer From the building side:-Sh. Ivan Philemon (Dy. Manager) 9. Year of construction:-10. Applicant's letter No:-No. Nil dated 28/10/2015. Old Case S.No. Minimum Standards on fire Requirement Provided at site Remarks Prevention and fire safety Existing **PSS** MR/NMR U/R 33 Access to Building 1) Road width 09 mtr. 12 mtr. MR 2) Gate width 05 mtr. 05 mtr. MR 3) Width of internal road 06 mtr. 06 mtr. MR Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 03 Nos. A-Block 01 Nos. MR B-Block 02 Nos. 2. Basements N/A N/A N/A B. Width of staircase A-Block 01 Nos. 1.15 1. Upper floors 1.25 mtr. MR B-Block 02 Nos. 1.25 mtr. 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door Required Provided MR 2. Pressurization N/A N/A N/A D. No. of continuous 01 01 MR staircase to terrace E. Width of corridor 1 mtr. 1.5 mtr. MR F. Door size 1 mtr. 1 mtr. MR Compartmentation 1) Fire check door Required Provided MR 2) Sealing of electrical shafts Required Provided MR 3) Fire rating of shaft door Required Provided MR 4) Water curtain N/AN/A N/A 5) Fire Dampers N/A N/A N/A Smoke Management System

30 ACPH

12 a/c per

hour

N/A

Natural

1.

2.

3.

4.

1) Basements

2) Upper floors

Me

N/A

MR

				8
5.	Fire Extinguishers	40 Nos.	40 Nos.	MR
	1) Total numbers	ABC & CO2	ABC & CO2	MR Q
	2) Types	Required	Provided	MR
	3) ISI marking	Required	1101100	
6.	First-Aid Hose Reel	01	01	MR
	1) Total number of eachfloor	30 mtr.	30 mtr.	MR
	2) Length of hose reel hose	05 mm	05 mm	MR
	3) Nozzle diameter			
7.	Automatic Fire Detection &	Required	Provided	MR
4	1) Type of detectors	Required	Provided	MR
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	Required	Provided	MR
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location		Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	TVIIC
10.	Automatic Sprinkler System	1	N/A	N/A
	1) Basement	N/A	Provided Provided	MR
	2) Upper floors (Kitchen)	Required		N/A
	3) Sprinkler above false	N/A	N/A	IVII
	ceiling			
11.	Internal Hydrants	100	100 mm	MR
ž.	1) Size of riser/down-comer	100 mm		MR
	2) Number of hydrants per	01	01	IVIIC
	floor		0.1	MR
	3) Hose box	01	01	IVIIC
12.	Yard Hydrants	MR		
	1) Total number of hydrants	02	02	MR
	2) Hose box	02	02	IVIIC
13.	Pumping Arrangement			
	1) Ground level		15(0 I DM	MR
	a) Discharge of main	1560 LPM	1560 LPM	IVIIC
	pump .	10	10 mtm	MR
	b) Head of main pump	40 mtr.	40 mtr.	MR
	c) Number of main pur		01	MR
	d) Jockey pump out pu	t 180 LPM	180 LPM	MR
	e) Jockey pump head	70 mtr.	70 mtr.	MR
	f) Stand by pump outp	ut 1560 LPM		MR
	g) Stand by pump head	40 mtr.	40 mtr. Provided	MR
	h) Auto starting/Manua	al Required	Provided	IVIIX
	stopping			
	2) Terrace level	200 7 77 7	OOOIDM	MR
	a) Discharge of pump	900 LPM		MR
	b) Head of pump	40 mtr.	40 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump Required Provided		IVIK	
14.	Captive Water Storage for	or Fire Fighting	1 00 000 1/	N/A
1.10	Under ground tank capacity	50,000 ltr.	1,00,000 10	
	a) Draw-off connection	n Required	Provided	MR
	b) Fire service inlet	Required	Provided	MR
	1	Required	Provided	MR
	d) Over head tank	20,000 ltr	. 20,000 ltr.	N/A
	capacity	Daguinad	Provided	MR
15.	Exit Signage.	Required	TTOVICC	

1. 148

· ON

		1		
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room			
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			ABC & Co ₂

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/2015/746 dated 17/04/2015 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/MS/DFS/GH/2012/1213 dated 04/04/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - G.S Chauhan Designation: - DO (CD)

Signature of the Inspecting Officer

Name: - M.K. Sharma
Designation: - ADO (CC)