GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F6/DF5/MS/Schal/2015/NIPZ/2049

Dated /3/11/15

FIRE SAFETY CERTIFICATE

Certified that the Shri R.B. Public School at E-135, Dilshad Garden, Mangal Bazar, Delhi-110095, comprised of ground plus two upper floors owned/occupied by Shri R.B. Public School have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 29/10/2015 in the presence of Mr. Deepak Sharma, Principal of the school and found that the GF+FF+SF of building is fit for occupancy class "B" 'Educational Building' with effect from ... ps/pl/ps... for a period of **three** years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on 13/11/15 at New Delhi by

(Dr. G.C. Misra) Chief Fire Officer Ph.011- 23414333

ole M

To.

The Manager, Shri R.B. Public School, E-135, Dilshad Garden, Mangal Bazar, Delhi-110095

Copy to:-

The Dy. Director of Education, B-Block, Yamuna Vihar, North-East, Delhi-110053 1. Name & address of the building : Snri R.B. Public Scriool, E-135, Dilshad Garden, Mangal Bazar, Delhi-110095

Ground plus two upper floors

3. Type of Occupancy : Educational

4. Type of Case : New

2. Building is comprised of

5. Details of Previous NOC letter : Nil

6. Fire Safety direction letter No : NBC Part-IV

7. Date of Inspection : 29/10/2015

8. Name of the Inspecting officers : ADO Vijay Bahadur

Name and designation of Officer

from the building side : Mr. Deepak Sharma (Principal)

10. Year of Construction : 2011

11. Applicant's letter No. -RB/015/25, Dated- 28/09/2015

Sr. No.	Minimum Standards on Fire Prevention and Fire Safety U/R33	NBC Part-IV Requirement	Provided at Site	Remarks MR/NMR			
01							
	Road width	06 mtr.	06 mtr.	MR			
	Gate width	N/A	N/A	N/A			
	Width of internal road	N/A	N/A	N/A			
02	Number, Width, Type and Arrangement of Exits.						
	a. Number of Staircases						
	 Upper floor 	01 Nos.	01 Nos.	MR			
	Basement	N/A	N/A.	N/A			
	b. Width of Staircases		4.50	MO			
	 Upper floor 	1.50 mtr.	1.52 mtr.	MR			
	Basement	N/A	N/A	N/A			
	c. Protection of exits	21/4	NIA	N/A			
	 Fire check door 	N/A	N/A	N/A			
	 Pressurization 	N/A	N/A				
	d. No. of Continuous Staircases to Terrace	01 Nos.	01 Nos.	MR			
	e. Width of Corridor	1.50 mtr.	♦ 02 mtr.	MR			
	f. Door Size	01 mtr.	01 mtr.	MR			
03	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire dampers	N/A	N/A	N/A			
04	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
05.	Fire Extinguishers.						
	Total numbers	06 nos.	07 nos.	MR			
	Types	ABC /CO ₂	ABC /CO₂	MR			
	IS marking	ISI marked	ISI marked	MR			

Width of corridor widened by removing devider in central corridor.

06	First-Aid-Hose Reels.						
	Total numbers on each floor	01 No.	01 No.	MR			
	Length of hose reel hose	30 mtr.	30 mtr.	MR			
	Nozzle diameter	05 mm	05 mm	MR			
07	Automatic Fire Detection and Alarming System.						
	Type of detectors	N/A	N/A	N/A			
	Location of main panel	N/A	N/A	N/A			
	 Location of repeater panel 	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooter's location	N/A	N/A	N/A			
08	MOEFA	N/A	N/A	N/A			
09	Public Address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	upper floor	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	➢ Ground Level						
	Discharge of main pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby pump out put	N/A	N/A	N/A			
	Standby pump head	· N/A	N/A	N/A			
	 Auto Starting /Manual stopping 	N/A	N/A	N/A N/A			
	Pump house access Terrace Level	N/A	N/A	IVIA			
		450 1	4501.00	MD			
distance representative specific property and the second	Discharge of pump	450 Lpm.	450 Lpm. 40 M	MR MR			
	Head of the pump	40 M Required	Provided	MR			
	Power supply Auto Starting of numb	Required	Provided	MR			
4.4	Auto Starting of pump Carting Meter Starting for Fire Fighting	required	7 1001000	1			
14	Captive Water Storage for Fire Fighting.	N1/A	N/A	N/A			
	Underground tank capacity	N/A N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank Access to tank	10,000 Ltr.	10,000 Ltr.	MR			
4E	Overhead tank capacity Evit Signage	Required	Provided	MR			
15	Exit Signage.	required	liovided	1011			

	Pressurization of lift shaft	N/A	N/A	N/A			
	Pressurization of lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
***************************************	Firemen's grounding switch	N/A	N/A	N/A			
	Lift signage	N/A	N/A	N/A			
17	Standby Power Supply	N/A	N/A	N/A			
18	Refuge Area.						
	Total area	N/A	N/A	N/A			
	 Location 	N/A	N/A	N/A			
19	Fire Control Room						
	Detector system panel	N/A	N/A	N/A			
	Flow switch panel	N/A	N/A	N/A			
	PA system panel	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
20	Building floor plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of Special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were tested/checked at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the NBC Part-IV, it is recommended to grant Fire Safety Certificate.

Signature of the Inspecting Officer Name- Vijay Bahadur Designation- A.D.O

O EDI