GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. F6/DFS/ms/9/1/2015/52/2058

0

Dated: | 6 | 11 | 15

FIRE SAFETY CERTIFICATE

Certified that the M/S "Hamilton Lodge" Guest House located at S-153, Panchsheel Park, New Delhi-110017, comprised of ground floor (reception+ owner's residence), 1st floor (05 Rooms), 2rd floor (11 Rooms) & 3rd floor (6 Rooms), total 22 guest rooms, owned/occupied by Hamilton Hotel Pvt. Ltd was granted FSC by this department vide letter No. F6/DFS/MS/GH/2012/3319, dated 11-09-2012. The premises was re-inspected by the officer concerned of this department on 05-11-2015 in the presence of Sh. Gurdeep Singh and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential (Guest House 22 guest rooms only) with effect from 2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on. 1.6. 11. 2015 at New Delhi by.

(Dr.G.C.Misra)

Chief Fire Officer

T.No.011-23414333

- Copy to:- 1. Joint Commissioner of Police, Licensing Branch, 1st floor, P.S. Defence Colony, New Delhi.
 - 2. M/S "Hamilton Hotel Pvt. Ltd" Guest House located at S-153, Panchsheel Park, New Delhi-110017.

Conditions for the validity of fire safety certificate are under:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate on form J, six month prior to its expiry.

N/30

		N/3	.0			
		INSPEC	CTION REPO	DRT		
1	Name & address of the building			vt. Ltd" Guest House lo	cated at S-153,	
2		Panchsheel Park, New Delhi-110017.				
2	Type of Occupancy	Residential & Lodging House "A"				
3	Building Comprised of	GF=Reception + Owner's Residence, 1st floor=5Rooms 2nd				
				oor=6Rooms. Total=22		
4	Type of case	Renewal		, , , , , , , , , , , , , , , , , , , ,		
			VINAC (0040)	LU0004 D 1 100 00 00	240	
5	Details of previous NOC	No.F6/DFS/MS/2012/GH/2221, Dated 20.06.2012.				
6	Fire safety directives letter No	Nil.				
7	Date of inspection	05.11.2015				
8	Name of the inspecting Officers :	: ADO(S.J.) Vedpal				
9	Name and designation of officers					
	from the building side	Mr.Gurdeep Singh, Manager.				
10	Year of construction	1992		<u> </u>		
4.4	Applicant's letter No	0145/ 1-1-1	C D/I := /I IV	D+ 1E 10 201E		
11	Applicant's letter No.	2115/ Joint. C.P/Lic(H) NBC/ BBL 1983				
S. NO.	Minimum Standards on fire			Provided at site	Remarks	
	prevention and fire safety U/R	Requi	irement		MR / NMR	
	33					
1	Access to building			140 5	IME.	
	1) Road width	Accessible	!	12m Provided	MR	
	2) Gate width	N/A		N/A	N/A	
	3) Width of internal road	N/A		N/A	N/A	
2	Number, width Type & arrangeme	ent of exits		T		
	a. Number of staircases					
	1. Upper floors	01no.		01no. Provided	MR	
	2. basements	N/A		N/A	N/A	
	b. Width of staircase					
	1. Upper floors	1.25 Mtr		1.05m	MR(old case)	
	2. basements	N/A		N/A	N/A	
	c. Protection of exits		* *	1		
	1. Fire check door	N/A		N/A	N/A	
	2. Pressurization	N/A		N/A	N/A	
	d. No. of continuous staircase			1 No. Provided	MR	
	to terrace					
	e. Width of corridor	N/A		N/A	N/A	
	f. Door size	1 Mtr		1Mtr.	MR	
3	Compartmentation.					
	1. Fire check door	N/A		N/A	N/A	
	2. Sealing of electrical shafts	Required		Provided	MR	
	3. Fire Rating of shaft door	N/A		N/A	N/A	
	4. water curtain	N/A		N/A	N/A	
	5. Fire dampers	N/A		N/A	N/A	
4	Smoke Management system.				Maria de la companya del companya de la companya de la companya del companya de la companya de l	
	Basement	30 a/c per hour		N/A	N/A	
	Upper floors	12 a/c per hour		Natural Ventilation	MR	
5	Fire Extinguishers					
	Total numbers			12 Nos	MR	
	Types			ABC, Co2,	MR	
	ISI marking	ISI		Yes	MR	
6	First-Aid Hose Reels.					
	Total numbers on each floor	One	,	01no. Provided	MR	
				100 to 1000,000 to 100		
	Length of Hose reel hose	30 m		Provided	MR	
	Nozzle Diameter	5 mm		Provided	MR	

,	Date of mopeotion	00.11.2010					
8	Name of the inspecting Officers :	: ADO(S.J.) Vedpal					
9	Name and designation of officers						
	from the building side	Mr.Gurdeep Singh, Ma	nager.				
10	Year of construction	1992					
11	Applicant's letter No.	2115/ Joint. C.P/Lic(H), Dt 15.10.2015.					
S. NO.	Minimum Standards on fire	NBC/ BBL 1983	Provided at site	Remarks			
	prevention and fire safety U/R 33	Requirement		MR / NMR			
1	Access to building						
	1) Road width	Accessible	12m Provided	MR			
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A	N/A			
2	Number, width Type & arrangeme	ent of exits					
	a. Number of staircases						
	1. Upper floors	01no.	01no. Provided	MR			
	2. basements	N/A	N/A	N/A			
	b. Width of staircase						
	1. Upper floors	1.25 Mtr	1.05m	MR(old case)			
	2. basements	N/A	N/A	N/A			
	c. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	d. No. of continuous staircase	Requied	1 No. Provided	MR			
	to terrace						
	e. Width of corridor	N/A	N/A	N/A			
	f. Door size	1 Mtr	1Mtr.	MR			
3	Compartmentation.						
	1. Fire check door	N/A	N/A	N/A			
	2. Sealing of electrical shafts	Required	Provided	MR			
	3. Fire Rating of shaft door	N/A	N/A	N/A			
	4. water curtain	N/A	N/A	N/A			
	5. Fire dampers	N/A	N/A	N/A			
4	Smoke Management system.						
	Basement	30 a/c per hour	N/A	N/A			
	Upper floors	12 a/c per hour	Natural Ventilation	MR			
5	Fire Extinguishers			1			
	Total numbers		12 Nos	MR			
	Types		ABC, Co2,	MR			
	ISI marking	ISI	Yes	MR			
6	First-Aid Hose Reels.		10.	LAD			
	Total numbers on each floor	One	01no. Provided	MR			
	Length of Hose reel hose	30 m	Provided	MR			
	Nozzle Diameter	5 mm	Provided	MR			
7	Automatic fire detection and alar	rming system	_	Yourselesses			
	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	hooter's location	N/A	N/A	N/A			
	hd S						

N131

8	MOEFA	Required	Provided	MR
9	Public Address System.		3 100 0 0 1000	
10	Automatic Sprinkler System.	N/A	N/A	N/A
10	Basement System.	NI/A	D1/0	
		N/A	N/A	N/A
	Upper floors	N/A	N/A	N/A
44	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-corner	N/A	N/A	N/A
	Number of Hydrants per floor	N/A	N/A	N/A
	hose Box	N/A	N/A	N/A
12	Yard Hydrants.		•	
	total number of hydrants	N/A	N/A	N/A
	hose box	N/A	N/A	N/A
13	Pumping arrangements			1107.1
	1. Ground level			
	a. Discharge of main Pump	N/A	N/A	N/A
	b.Head of main pump	N/A	N/A	N/A
	c.Number of main pumps	N/A	N/A	N/A
	d.jockey pump out put	N/A	N/A	N/A
	e.jockey pump head	N/N	N/A	N/A
	f. Standby Pump output	N/A	N/A	N/A
	g.Stanby Pump head	N/A	N/A	N/A
	h.Auto Starting/Manual stopping	N/A	N/A	N/A
	pump house access	N/A	N/A	
	2.Terrace level	14//	INA	N/A
	a. Discharge of pump	450LPM	450LPM	IMP
	b. head of the pump	40m	40m	MR
	c. Power supply	Required		MR
	d. Auto starting of pump	Required	Provided	MR
14	Captive water storage for fire	Required	Provided	MR
	fighting			
	Underground tank capacity	N/A	N/A	N/A
	a. Draw-off connection	N/A	N/A	N/A
	b. fire service inlet	N/A	N/A	N/A
	c.Access to tank	N/A	N/A	N/A
	Over head tank Capacity	5,000 Itr	5,000 ltrs. Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of lifts.			
	a. Pressurization of lift shaft	N/A	N/A	N/A
	b. pressurization of lift lobby	N/A	N/A	N/A
	c. communication in lift car	Required	Provided	MR
	d. Fireman's grounding switch	Required	Provided	MR
	e. Lift signage	Required	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area.		Not Required	
	total area		. Tot Royallou	
	location			
19	Fire control room	:		
	a. Detector system Panel	N/A	N/A	N/A
			I N/ / \	
		N/A	NI/Δ	NI/A
	b. Flow switch Panel	N/A	N/A	N/A
		N/A N/A Required	N/A N/A Provided	N/A N/A MR



20 Special Fire Protection systems for protection of special risks, if any:

The fire protection systems provided in the building were test checked randomly and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter No.F.6/DFS/MS/GH/2012/3319, dated 11.09.12 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Accordingly DFA is put up for your approval and signature please.

6/11/15

Signature of the inspecting officer

Name

Vedpal

Designation : Assistant Divisional Officer (S.

D.O. (South)