FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

F6/DF3/M5/EN/2016/W2/1658 No.

Dated: 1/1/1/6

FIRE SAFETY CERTIFICATE

Certified that the M/s Barshala (A Unit of Indo Spirit Bars Pvt. Ltd.) located at 1st Floor 23-A First Floor Road No. 44, NN Towers, Community Centre, Pitampura, Delhi – 110034 in a FSC vide Letter No. building comprised of G + 1 Upper Floor issued was F6/DFS/MS/EH/2015/WZ/394 dated 20-03-2015 (for Gola Sizzlers Restaurant & Bar). The premises was re inspected by the officers concerned of this department on 31-10-2016 in the presence of Mr. Vijay Kumar and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" Group D with effect from ______________________ for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Chief Fire Officer Ph: 011-23414250

Copy to:

1. Vijay Kumar, M/s Barshala (A Unit of Indo Spirit Bars Pvt. Ltd.) 23-A First Floor Road No. 44, NN Towers, Community Centre, Pitampura, Delhi – 110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: M/s Barshala (A Unit of Indo Spirit Bars Pvt. Ltd.) located at 23-A First Floor Road No. 44, NN Towers, Community Centre, Pitampura, Delhi – 110034

2. Type of Occupancy

: Assembly (1st Floor)

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F6/DFS/MS/EH/2015/WZ/394

dated 20-03-2015 (For Gola Sizzlers Restaurant & Bar)

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 31-10-2016

7. Name of the Inspecting Officer: ADO (WP)

8. Name and designation of Officer

from the building side

: Sh. Vijay Kumar

9. Year of Construction

: 2005

10. Applicant's letter No.

: DHO/RZ/2016/1122 dated 31-08-2016

S No	Minimum standards on fire prevention and fire safety U/R 33	RRI	Provided at site	Remarks MR/NMR			
1.	Access of building						
	Road width	6 m					
	• Gate width		Provided	MR			
	• Width of internal road	NA	NA	NA			
2		NA	NA	NA			
2.	Arrangements of evits						
	a. Number of staircases						
	 Upper floors 	2	Provided	MR			
	 Basements 	NA	NA	NA NA			
	b. Width of staircases		1111	INA			
	 Upper floors 	2 m	2m & 87	MD (11			
	 Basements 	NA	NA NA	MR (old case)			
	c. Protection of exits		IVA	NA			
	 Fire check door 	NA)) T A				
	 Pressurization 	NA	NA	NA			
*	d. No of continuous	NA	NA	NA			
	staircase to terrace	IVA	NA	NA			
	e. Width Of Corridor	2 m					
	f. Door Size		2 m	MR			
. (Compartmentation	1x2m &1x1 m	1x2m &1x1 m	MR			
	• Fire check door	Dogwin 1'					
	THE CHECK GOOT	Required in	Provided	MR			
	• Sealing of alastric-1	Kitchen					
	 Sealing of electrical shafts 	NA	NA	NA			
		NA	NA	NA			
	Fire Rating of shaft doorWater Curtain	NA	NA	NA			
		NA	NA	NA			
S	• Fire Dampers			41/1			
3	moke managements System						
	• Basements	30 a/c per hour	NA	NA			
	• Upper floors	12 a/c per hour	Provided	MR			
			- To rided	IVIIV			

	Fire Extinguishers			1.00				
	Total numbers	06 nos.	Provided	MR				
	• Types	ABC & CO ₂	Provided	MR				
	• IS marking	ISI marked	Provided	MR				
6.	First – Aid Hose Reels		D '1 1	MR				
	 Total numbers on each 	1	Provided Provided	MR				
	floor	30 m	Provided	IVIIX				
	 Length of hose reel hose 	6.5 mm	Provided	MR				
	Nozzle diameter	~	TTOVICE					
7.	Automatic fire detection and alarm	NR	NR	NR				
	Type of detectorsLocation of Main Panel	NR	NR	NR				
	CDtou	NR	NR	NR				
	Location of Repeater Panel							
	• Alternate source of	NR	NR	NR				
	power			NID				
	Hooters' Location	NR	NR	NR				
8.	MOEFA	Required	Provided	MR				
9.	Public Address System	NR	Provided	NR				
	1 2 A							
10.	Automatic Sprinkler System		NA	NA				
	 Basements 	NA	Provided	MR				
	• Upper Floor	Required NR	NR	NR				
	• Sprinkler above false	INIX	TVIC	1112				
	ceiling							
11.	Internal Hydrants: • Size of riser/down-	100 mm	Provided	MR				
	Size of riser/down- comer	100 11111	×					
	 Number of hydrants per 	1	Provided	MR				
	floor							
	 Hose Box 	Required	Provided	MR				
12.	Yard Hydrants			NTA				
	 Total number of 	NA	NA	NA				
	hydrants	NT A	NA	NA				
	Hose Box	NA	INT	1111				
13.								
	Ground Level	NA	NA	NA				
	Discharge of main pumpHead of main pump	NA NA	NA	NA				
	Head of main pumpNumber of main pumps	NA	NA	NA				
	Jockey pump out put	NA	NA	NA				
	> Jockey pump head	NA	NA	NA				
	Standby Pump out put	NA	NA	NA				
	Standby Pump Head	NA	NA	NA				
	Auto Staring/Manual	NA	NA	NA				
	stopping		NIA	NA				
	Pump House AccessTerrace level	NA	NA	INA				
	Terrace levelDischarge of pump	450 lpm, 180 lp	om Provided	MR				
	Head of the pump	36 m	Provided	MR				
	> Power supply	Required	Provided	MR				
	> Auto starting of pump	Required	Provided	MR				
1/	14. Captive water Storage for fire fighting:							
12	Under ground tank	NA	NA	NA				
	capacity							
	> Draw off connection	NA	NA	NA				
	> Fire service inlet	NA	NA	NA				
	> Access to tank	NA 5000 litros	Provided	MR MR				
	O T T	SIMIL LITUOC	F 1'(1)/1(1 -4(1)	LIVIIX				

15	Exit Signage	Required	Provided	MR			
16.	Provision of Lifts						
511	Pressurization of Lift	NA	NA	NA			
	Shaft	NA	NA	NA			
	Pressurization of lift	NA	NA	NA			
	lobby	NA	NA	NA			
	Communication in lift						
	Car	NA	NA	NA			
	Fireman's Grounding						
	Switch						
17.	Lift Signage						
	Standby power supply	Required	Provided	MR			
18.	Refuge Area						
1. 1.	Total area	NA	NA	NA			
	Location	NA	NA	NA			
19.		Fire control room					
	Detector system panel	NA	NA	NA			
	Flow Switch Panel	NA	NA	NA			
	PA System Panel	NA	NA	NA			
1	Battery backup	-NA	NA	NA			
	Building Floor Plans	NA	NA	NA			
20.	Special Fire Protection Systems	NA	NA	NA			
	for Protection of special Risks,						
	if any;						
	The fire protection systems provided in the building years took should be						

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/EH/2015/WZ/394 dated 20-03-2015 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name Udai Vir Singh

Designation ADO WP

Tytho W2)
Po Healthill