## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. f6/Dfs/ms/2016/ND2/1170

Dated: 15/11/16

## FIRE SAFETY CERTIFICATE

Certified that the Plot no. 82, FIE Patpargang, Industrial area Delhi-92,owned/occupied by Toyo Ink India Pvt. Ltd. Comprised of basement, ground plus one upper floors of the building was granted NOC by this department vide letter no. F6/MS/DFS/96/1132 Dated-17/09/96. The premises was re-inspected by the concerned of this department on dated 27/09/16 & 24/10/16 in the presence of Smt. Sharda Jha (Manager) and found the premise is comprised of basement, ground plus two upper floors have deemed complied with the fire prevention and fire safety requirements in accordance with BBL & NBC Part-IV and found that the premises is fit for occupancy Group "G (Industrial Building)", with effect from occupancy Group "G (Industrial Building)", with effect from occupancy Group "G (Industrial Building)" and subject to compliance of the conditions under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on \_\_\_\_\_at New Delhi by

( Vipin Kental)
Chief Fire Officer
Delhi Fire Service

To,

The Excutive Engineer (Bldg.)HQ,
East Delhi Municipal Corporation,
Udyog Sadan, Patpargang, Industrial Area Delhi-92.
Copy to-

Smt..Sharda Jha (Manager), Plot no. 82,FIE Patpargang,Industrial area Delhi-92

## CONDITIONS:

- 1. All the means of escape shall be kept free of all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 5. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. All comments/ directions of the Licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate,six months prior to its expiry"
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building : Plot no. 82,FIE Patpargang,Industrial area Delhi-92. 2. Building is comprised of : Basement, Ground+2 Upper floors 3. Type of Occupancy : Industrial 4. Type of Case : Renewal/Additional & Alteration 5. Details of Previous NOC : F6/DFS/MS/96/1132 Dated 17/09/96 (for basement,G+1) 6. Fire Safety direction letter No : F6/DFS/MS/96/1056 Dated-30/08/96 7. Date of Inspection : 27/09/16 & 24/10/16 8. Name of the Inspecting Officers: : R.K.Yadav (ADO) 9. Name of the designation of Officer from the building side : Smt.Sharda Jha (Manager) 10. Year of Construction : 1996 11. Applicant's letter No : dated 01/09/16 Minimum Standards fire BBL/NBC on Provided Remarks at N prevention and fire safety U/R33 Part-IV Site MR/NMR 1 Access to building Road width 12 m 12 m MR Gate width 4.5 m 4.5 m MR Width of internal road N.A. N.A. N.A. Number, Width, Type and Arrangement of Exits a. Number of Staircases Upper Floor 2 nos. 2 nos. MR Basement 1 no. 1 no. MR (Old accepted) b. Width of Staircases **Upper Floor** 1.5 & 1.25 m 1.5 & 1.25 m MR Basement 1.25 m 1.25 m MR (Old accepted) c. Protection of exits Fire check door Required provided MR Pressurization Required provided MR e. No. of continuous staircases to 1 no. 1 no. MR terrace g. Width of Corridor 1.5 m 1.5 m MR h. Door Size 1.0 m 1.0 m MR Compartmentation. Fire check door Required provided MR Sealing of electrical shafts Required Sealed MR Fire rating of shaft door 02 hrs. 02 hrs. MR Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A. Smoke Management System. Basement Required provided MR Upper floor N.A. N.A. N.A. 5 Fire Extinguisher Total numbers 40 nos. 40 nos. MR types CO<sub>2</sub> & ABC provided MR IS marking ISI marked provided MR

Earlier Noe issued vide letter No. F6/DF3/m5/96/1132 dt. 17/09/96.

mis

6	First-aid-Hose Reels.					
	Total numbers of each floor	1 no.	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming sy		riovided	IVIK		
	Type of detectors	N.A.	Heat & Smoke	MR		
	Location of main panel	Security Room	Provided	MR		
	Location of repeater panel	Security Room				
	Alternate source of power	Battery & DG	Provided	MR		
		Set Set	Provided	MR		
	Hooters's location	Staircase	Provided	MR		
8	MOEFA	Required	provided	MR		
9	Public address System.	Required	provided	MR		
10	Automatic Sprinkler System.	-				
	basement	Required	provided	MR		
	upper floor Rs	REQUIRED PK	provided	MR		
	sprinkler above false ceiling	N.A.	provided	MR		
11	Internal Hydrants		provided	IVIN		
	size of riser/down-comer	N.A.	Provided	MD		
	Total no. of hydrants each floor	N.A.	Provided	MR		
	Hose Box per floor	N.A.	Provided	MR		
12	Yard Hydrants.	IV.A.	Provided	MR		
	Total number of hydrants	N.A.	10 No.	2.45		
	Hose Box	N.A.	10 Nos.	MR		
13	Pumping Arrangements.	IV.A.	10 Nos.	MR		
	Ground Level					
	<ul><li>Discharge of main Pump</li></ul>	N.A.	AL A			
	Head of Main Pump	N.A.	N.A.	N.A.		
	<ul> <li>Number of main pumps</li> </ul>		N.A.	N.A.		
	> Jockey pump out put	N.A.	N.A.	N.A.		
	> Jockey pump head	N.A.	N.A.	N.A.		
	> Standby pump out put	N.A.	N.A.	N.A.		
	Standby pump Head	N.A.	N.A.	N.A.		
	> Auto Starting /Manual stopping	N.A.	N.A.	N.A.		
	Pump House Access	N.A.	N.A.	N.A.		
	Terrace Level					
	Discharge of pump	900 LPM	Provided	MR		
	Head of the Pump	40 m	Provided	MR		
	Power supply	Required	Provided	MR		
	> Auto Starting of pump	N.A.	N.A.	N.A.		
14	Captive Water Storage for Fire Fighting.					
	I Indonesia de la					
	Underground tank capacity  Draw-off connection	N.A.	N.A.	N.A.		
	Fire service inlet	Required	Provided	MR		
- :	C III C (COMMONISTIC VIRICIDIALISM)	Required	provided	MR		
	Access to tank	Required	provided	MR		
	Overhead Tank capacity	10,000 Liters	Provided	MR		
15	Exit Signage.	Required	Provided	MR		

16	Provision of Lifts.					
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication in lift car Firemen's grounding switch Lift Signage	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
17	Standby power supply	N.A.	N.A.	N.A.		
18	Refuge Area.					
	Total area Location	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A.	provided	MR		
	Flow switch panel PA system panel Batter backup Building Floor Plans	N.A.	provided	MR		
		N.A.	provided	MR		
		N.A.	provided	MR		
		N.A.	N.A.	N.A.		
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.		

The fire extinguhers provided in the building were tested/checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the BBL & NBC Part-IV. The NOC issued vide letter no. F6/MS/DFS/96/1132 Dated-17/09/96 is recommended to Fire Safety Certificate.

Signature of the Inspecting Officer

Name- R.K. Yadav

Designation- ADO (LN)

DO(ED)

DEFO(NDZ)

28/X