GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2016/ 188

Dated: 24/11/16

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to: -

1. The Joint C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, M/s Hotel L'affaire, 17A/12, WEA, Karol Bagh, New Delhi- 110005

Conditions for the Validity of Fire Safety Certificate

a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.

b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety

certificate stands null and void.

c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

d. The basement shall be used strictly as per the provisions of the Building Bye

Laws, 1983.

e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

1. Name & address of the building : M/s Hotel L'affaire, 17A/12, WEA, Karol Bagh, New

Delhi- 110005.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2013/922 dated 17.09.2013

5. Fire Safety directives letter No : Nil

6. Date of inspection : 05-10-2016

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO (South West)8. Name and designation of officers

from the building side : Mr. Rajatdeep Kathuria, Proprietor 9. Year of Construction : Before 1994

10. Applicant's letter No. : nil dated nil

The said guest house is comprised of basement (Storage), ground floor (reception + hall), first floor (09 guest rooms), second floor (10 guest rooms), third floor (10 guest rooms) & a pantry for staff at terrace floor.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire Safety arrangements as per previous FSC	Provided at site	Remarks MR/NMR			
1	Access to building						
	Road width	06 mts	Provided	MR			
	Gate width		Directly accessible	MR			
	Width of internal road	N/A	N/A	N/A			
2	Number, Width, Type & Arrangement	t of Exits		1			
	a. Number of staircases	- ,	-	_			
	Upper Floors	01	01	MR being old case			
	Basements	01	01	MR being old case			
	b. Width of staircases	-	-	-			
	Upper Floors	N/A	Provided(1.20 Mts)	MR being old case			
	Basements	N/A	Provided(1.22 Mts)	MR being old case			
	c. Protection of exits	-	-	-			
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	e. No. of continuous staircases to terrace	01	01	MR			
	g. Width of Corridor	N/A	N/A	N/A			
	h. Door Size	N/A	Provided (0.78 Mt)	MR being old case			
3	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
b	Fire Rating of shaft door	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			

4	Smoke Management System.		Exhaust fan					
	Basements	30 a/c per hour	provided	MR MR				
	Upper floors	12 a/c per hour	Natural Ventilation					
-	Time Entinguishors							
5	• Total numbers	12	Provided	MR				
	• Types	Co ₂ , ABC type	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6								
	• Total numbers on each floor	01	Provided	MR				
	 Length of hose reel hose 	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
7	Automatic fire detection and alarmin	g system.						
/	C 1-tstore	N/A	N/A	N/A				
	-9	N/A	N/A	N/A				
	Location of Main Panel	N/A	N/A	N/A .				
	 Location of Repeater Panel 	Required	Provided	MR				
	 Alternate source of power 			27/4				
-,	Hooters' Location	N/A	N/A	N/A				
8	MOEFA	Required	Provided	MR				
9	Public Address System.	Required	Provided	MR				
10	Automatic Sprinkler System.							
	Basement	Required	Provided	MR				
	Upper Floor	N/A	N/A	N/A				
	 Sprinkler above false ceiling 	N/A	N/A	N/A				
		14/71						
11	Internal Hydrants	N/A	N/A	N/A				
	Size of riser/down-comer	N/A	N/A	N/A				
	 Number of hydrants per floor 	. *		8				
	Hose Box	N/A	N/A	N/A				
12	Yard Hydrants.							
12	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.	9						
13	Ground Level							
	Discharge of main Pump	N/A	N/A	N/A				
	> Head of Main pump	N/A	N/A	N/A				
	> Number of main pumps	N/A	N/A	N/A				
	> Jockey Pump out put		N/A	N/A				
	> Jockey pump head	N/A	N/A	N/A				
	> Standby Pump out put	N/A	N/A	N/A				
		N/A	11/11					

S. C.	Standby Pump Head	N/A	N/A	N/A				
	Auto Starting/ Manual	N/A	N/A	N/A				
	stopping	N/A	N/A	N/A				
	Pump House Access							
	Terrace level	450 LPM	450 LPM	MR				
	Discharge of pump	30 mts	Provided	MR				
	➤ Head of the pump	Required	Provided	MR				
	Power SupplyAuto Starting of pump	Required	Provided	MR				
14	Captive Water Storage for fire fighting.							
	Underground tank capacity	N/A	N/A	N/A				
	Draw-off connection	N/A	N/A	N/A				
	> Fire service inlet	N/A	N/A	N/A				
	Access to tank	N/A	N/A	N/A				
	Overhead Tank capacity	5,000 lts	Provided	MR being old case				
15	Exit Signage.	Required	Provided	MR				
16	Provision of Lifts.							
×	Pressurization of Lift Shaft	N/A	N/A	N/A				
	Pressurization of Lift lobby	N/A	N/A	N/A				
	Communication In lift Car	Required	Provided	MR				
	Fireman's Grounding Switch	Required	Provided	MR				
	Lift Signage	Required	Provided	MR				
17	Standby power supply	Required	Provided	MR				
18	Refuge Area.							
1, 1	> Total Area	N/A	N/A	N/A				
	> Location	N/A	N/A	N/A				
19	Fire Control Room							
	Detector System Panel	N/A	N/A	N/A				
* N	Flow Switch Panel	N/A	N/A	N/A				
	PA System Panel	N/A	N/A	N/A				
	Batter backup	N/A	N/A	N/A				
	Building Floor Plans	N/A	N/A	N/A				
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC type fire extinguisher found provided near elect. panel	MR				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2013/922 dated 17.09.2013, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

DCFO(SZ)

Left

Tho

CFO(SZ)

Plopeally

Volv

Signature of the inspecting Officer
Name M.K.CHATTOPADHYAY
Div. Officer (South West)

