GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. F6/OFS/as/2016/52/1203

Dated: 25/11/16

FIRE SAFETY CERTIFICATE

Issued on 25.7.1.1.......2016 at New Delhi by.

(Vipin Kental)
Chief Fire Officer
T.No.011-23412225

Copy to:- Sh. B.D.Sukal, Dy. General Manager (Engg.), NBCC Ltd. Block No.01, General Pool Residential Accommodation (GPRA), New Moti Bagh, New Delhi-110023.

Conditions for the validity of fire safety certificate are under:-

61C

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate on form J, six month prior to its expiry.

		INSPECTION	N REPORT		
1	Name & address of the building		eneral Pool Residential Accommo	odation (GPRA), New Mo	
2	Type of Occupancy	Residential Building	"A"		
3	Type of case	Renewal			
	Details of previous NOC		1/3342, Dated 02.12.2011.	×	
4	Fire safety directives letter No		BP/2007/1304, Dated- 08.05.200	77	
5			BP/2007/1304, Dated- 08.05.200)/.	
6	Date of inspection	10.11.2016.			
7	Name of the inspecting Officers :	Vedpal ADO.			
8	Name and designation of officers from the building side	Sh. B.D.Sukla DGM (Electrical) NBCC.			
9	Building Comprised of	Stillt+08Upper floors. (Stillt=Parking & Upper Floors=04 Residential flats at each floor).			
10	Year of construction	2007-2010			
11	Applicant's letter No.	NBCC/GM/NMBC/2	016/166, Dated 17.10.2016.		
S. NO.	Minimum Standards on fire prevention and fire safety U/R 33	Requirements as per BBL	Provided at site	Remarks MR / NMR	
1	Access to building		<u> </u>		
	1) Road width	9m	25m	MR	
	2) Gate width	5m	6m	MR	
	3) Width of internal road	6m	6m	MR	
2	Number, width Type & arrangement of	exits		Truck Control of the	
	a. Number of staircases				
	1. Upper floors	06nos.	06nos.	MR	
	2. basements	N/A	N/A	N/A	
	b. Width of staircase				
	1. Upper floors	1.25m/90cm	1no=1.5m, 1no=1.25m & 4nos=90cm(each)	MR	
	2. Basements	N/A	N/A	N/A	
	c. Protection of exits				
	1. Fire check door	Required	Provided	MR	
	2. Pressurization	N/A	N/A	N/A	
	d. No. of continuous staircase to terrace	06nos.	06nos.	MR	
	e. Width of corridor	N/A	N/A	N/A	
	f. Door size	1 Mtr	1Mtr	MR	
3	Compartmentation.				
	1. Fire check door	Required	Provided	MR	
	2. Sealing of electrical shafts	Required	Provided	MR	
	3. Fire Rating of shaft door	N/A	N/A	N/A	
	4. water curtain	N/A	N/A	N/A	
4	5. Fire dampers	N/A	N/A	N/A	
4	Smoke Management system.	30 a/c per hour	INI/A	laura.	
	Upper Floors	12 a/c per hour	N/A Natural Ventilation	N/A MR	
5	Fire Extinguishers	,	ivaturai ventilation	IVIE	
		44nos.	48nos.	MR	
	Types	and the state of t	ABC & Water CO2	MR	
	ISI marking		ISI Mark	MR	
6	First-Aid Hose Reels.		IIOI IVIAIN	INIL	
0		02nos.	02nos.	MR	
	TOTAL TIGHTIDOTO OTT CUOTT HOOF	UZ1103.	021103.	IVIE	
	Length of Hose reel hose	30m	30m	MR	



A	ıv	- /	L
,		r	σ

7	Automatic fire detection and alarming	system		
	Type of detectors	N/A	N/A	N/A
	location of Main Panel	N/A	N/A	N/A
	location of Repeater panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	hooter's location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	basement	N/A	N/A	N/A
	upper floors	N/A	N/A	N/A
	sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants	1	1477	114/74
	Size of riser/down-corner	150mm	150mm	MR
	Number of Hydrants per floor	02nos.	02nos.	MR
	hose Box	02nos.	02nos.	MR
12	Yard Hydrants.	021105.	021105.	IVIR
	total number of hydrants	N/A	N/A	N/A
	hose box	N/A	N/A	
13	Pumping arrangements	INA	IIV/M	N/A
13	1. Ground level	N/A	N/A	NI/A
	a. Discharge of main Pump	N/A		N/A
			N/A	N/A
	b.Head of main pump	N/A	N/A	N/A
	c.Number of main pumps	N/A	N/A	N/A
	d.jockey pump out put	N/A	N/A	N/A
	e.jockey pump head	N/A	N/A	N/A
	f. Standby Pump output	N/A	N/A	N/A
	g.Stanby Pump head	N/A	N/A	N/A
	h.Auto Starting/Manual stopping	N/A	N/A	N/A
	pump house access	N/A	N/A	N/A
	2.Terrace level	0001 511		*
	a. Discharge of pump	900LPM	90O+220LPM	MR
	b. head of the pump	40m	40m(each)	MR
	c. Power supply	Required	Provided	MR
	d. Auto starting of pump	Required	Provided	MR
4.4	Contino victor atomorphism		1 8 H	
14	Captive water storage for fire fighting 1. Underground tank capacity	250000Liters	250000Liters common for entire	IMP
	1. Onderground tank capacity	Zooooliters	complex	MR ·
	a. Draw-off connection	Required	Provided	MR
	b. fire service inlet	Required	Provided	MR
	c.Access to tank	Required	Provided	MR
	Over head tank Capacity	25000Litrs	25000Liters	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of lifts.		*	
	a. Pressurization of lift shaft	N/A	N/A	N/A
	b. pressurization of lift lobby	N/A	N/A	N/A
	c. communication in lift car	Required	Provided	MR
	d. Fireman's grounding switch	Required	Provided	MR
	e. Lift signage	Required	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area.	Trequired	Not Required	Livitz
10	total area	N/A		INIA
			N/A	N/A
10	location	N/A	N/A	N/A
19	Fire control room	N/A	laura -	1
	a. detector system Panel	N/A	N/A	N/A
	b. Flow switch Panel	N/A	N/A	N/A
	c. PA system Panel	Required	Provided	MR

	N/7				
20 Special I	Fire Protection systems for protection of special risks, if any: N/A				
The fire protectiview the deemed	ion systems provided in the building were test checked at random and found functional at the time of inspection compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued S/MS/2011/3342, dated 02.12.2011 renewal under rule 37 of the Delhi Fire Service Rule 2010 is recommended				
Accordingly DF	A is put up for your approval and signature please. Signature of the inspecting officer				
	Name: Vedpal				
	Designation : ADO				
DO.C.	8-D) July 15 16 16 16 16 16 16 16				
LIPE SERVICE	Ly crocses Learl 15/11				

23/11/16 25.11.16

CFO(S2) M-SCELL F7 M.

FT letter is put up far sign please

W

20-6-6-6

miscell