GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/BNQT/2016/NDZ/ 1 206

Dated: 25/11/16

FIRE SAFETY CERTIFICATE

(Vipin Kental)
Chief Fire Officer

To,

Manager, Shubh Milan Banquet Hall, 534,534/4,534/5 Jheel Khuranja,Delhi -51.

Copy to:-

 The Deputy Health Officer (EDMC), SHD (N)-Zone, Health Department, Delhi-110032

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, six months prior to its expiry.

1. Name & address of the building : Shubh Milan Banquet Hall,534,534/4,534/5 Jheel Khuranja, Delhi -51. :G+2 (Banquet hall running at I^{ST} & II^{ND} floor only) 2. Building is comprised of : Assembly (Banquet Hall) 3. Type of Occupancy 4. Type of Case : New Case 5. Details of Previous NOC : Nil 6. Fire Safety direction letter No : BBL 7. Date of Inspection : 10/11/16 8. Name of the Inspecting Officers: : ADO R.K.Yadav 9. Name of the designation of Officer from the building side : Mr.Tilakraj (Manager) 10. Year of Construction : 1985 11. Applicant's letter No : dated 19/10/16 Standards fire **BBL 1983** Provided at Remarks S. Minimum on N prevention and fire safety U/R33 Site MR/NMR 0 1 Access to building Road width 06 m 06 m MR Gate width MR 4.5 m 4.5 m Width of internal road N.A. N.A. N.A. 2 Number, Width, Type and Arrangement of Exits a. Number of Staircases Upper Floor MR 2 no. 2 no. Basement N.A. N.A. N.A. b. Width of Staircases Upper Floor 1.5 m 1.8 m & 1.5 m MR Basement N.A. N.A. N.A. c. Protection of exits Fire check door Required provided MR Pressurization Required provided MR e. No. of continuous staircases to MR 1 no. 2 no. terrace g. Width of Corridor N.A. N.A. N.A. h. No. of door N.A. N.A. N.A. i. Door Size 2 m 2 m MR 3 Compartmentation. Fire check door Required provided MR Sealing of electrical shafts Required MR provided Fire rating of shaft door N.A. N.A. N.A. Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A. 4 Smoke Management System. Basement N.A. N.A. N.A. Upper floor Ventilated Provided MR 5 Fire Extinguisher Total numbers Provided 10 no. MR Types CO₂ & ABC Provided MR IS marking ISI marked Provided MR

MIY HADI LUTION BILL ON

6	First-aid-Hose Reels.	Λ					
	Total numbers of each floor	1 no.	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
	Nozzle diameter	5 mm Provided		MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N.A.	N.A.	N.A.			
	Location of main panel	N.A.	N.A.	N.A.			
	Location of repeater panel	N.A.	N.A.	N.A.			
	Alternate source of power	N.A.	N.A.	N.A.			
	Hooters's location	Required	Provided	MR			
8	MOEFA	Required	Provided	MR			
9	Public address System.	N.A.	N.A.	N.A.			
10	Automatic Sprinkler System.						
	basement	N.A.	N.A.	N.A.			
	upper floor	N.A.	N.A.	N.A.			
	sprinkler above false ceiling	N.A.	N.A.	N.A.			
11	Internal Hydrants						
201	size of riser/down-comer	100 mm	Provided	MR			
	Total no. of hydrants each floor	1 no.	Provided	MR			
	Hose Box per floor	1 no.	Provided	MR			
12	Yard Hydrants.						
	Total number of hydrants	N.A.	N.A.	N.A.			
	Hose Box	- N.A.	N.A.	N.A.			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N.A.	N.A.	N.A.			
	➤ Head of Main Pump	N.A.	N.A.	N.A.			
	Number of main pumps	N.A.	N.A.	N.A.			
	Jockey pump out put	N.A.	N.A.	N.A.			
	Jockey pump head	N.A.	N.A.	N.A.			
	Standby pump out put	N.A.	N.A.	N.A.			
	Standby pump Head	N.A.	N.A.	N.A.			
	 Auto Starting /Manual stopping 	N.A.	N.A.	N.A.			
	Pump House Access	N.A.	N.A.	N.A.			
	Terrace Level	450 Lpm	900Lpm	MR			
	Discharge of pump	40 m	Provided	MR			
	Head of the Pump	Required	Provided	MR			
	Power supplyAuto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.						
	Underground tank capacity	N.A.	N.A.	N.A.			
	Draw-off connection	N.A.	N.A.	N.A.			
	Fire service inlet	N.A.	N.A.	N.A.			
	Access to tank	N.A.	N.A.	N.A.			
	Overhead Tank capacity	10,000 Liters	Provided	MR			

15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
	Pressurization of Lift lobby Communication in lift car	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
	Firemen's grounding switch	N.A.	N.A.	N.A.		
	Lift Signage	N.A.	N.A.	N.A.		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A.	N.A.	N.A.		
	Flow switch panel	N.A.	N.A.	N.A.		
	PA system panel	N.A.	N.A.	N.A.		
	Batter backup	N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.	N.A		
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.		

The fire extinguishers provided in the building were tested/ checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the BBL it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name- R.K. Yadav

Designation- ADO (LN)

DO(ED) 16(1)

DeFO(NB2)