FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/2016/ W2/1210.

Dated: 15/11/2016

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by.

Chief Fire Officer
Delhi Fire Service

Copy to:

Sh Sanjeev Verma, B-2 Lawrence Road Ind. Area, Delhi

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

Name & address of the building: Party Place Banquet located at B-2
 Lawrence Road Inld Area, Delhi

 Type of Occupancy : Banquet, (Assembly) Ground Floor + Two UFs
 Type of Case : Renewal
 Details of previous NOC ; F6/DFS/MS/2011/1091 Dated 03/06/2011

6. Fire Safety directives Letter No. :F-6/DFS/MS/BP/2011/649 Dated 11/04/2011

7. Date of inspection . 11-11-2016

8. Name of the Inspecting Officer: Udai vir Singh ADO (WP)

9. Name and designation of Officer

from the building side

: Sh. Sunil Puri (Banquet Staff))

10. Year of Construction : 2004

11. Applicant's letter No. : Nil dated 18/10/2016

S N o	Minimum standards on fire prevention and fire safety U/R 33	NA NA Required Pro NA NA 2 2 Pro NA NA 2x2m GF 100 FF		Provided at site		marks R/NM	
1.	 Road width Gate width Width of internal road 			Provided Provided ,560 cm NA		MR MR NA	
2.	a. Number of staircases Upper floors Basements Width of staircases Upper floors Basements C. Protection of exits Fire check door Pressurization Mo of continuous staircase to terrace Width Of Corridor Door Size			4 Provided NA m,1x170cm,1x140cm,1x160cm MR(Bellow) NA Provided NA 2 Provided		MR NA eing Old case MR NA	
3.	Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers	Require Require NA NA NA	d Pro	Provided Provided NA NA NA			

7.41	1-11-12-12-12-2	J. F. J.	7/8 2	10117	***	NOT WAR	1/2
4.	Smoke managements						
	System	NIA			NA		NA
	• Basements	NA 12 a	/a man hai	114	Provided		MR
	Upper floor	12 a	/c per hor	uı	Tiovided		1,11
5.	Fire Extinguishers	1 1 4	DC CO2	e- WCO2	Provided		MR
	 Total numbers 			& WCO2	Provided		MR
	• Types	ISI marked			Provided		MR
	IS marking				Tiovided		1111
6.	First – Aid Hose Reels	2			3 Provided		MR
	• Total numbers on	2			3 Flovided		1411
	each floor	30 r	n		Provided		MR
	 Length of hose reel hose 	301	11		110/1404		
	Nozzle diameter	5 m	m		Provided		MR
7	Automatic fire detection an	2770 200000	The same of the sa	tem	ν,		
7.			moke & H		rided	. 1	MR
	Type of detectorsLocation of Main		equired		rided	N	MR
	Panel		oquirou				
	• Location of	Required Provi		rided		MR	
	Repeater Panel		•				
	• Alternate source of	R	equired	Prov	vided	I	MR
	power	-	Endown?		less sales		(D)
	Hooters' Location	R	equired	Prov	vided		MR
8.	MOEFA	R	equired	Prov	vided		MR
9.	Public Address System	R	equired	Prov	vided]	MR
10	Automatic Sprinkler System	m				1.2	
	Basements]	NA	NA	N 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	NA NA	
	Upper Floor	NA		NA			
	Sprinkler above fal	se]	NA	NA		NA	4
	ceiling				4.		.0
11	Internal Hydrants					•	
	Size of riser/down-		150 mm	Pro	vided	M	R
	comer		r			2.6	7
	 Number of hydrant 	S	2	3 P1	covided	M	R
	per floor			D	• 1 1	M	D
	Hose Box		Required	Pro	vided	IVI	N.
12	Yard Hydrants			27.4		N	Λ
	 Total number of 	NA		NA		IN A	4
"	hydrants	NIA		NA		N.	Α
	Hose Box	NA		en su-cen		1112	
13	Pumping Arrangements(A	All th	e pumps	rrovided	at terrace)		
	D' 1		2280 100	n	Provided	M	R
	Discharge of main		1		110 / 1000		
	pump Head of main pum	n			Provided		R
	> Number of main	Р			Provided	. M	
	pumps						
	Jockey pump out p	out			Provided		IR
	> Jockey pump head		60 m		Provided		IR
	> Standby Pump out				Provided		IR
	> Standby Pump He	ad 60 m			Provided		IR
	> Auto Staring/Man	ual Required		d	Provided	M	IR
	stopping						m .
	> Pump House Acce	SS	Require	d	Provided	l N	IR .
	Terrace level				7.7		m ·
	Discharge of pum		450 lpm	1	Provided		IR IR
	Head of the pump		40 m		Provided		IR III
	> Power supply		Required		Provided	M	IK

	~		ra fighting		
4	Ca	ptive water Storage for fi	NA NA	NA	NA
		Olider ground		You the second of	
		tank capacity Draw of	NA	NA	NA
		> Draw of connection			
			Required	Provided	MR
			Required	Provided	MR
		Overhead Tank	50000 Ltrs +10, 00	00 Provided	MR
	4		ltrs		
5	Ex	capacity	Required	Provided	MR
15 Exit Signage16 Provision of Lifts					
0	11		NA	NA	NA
		Lift Shaft			
			NA	NA	NA
		lift lobby) (D)
	1	> Communication	Required	Provided	MR
	-	in lift Car	<i>\$</i> *		N/D
	1	> Fireman's	Required	Provided	MR
		Grounding) (D
		Switch	Required	Provided	MR
		Lift Signage		D '1 1	MR
17	S	tandby power supply	Required	Provided	IVIIX
18	R	efuge Area		77.1	NA
		Total area	NA	NA	NA NA
	> Location N		NA	NA	INA
19	F	ire control room		D 11.1	MR
		Detector system pa	nel Required	Provided	NA NA
		Flow Switch Panel		NA	NA NA
	> PA System Panel		NA	NA	MR
		Battery backup	Required	Provided	NA NA
57 5		Building Floor Plan		NA	NA NA
20 Special F		pecial Fire Protection	NA ,	NA	INA
	S	ystems for Protection of			2
	S	pecial Risks, if any;		•	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and file safety as required under the rules the FSC issued vide letter no. F6/DFS/MS/2011/1091 Dated 03/06/2011 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Note; - Sprinkler system has been removed due to leaking of the system as it is not required as per NBC.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name ANO[WP/Vday Viv

1 Ow h Nam

Designation

Designation.

pole

muder ispifes

1911/16