GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6/DFS/MS/2016/WZ/1749 FIRE SAFETY CERTIFICATE Dated 5 //> / 2016

Certified that Delhi Police Housing Scheme located at Sec-11, Rohini Delhi, comprised of 02 Blocks with common Basement+Stilt+13 Floors owned/ occupied by Delhi Police have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 17.11.2016 in the presence of Mr. Bharat Aggarwal & Rakesh Kinha Engr and that the building/ premises is fit for occupancy "Residential A-4" with effect from -5/12/2016 for a period of Five years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the The form is available on schedule of Delhi Fire Service Rules 2010. WWW.dfs.Delhigovt.nic.in
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

Issued on at New Delhi by

Chief Fire Officer Ph: 011-23414250

Copy to:-

1. Sh. A K Johari, Sr. DGM, Rites Ltd, Scope Minar, Laxmi Nagar, Delhi-110024.

INSPECTION REPORT

1. Name & address of the building: Delhi Police Housing Scheme, Sec-11, Rohini Delh.

: Residential

3. Type of Case :New Case (02 Blocks with common Basement+S(iI(+13)) 4. Details of previous NOC : Nil

5. Fire Safety directives letter No : F6/DFS/MS/2010/BP/3142 dated 12.11.2010. 6. ate of inspection

: 17.11.2016

7. Name of the Inspecting Officers: Suresh Singh/ DO (NWD) & Rajesh Kumar /ADO (RN) 8. Name and designation of officers

from the building side : Mr. Bharat Aggarwal & Rakesh Kinha Engr

9. Year of Construction : 2015-16

10. Applicant's letter No. : RITES/CP/DP/Rohini /2016 dated 20.10.2016

S. No	prevention and fire safety U/R 3	fire NBC Requirement	Provided at site	Renark MR/\M
	Access to building			
	 Road width 	12m	24m	NR
	• Gate width	4.5m	5m	NR
	 Width of internal road 	6m	6m	NR
	Number, Width, Type & Arrange a. Number of staircases	ement of Exits		
	Upper Floors	02 in each block	02:	
	Basements	2 nos+ 02 Ramp	02 in each block =4 nos 02nos +2 ramp	VIR VIR
	b. Width of staircases	2		
	• Upper Floors	1.50m	4 x 1.50m	VIR
	Basements	1.50m	2x1.5m	VIR
	c. Protection of exits • Fire check door			
	Fire check doorPressurization	Required	Provided	VIR
	d. No. of continuous	Required	Provided	VIR
	staircases to terrace	02	02	VIR
And and a second of the second	e. Width of Corridor	NA	NA	\A
	f. Door Size	1.0m	1.0m	VIR
Co	mpartmentation.			

N/q

	Fire check door.	Required	Provided	VIR
	 Sealing of electrical shafts 	Required	Provided	MR
	• Fire Rating of shaft door	Required	Provided	MR
	Water Curtain	NA	NA	T A
	 Fire Dampers 	NA	NA	
4	Smoke Management System.		. , , ,	
-	• Basements	30ACPH	Exhaust Fans	
	Upper floors	12ACPH		VIR
5	Fire Extinguishers	IZACFI	Natural	VIR
	Total numbers	40		
		40nos	40nos	VIR
	• Types	ABC/CO2	ABC/CO2	MR
	IS marking	ISI Marks	IDI Marks	MR
6	First-Aid Hose Reels.			
	Total numbers on each	01 at each floor	01 at each floor	MR
	floor			
	 Length of hose reel hose 	30m	30m	VIR
	Nozzle diameter	5mm	5mm	VIR
7	Automatic fire detection and alarming system.			
	Type of detectors	NA	NA	T N
	 Location of Main Panel 	NA	NA NA	1 1
	Location of Repeater Panel	NA	NA NA	
	Alternate source of power	NA		A
	Hooters' Location		NA	\\
8		NA	NA	\A
	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	Basement	Required	Provided	MR
	 Upper Floor 	NA	NA	NA
	Sprinkler above false ceiling	NA	NA	\A
11	Internal Hydrants			1
	Size of riser/down-comer	100mm	100mm	MR
-	• Size of fiser/down-comer	TOOMIN	Toomm	MR

and the second second second	 Number of hydrants per floor 	01at each Floor	01 at each floor	NI J	
NATIONAL PROPERTY.	• Hose Box	01 at each Floor	01 at each floor	VI F	
2	Yard Hydrants.				
	Total number of hydrants	04	04	VII	
	Hose Box	04	04	vII	
3	Pumping Arrangements.		2		
	➤ Ground Level				
	Discharge of main Pump	1620 lpm	1620lpm	V11	
	> Head of Main pump	70m	70m	vii	
	Number of main pumps	01	01	VII	
	Jockey Pump out put	180 lpm	180 pm	VII	
	Jockey pump head	70m	70m	VII	
	Standby Pump out put	16201pm	1620lpm	VII	
	Standby Pump Head	70m	70m	VII	
	Auto Starting/ Manual	Required	Provided	.VII	
	stopping	Required	Provided	MI	
	Pump House Access				
	Terrace level	900 lpm	900 Lpm	[V] I-	
	Discharge of pump	40m	40m	VIII	
	► Head of the pump	Required	Provided	MF	
	Power Supply	Required	Provided	VII	
	➤ Auto Starting of pump		*	L	
	Captive Water Storage for fire fighting.				
	Underground tank capacity	75,000 ltrs	75,000 ltrs	MR	
	Draw-off connection	Required	Provided	VIR	
	Fire service inlet	Required	Provided	MR	
	> Access to tank	Required	Provided	VIR	
	 Overhead Tank capacity 	25,000 ltrs	25,000ltrs	VIR	
	Exit Signage.	Required	Provided	VIR	
	Provision of Lifts.	,			
	Pressurization of Lift Shaft	Required	Provided	VIR	
	Pressurization of Lift lobby	NA	NA	\A	

N/II			
Required	Provided		

	14 / 11			
	Communication In lift Car	Required	Provided	IVR
	Fireman's Grounding	Required	Provided	
	Switch • Lift Signage	NA	NA	N.A.
7	Standby power supply	Required	Provided	YR
8	Refuge Area.			
	> Total Area	NA	NA	14/
	> Location	NA	NA	\A
9	Fire Control Room (Not provided)			
- 17 - 17	Detector System Panel	NA	NA	NA
	Flow Switch Panel	NA	NA	NA
	PA System Panel	Required	Provided	MR
	Batter backup	Required	Provided	VIR
	Building Floor Plans	Required	Provided	VIR
0	Special Fire Protection Systems	NA	NA	NA
	for Protection of special Risks, if			
	any:			

The fire protection systems provided in the building were test checked and found The observations/ shortcomings issued and functional at the time of inspection. communicated vide this department letter of even no. 2281 dated 23.09.2016 have been complied by the managemennt.

Keeping in view of satisfactory compliance of the minimum standards on fire prevention and fire safety required under the rules and fire safety guidelines issued vide letter of even no. 3142 dated 12.11.2010, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Officer

Sweeth Singh Name

Designation

Signature of the Inspecting Officer

Designation