## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. 66/085/2016/402/1784

Dated: 15/12/16

## FIRE SAFETY CERTIFICATE

Certified that the Askon Bhawan Banquet Hall is running at ground floor of building comprised of basement, ground plus two upper floors at 36X, FC-, Karkardooma Institutional area, Delhi-92 owned/occupied by Baba Haridas Educational and Vocational Society have complied with the fire prevention and fire safety requirements in accordance with BBL and verified by the officer concerned of Fire Service on 24/10/16 in the presence of Mr. Ashok Kumar (Manager) of the Banquet Hall and that the ground floor building is fit for occupancy class "D" 'Assembly Building' with effect from the conditions of the period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on.....at New Delhi by

(Vipin Kental) Chief Fire Officer

To.

Manager, Askon Bhawan at 36X, FC-, Karkardooma Institutional area, Delhi -92

Copy to:-

 The Deputy Health Officer (EDMC), SHD (N)-Zone, Health Department, Delhi-110032

## **CONDITIONS**:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 7. The basement shall only Be used as per BBL1983.
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, six months prior to its expiry.

1. Name & address of the building : Askon Bhawan at 36X, FC-, Karkardooma Institutional area, Delhi -92

2. Building is comprised of : B+G+2 floors(Banquet Hall at ground floor only)

3. Type of Occupancy : Assembly (Banquet Hall)

4. Type of Case : New Case

5. Details of Previous NOC : Nil6. Fire Safety direction letter No : BBL

7. Date of Inspection : 24/10/16

8. Name of the Inspecting Officers: : R.K.Yadav (ADO)

9. Name of the designation of Officer

from the building side : Mr.Ashok Kumar (Manager)

10. Year of Construction : 2003

S.N	pplicant's letter No : date  Minimum Standards on fire pre-	BBL	Provided at	Remarks		
0	vention and fire safety U/R33		Site	MR/NMR		
1	Access to building					
	Road width	6 m	10 m	MR		
	Gate width	4.5 m	4.5 m	MR		
	Width of internal road	N.A.	N.A.	N.A.		
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases					
	Upper Floor	2 no.	2 no.	MR		
	Basement	2 no.	2 no.	MR		
	b. Width of Staircases	H. H.				
	Upper Floor	N.A.	2 no. of 1.5 m	MR		
	Basement	N.A.	1 no. of 1.5 m	MR		
	c. Protection of exits					
	Fire check door	Required	provided	MR		
	Pressurization	Required	provided	MR		
	e. No. of continuous staircases to terrace	N.A.	1 no.	MR		
	g. Width of Corridor	N.A.	N.A.	N.A.		
	h. No. of door	N.A.	N.A.	N.A.		
	i. Door Size	2 no. of 2.0 m	provided	MR		
3	Compartmentation.					
	Fire check door	Required	provided	MR		
	Sealing of electrical shafts	Required	provided	MR		
	Fire rating of shaft door	N.A.	N.A.	N.A.		
	Water curtain	N.A.	N.A.	N.A.		
	Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	Basement	30a/c per hour	Provided	MR		
	Upper floor	12 a/c perhour	Provided	MR		
5	Fire Extinguisher					
	Total numbers	10 nos.	Provided	MR		
	Types	CO <sub>2</sub> & ABC	Provided	MR		
	IS marking	ISI marked	Provided	MR		

NIS

6	First-aid-Hose Reels.					
	Total numbers of each floor	1 no.	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N.A.	N.A.	N.A.		
	Location of main panel	N.A.	N.A.	N.A.		
	Location of repeater panel	N.A.	N.A.	N.A.		
	Alternate source of power	N.A.	N.A.	N.A.		
	Hooters's location	Required	Provided	MR		
8	MOEFA	Required	Provided	MR		
9	Public address System.	N.A.	N.A.	N.A.		
	Automatic Sprinkler System.	II.A.	140.0	1.40		
10	basement	Required	Provided	MR		
	upper floor	N.A.	N.A.	N.A.		
	sprinkler above false ceiling		N.A.	N.A.		
75.00		N.A.	IV.A.	IV.A.		
11	Internal Hydrants	1400	Described.	NAD.		
	size of riser/down-comer	100 mm	Provided	MR		
	Total no. of hydrants each floor	1 no.	Provided	MR		
	Hose Box per floor	1 no.	Provided	MR		
12	Yard Hydrants.					
12	Total number of hydrants	N.A.	N.A.	N.A.		
	Hose Box	N.A.	N.A.	N.A.		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	N.A.	N.A.	N.A.		
	Head of Main Pump	N.A.	N.A.	N.A.		
	Number of main pumps	N.A.	N.A.	N.A.		
	Jockey pump out put	N.A.	N.A.	N.A.		
	Jockey pump head	N.A.	N.A.	N.A.		
	Standby pump out put	N.A.	N.A.	N.A.		
	Standby pump Head	N.A.	N.A.	N.A.		
	Auto Starting /Manual stopping	N.A.	N.A.	N.A.		
	Pump House Access	N.A.	N.A.	N.A.		
	Terrace Level	IN.A.	IN.A.	14.74.		
	Discharge of pump	900 Lpm	Provided	MR		
	➤ Head of the Pump	40 m	Provided	MR		
	> Power supply	Required	Provided	MR		
	> Auto Starting of pump	Required	Provided	MR		
		nequired	Flovided	IVII		
14	Captive Water Storage for Fire Fighting.					
	Underground tank capacity	N.A.	N.A.	N.A.		
	Draw-off connection	N.A.	N.A.	N.A.		
	Fire service inlet	N.A.	N.A.	N.A.		
	Access to tank	N.A.	N.A.	N.A.		
	Overhead Tank capacity	15,000 Liters	Provided	MR		
15	Exit Signage.	Required	Provided	MR		

16	Provision of Lifts.				
	Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage	N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
4.7		N.A.	N.A.	N.A.	
17	Standby power supply	Required	Provided	MR	
18	Refuge Area.				
	Total area	N.A.	N.A.	N.A.	
	Location	N.A.	N.A.	N.A.	
19	Fire Control Room				
	Detector system panel	N.A.	N.A.	N.A.	
	Flow switch panel	N.A.	N.A.	N.A.	
	PA system panel Batter backup Building Floor Plans	N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.	

The fire extinguishers provided in the building were tested/ checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name- R.K. Yadav

Designation- ADO (LN)

DO(ED)

Defo(NOZ)

22/11

87/CFOND2

FTD