## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADOUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ MD2/2096

Dated: 24/11/11-

## FIRE SAFETY CERTIFICATE

Certified that the Sawera International Guest House, 7875, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 4 Upper Floors (ground floor reception + 03 guest rooms + office 1st floor to 3rd floor 06 guest rooms at each floor total 21 guest rooms) 4th floor having 05 rooms used owner's residence + kitchen was granted FSC by this department vide letter No.F6/DFS/MS/2012/GH/3777 dated 12/10/2012. The premise was re-inspected by the officer concerned of this department on 03/11/15 in the presence of Sh. Sukhvinder Singh (**Proprietor**) and found that the owner have added 4<sup>th</sup> floor 06 rooms in guest rooms & now floor wise number of guest rooms will be as ground floor (reception + 03 guest rooms) 1<sup>st</sup> to 4<sup>th</sup> floor 06 guest rooms each to talling 27 guest rooms and said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 27 guest rooms only as above with effect from ----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - 24 11/15 at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service

Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1<sup>st</sup> Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee. Sawera International Guest House, 7875, Arakashan Road, Pahar Ganj, New Delhi.

## Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-14111-

## INSPECTION REPORT

1. Name & address of the building:- Sawera International Guest House, 7875,

Arakashan Road, Pahar Ganj, New Delhi.

2. Type of occupancy:- Residential Group A-1 Ground,

+ 4 Upper Floors (Total 27 Guest

Rooms)

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/2012/GH/3777 dated

12/10/2012.

5. Fire safety directives No.- N/A

6. Date of inspection: 03/11/15

7. Name of the inspecting officer:- D.O. Gurmukh Singh

8. Name & designation of officer

From the building side:- Sh. Sukhvinder Singh (Prop.)

9. Year of construction:- 2001

10. Applicant's letter No:- 2060-61/Joint.C.P./Lic. dated 08/10/15

		8	in.C.1 ./Lic. dated 0	Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	3 Mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	NA	NA	NA		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 No	01 No.	MR		
	2. Basements	NA	NA	NA		
	B. Width of staircase					
	1. Upper floors	80 cms	125 cms.	MR		
	2. Basements	NA	NA	NA		
	C. Protection of exits		3			
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 Mtr.	1 Mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	NA	NA		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	14 Nos.	14 Nos	MR		

	2) Types	ABC & CO2	ABC, CO2 &	MR*		
1-1-1	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1)Total number of each	01 no.	01 no.	MR		
	floor	1				
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR		
	3) Nozzle diameter	5 mm	5 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	NA	NA	NA		
9.	Public Address System	Required	Provided	MR		
	/Intercom	1	11012	IVAA		
10.	Automatic Sprinkler System					
10.	1) Basement	NA	NA	NA		
1	2) Upper floors	N/A	N/A	N/A		
1	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	14/21	IV/IX	11/11		
11.	Internal Hydrants					
11.		NA	NA	NA		
	2) Number of hydrants per	NA	NA NA	NA NA		
V	floor	INA	INA	INA		
	3) Hose box	NA	NA	NA		
12.	Yard Hydrants	IVA	INA	INA		
12.	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A N/A	N/A		
13.	Pumping Arrangement	IV/A	IN/FA	IN//A		
13.	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	b) Head of main numn	NT/A	DT/A	NT/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump		N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping					
	2) Terrace level					
	a) Discharge of pump	450 LPM	450 LPM	MR		
	b) Head of pump	30 Mtr.	30 Mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire	Fighting				
	1) Under ground tank	N/A	N/A	N/A		

	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 Ltr.	2,500 Ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	n for Protection o	f special Risk, if	N/A

The owner have added 06 guest rooms of 4<sup>th</sup> floor, which were earlier used for owner's residence & kitchen, after renovation.

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter NoF6/DFS/MS/2012/GH/3777 dated 12/10/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

Dy. C.F.O. (NDZ)

Lagre