FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

No. F6/OGS/ans/EH/2015/W2/2/19

Dated: 0 1/12/15

FIRE SAFETY CERTIFICATE

Certified that the Kays Banquet Restaurants located at Plot No.-4, Nipum Complex, Ashok Vihar, Delhi-110052 on Ground Floor of premises comprised of Basement+ Ground +Maz+3 upper Floors owned /occupied by Kays Banquet Restaurants have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 01/08/2015 in the presence of Sh Pushipinder Singh(Owner) that the premises is fit for occupancy class "Assembly" Group D with effect from bl/15 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ...O.I. / 1.2. / 1.5... at New Delhi by.

Santokh Singh)

Copy to:

1. Dy. Health Officer, Civil Line Zone, 16, Raj pura Road, Delhi-110054

2. Sh Pushpinder Singh Kays Banquet Restaurants, Ground Floor, Plot No.-4, Nipum Complex, Ashok Vihar, Delhi-110052

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws 1983.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Kays Banquet Restaurants, At Ground Floor, Plot No.-4, Nipum Complex, Ashok Vihar, Delhi-110052.

2. Type of Occupancy : Assembly (Restaurant)

3. Type of Case : New (At Ground Floor in the building comprised of Basement + Ground + Mezzanine + 3 Upper Floor)

4. Details of previous NOC : Nil

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 01/08/2015

7. Name of the Inspecting Officer: ADO (WP)

8. Name and designation of Officer

from the building side : Sh. Pushpinder Singh Chawla

9. Year of Construction : 2014

10. Applicant's letter No. : DHO/CLZ/2015/1036 dated 22-07-2015

Sr.		num standards on fire	NBC/BBL	Provided at site	Remarks
No	prevei	ntion and fire safety U/R	Requirements		MR/NMR
1.		s of building			
CONTRACTOR CONTRACTOR	9	Road width	6 mtr.	Provided	MR
	9	Gate width	NA	NA	NA
	9	Width of internal road	NA	NA	NA
2.	Numb	er, width, Type & Arrang	ements of exits		
	The state of the s				
	a.	· · · · · · · · · · · · · · · · · · ·			
	9	Upper floors	NA	01 Provided	NA
	9	Basements	NA	01 Provided	NA
	b.	Width of staircases			the same of the sa
	٥	Upper floors	NA MA	1x130cm	NA
	Φ	Basements	NA	1x127cm	NA
	C.	Protection of exits			
	9	Fire check door	Required	Provided	MR
	 Upper floors Basements Protection of exits Fire check door Pressurization No of continuous 	Pressurization	NA	NA	NA
	d.	No of continuous staircase to terrace	Required	Provided	MR
	e.	Width Of Corridor	NA	NA	NA
	f.	Door Size	1x1.5 mtr.	Provided	MR
			&1x1mtr		17111

1/12

		· y		
	Compartmentation	Required	Provided	MR
	• Fire check door			NA
		NA	NA	INT
	shafts		> T A	NA
	 Fire Rating of shaft 	NA	NA	INA
	door		NTA .	NA
	 Water Curtain 	NA	NA	NA
	 Fire Dampers 	NA	NA	1471
	Smoke managements System			
		30 a/c per hour	Provided(Exhaust	MR
	 Basements 		fan provided)	
	Y I Grand	NA	Provided	NA
-	• Upper floors			
,	Fire Extinguishers	2 ABC / CO2	2	MR
	 Total numbers 	and a second	Provided	MR
4. Si	• Types	ISI marked		2.00
	 IS marking 		Provided	MR
	Ti A'd Hass Dools			
6.	First – Aid Hose Reels Total numbers on each	1	Provided	MR
	floor			
	 Length of hose reel 	30 m	Provided	MR
	hose	5 mm	Provided	MR
	Nozzle diameter			
pm)	Automatic fire detection and al	arming system		D.Y.A.
/,	m Clatactore	NA	Provided	NA
	Dane	NA	Provided	NA
	r dies of Donaster	NA	NA	NA
	Panel			NA
	the standard of	NA	Provided	IN A
				NA
	e Hooters' Location	NA	Provided	
	The same of the sa	Required	Provided	MR
-	11 0 1-11	NA	NA	NA
	· c · l-lan Cristam			
8. 9. 10.	U. Automatic Sprinkler System	NA	Provided	NA
	Basements	NA	Provided	NA
	• Upper Floor	NA	Provided	NA
	• Sprinkler above false			
	ceiling			
1	1. Internal Hydrants:	100 mm	Provided	MR
	Size of riser/down-			
	comer	1	Provided	MR.
	Number of hydrants			
	per floor	1	Provided	MR
-	• Hose Box		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
	12. Yard Hydrants			
-	The state of	NA	NA	NA
	Total number of	NA	NA	NA
5. 6. 7. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	hydrants	1 1 1		
	 Hose Box 			

1		5	
	,		

1)				
13.	Pump	oing Arrangements:						
	0	Ground Level						
	0	Discharge of main pump	o NA	NA	NA			
	>		NA	NA	NA			
	>			NA	NA			
	>		NA	NA	NA			
	>		NA	NA	NA			
	>		NA	NA	NA NA			
	. >		NA NA	NA NA				
	>	,	NA		NA			
		stopping	IVA	NA	NA			
	>		NA	NIA	D.T.A.			
	Terrace level		INA	NA	NA			
	>	Discharge of pump	4501	4501				
	>		450 lpm ·	Provided	MR -			
		Power supply	40 m	Provided	MR			
Name of the least	. 2	1 1 1	Required	Provided	MR			
		. rate starting of pump	Required	Provided	MR			
14.	Captiv	ve water Storage for fire fi	ghting:					
	٥	Under ground tank	NA	NA	NA			
	3	capacity						
	1	Draw off connection	NA	NA	NA			
	1	The service inict	NA	NA	NA			
	>	Access to tank	NA	NA	NA			
	9	Overhead Tank capacity	10, 000 liters	10, 000 Liters	MR			
15	Exit S	ignage	Required	Provided	MR			
16.	Provis	ion of Lifts (Lift Provide	d for upper Floo	or)				
	>	Pressurization of Lift	NA	NA	NA			
		Shaft		- B				
		Pressurization of lift	NA	NA	NA			
		lobby						
	-	Communication in lift	NA	NA	NA			
		Car						
	>	Fireman's Grounding	Required	Provided	MR			
		Switch						
	>	Lift Signage	Required	Provided	MR			
10				1/4				
17.		y power supply	Required	Provided	MR *			
18.	Refuge		-					
		Total area	NA	NA	NA			
		Location	NA	NA	NA			
19.	Fire co	ntrol room						
	2	Detector system panel	NA	NIA .	NEW TOTAL			
	À	Flow Switch Panel		NA	NA			
	>	PA System Panel	NA	NA	NA			
	>	Battery backup	NA	NA	NA			
		Building Floor Plans	NA NA	NA NA	NA NA			

	~	1/14			
20. Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA		
The fire protection syst the time of inspection. Keeping in view the su fire safety required under the the Delhi Fire Service NIL	ubstantial completules it is recom Rules 2010/is	liance of the min mended to grant ssue shortcomi	nimum standards of Fire Safety Certifings as noted Ground floor, M	n fire prevention and teate under rule 35 of at serial numbers	
office, the 1 st , 2 nd & 3 rd floors Signature of the hispecting Of Name Uder 1/7 So	ficer	Sig	gnature of the Inspe ume esignation	ecting Officer	<i>/</i> 0