## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F.6/DFS/MS/EH/2015/SZ/ 2112

Dated: 30 11 15

## FIRE SAFETY CERTIFICATE

Certified that The Village Restaurant (K.I.C. Food Products Pvt. Ltd) at Village Complex, Asian Games Village, Sirifort Road, New Delhi, running at ground floor & 1<sup>st</sup> floor of the building comprised of basement, ground plus one upper floor was granted NOC by this department vide letter No. F6/MS/DFS/EH/2012/4292 dated. 16.11.2012. The premises was re-inspected by the officers concerned of Delhi Fire Service on 18.11.2015 in the presence of Sh. Ajay Pundir (Manager) of the restaurant and observed that fire safety norms as required under Rule 33 of Delhi Fire Service Rules, 2010 have deemed complied and that the building / premises is fit for occupancy class-D "Assembly building Restaurant" with effect from 30 11 for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule 2010.

Issued on .30 11 at New Delhi by

(Dr. G.C. Misra) Chief Fire Officer T.No.011-2341433

Copy to: -

1. The DHO(South Zone), Office of Deputy Health Officer, M.C.D. Health Department South Zone, Green Park, New Delhi,

2. The Authorized Signatory, M/s The Village Restaurant (K.I.C. Food Products Pvt. Ltd) at Village Complex, Asian Games Village, Sirifort Road, New Delhi.

## Conditions for the validity of Fire Safety Certificate

1. All the Fire Safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.

2. Building Sanctioning Authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate

stands null and void.

3. The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

4. The Basement shall be used strictly as per the provisions of Building Bye Laws.

5. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

N/13

| 1   |   | 10713  |   |                      |  |  |
|-----|---|--|---|----------------------|--|--|
| 10  |   | INSPECTION REPORT  |   |                      |  |  |
| 1 1 | Name & address of the building  | The Village Restaurar  | nt (K.I.C. Food Products P                | rt. Ltd), at Village |  |  |
|     |   | Complex, Asian Games Village, Sirifort Road, New Delhi B+G+1st floor. ( Resturant running at ground & 1st floor) |   |                      |  |  |
| 2   | Building Comprised of   | B+G+1st floor. ( <b>Rest</b>   | urant running at ground a                 | & 1St floor)         |  |  |
| 3   | Type of Occupancy   | Assembly building "D" Restaurant   |   |                      |  |  |
| 4   | Type of case  | Renewal  |   |                      |  |  |
|     | Details of previous NOC   | F6/MS/DFS/EH/2012/4292 dated. 16.11.2012   |   |                      |  |  |
|     | Fire safety directives letter No  | Nil  |   |                      |  |  |
| 7   |   | 18.11.2015   |   |                      |  |  |
| ٦   | Date of inspection  | : D.O. (South) D.P. Bhardwaj, ADO Vedpal (SJ)  |   |                      |  |  |
|     | Name of the inspecting Officers :   |  |   |                      |  |  |
|     | Name and designation of officers from the building side                         | Sh. Ajay Pundir ( Manager),  |   |                      |  |  |
|     |   |  |   |                      |  |  |
| 10  | Year of construction  | 1982   |   |                      |  |  |
| 11  | Applicant's letter No.  | Nil dated 26.10.2015   |   |                      |  |  |
| NO. | Minimum Standards on fire prevention  | NBC Requirement  | Provided at site                          | Remarks              |  |  |
|     | and fire safety U/R 33  | 120  |   | MR / NMR             |  |  |
| 1   | Access to building  |  |   | IMD.                 |  |  |
|     | 1) Road width   | Required   | 6 Mtr                                     | MR<br>N/A            |  |  |
|     | Sate width     Width of internal road   | N/A  | N/A                                       | N/A                  |  |  |
|     |   | N/A  | N/A                                       | IN/A                 |  |  |
| 2   | Number, width Type & arrangement of   | exits  |   |                      |  |  |
|     | a. Number of staircases   |  |   |                      |  |  |
|     | 1. Upper floors   | Two  | Provided                                  | MR                   |  |  |
|     | 2. basements  | One  | Provided                                  | MR                   |  |  |
|     | b. Width of staircase   | One  |   |                      |  |  |
|     | b. Widii of Standage  | F- T-  |   |                      |  |  |
|     | 1. Upper floors   | Required Old Case  | 1.25 & 1.00 Mtr                           | MR (Old Case)        |  |  |
|     | 2. basements  | Required Old Case  | 1 Mtr                                     | MR (Old Case)        |  |  |
|     | c. Protection of exits  |  | NI/A                                      | N/A                  |  |  |
|     | 1. Fire check door  | N/A  | N/A                                       | N/A                  |  |  |
|     | <ul><li>2. Pressurization</li><li>d. No. of continuous staircase to t</li></ul> | N/A<br>e One   | N/A<br>One                                | MR                   |  |  |
|     | 4. 1101 01 00111111111111111111111111111  |  |   |                      |  |  |
|     | e. Width of corridor  | N/A  | N/A<br>Gr. Floor- 2.00 & 1.43             | N/A                  |  |  |
|     | f. Door size  | Required Old Case  | Mtrs & 1st floor- 1.5 & 1.64 Mtr Provided | MR                   |  |  |
| 3   | Compartmentation.   | I THE PARTY OF THE   |   |                      |  |  |
| -   | 1. Fire check door  | N/A  | N/A                                       | N/A                  |  |  |
|     | 2. Sealing of electrical shafts   | N/A  | N/A                                       | N/A                  |  |  |
|     | 3. Fire Rating of shaft door  | N/A  | N/A                                       | N/A                  |  |  |
|     | 4. water curtain  | N/A  | N/A                                       | N/A                  |  |  |
|     | 5. Fire dampers   | N/A  | N/A                                       | N/A                  |  |  |
| 4   | Smoke Management system.  | 00 - /   |   |                      |  |  |
|     | basement  | 30 a/c per hour<br>12 a/c per hour   | Exhust Fans                               | MR                   |  |  |
|     | upper floors  |  | Exhust Fans                               | MR                   |  |  |
| 5   | Fire Extinguishers  |  | (1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -  |                      |  |  |
|     | total numbers   |  | 18 Nos                                    | MR                   |  |  |
|     | Types   | en Til   | ABC, Co2 Provided                         | MR                   |  |  |
|     | ISI marking   | ISI  | Yes                                       | MR                   |  |  |

|     | a port for the sense and are prefer three to 172 his | Required  | Gr. Floor 2 Nos. & 1st | MR   |
|-----|--|---|------------------------|------|
| to  | otal numbers on each floor                           | READ MILLERANGER  | floor- 1no. Provided   | MR   |
| L   | ength of Hose reel hose                              | 30 Mtr  | Provided               | MR   |
|     | Nozzle Diameter                                      | 5 MM  | Provided               | IVIH |
| 7 A | Automatic fire detection and alarming sy             |   | B 11.1                 | MR   |
| T   | ype of detectors                                     | Required  | Provided               | MR   |
| lo  | ocation of Main Panel                                | Ground floor  | Provided               |      |
| lo  | ocation of Repeater panel                            | N/A   | N/A                    | N/A  |
| A   | Alternate source of power                            | Required  | Provided               | MR   |
| h   | nooter's location                                    | Required  | Provided               | MR   |
| 8 1 | MOEFA  | Required  | Provided               | MR   |
|     | Public Address System.                               | N/A   | N/A                    | N/A  |
|     | Automatic Sprinkler System.                          | -x  |                        |      |
|     | pasement   | N/A   | s N/A                  | N/A  |
|     | upper floors   | Required  | Provided               | MR   |
|     | sprinkler above false ceiling                        | N/A   | N/A                    | N/A  |
|     | Internal Hydrants                                    | and a part of the state of the |                        |      |
|     | Size of riser/down-corner                            | Required  | Provided               | MR   |
|     | Number of Hydrants per floor                         | One   | Provided               | MR   |
| 1   |  | One   | Provided               | MR   |
|     | hose Box   | 0110  |                        |      |
|     | Yard Hydrants.                                       | N/A   | N/A                    | N/A  |
|     | total number of hydrants                             | N/A   | N/A                    | N/A  |
|     | hose box   | IN/A  | 1,47.                  |      |
|     | Pumping arrangements                                 |   |                        |      |
|     | 1. Ground level                                      | NI/A  | N/A                    | N/A  |
| 1   | a. Discharge of main Pump                            | N/A   | N/A                    | N/A  |
| 1   | b.Head of main pump                                  | N/A   | N/A                    | N/A  |
| 1   | c.Number of main pumps                               | N/A   | N/A                    | N/A  |
|     | d.jockey pump out put                                | N/A   | N/A                    | N/A  |
|     | e.jockey pump head                                   | N/A   | N/A                    | N/A  |
|     | f. Standby Pump output                               | N/A   |                        | N/A  |
|     | g.Stanby Pump head                                   | N/A   | N/A                    | N/A  |
| - 1 | h.Auto Starting/Manual stopping                      | N/A   | N/A                    | N/A  |
|     | pump house access                                    | N/A   | N/A                    | IN/A |
|     | 2.Terrace level                                      |   |                        |      |
|     | a. Discharge of pump                                 | 450 & 220 LPM   | Provided               | MR   |
|     | b. head of the pump                                  | 35 Mtr  | Provided               | MR   |
|     | c. Power supply                                      | Required  | Provided               | MR   |
|     | d. Auto starting of pump                             | Required  | Provided               | MR   |
|     |  |   |                        |      |
| 14  | Captive water storage for fire fighting              |   | ALIA                   | N/A  |
|     | 1. Underground tank capacity                         | N/A   | N/A                    | N/A  |
|     | a. Draw-off connection                               | N/A   | N/A                    | MR   |
|     | b. fire service inlet                                | Required  | Provided               |      |
|     | c.Access to tank                                     | N/A   | N/A                    | N/A  |
|     | Over head tank Capacity                              | 10,000  | Provided               | MR   |
| 15  | Exit Signage.  | Required  | Provided               | MR   |
| 16  | Provision of lifts.                                  |   |                        | N/A  |
|     | a. Pressurization of lift shaft                      | N/A   | N/A                    | N/A  |
|     | b. pressurization of lift lobby                      | N/A   | N/A                    | N/A  |
|     | c. communication in lift car                         | N/A   | N/A                    | N/A  |
|     | d. Fireman's grounding switch                        | N/A   | N/A                    | N/A  |
|     | e. Lift signage                                      | N/A   | N/A                    | N/A  |
| 17  | Standby power supply                                 | Required  | Provided               | MR   |
| 18  | Refuge Area.   |   |                        |      |

| 0 | ) | 0 |
|---|---|---|
|---|---|---|

| N/A | N/A               | N/A                         |
|-----|-------------------|-----------------------------|
| N/A | N/A               | N/A                         |
|     | N/A<br>N/A<br>N/A | N/A N/A N/A N/A N/A N/A N/A |

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules of NOC issued vide letter no.F6/MS/DFS/EH/2012/4292 dated. 16.11.2012 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name D. P. Bhardwaj

Designation : Divisional Officer (South)

Signature of the inspecting officer

Name Vedpal

Designation : ADO (SJ)