FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE

NEW DELHI - 110001

F6/DF5/M5/ BNOT/2015/W2/ 2143

Dated: 08/12/15

FIRE SAFETY CERTIFICATE

Certified that the M/s Mehak Banquet (A Unit of Amour Banquets Pvt. Ltd.) Upper Ground Floor and First Floor only located at Plot No. 43/35, Rohtak Road, West Punjabi Bagh, New Delhi - 110026 in a building comprised of Basement + Stilt + Upper Ground + 3 Upper Floors owned/ occupied by M/s Mehak Banquet (A Unit of Amour Banquets Pvt. Ltd.) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officer concerned of this department on 05-11-2015 in the presence of Mr. Rohit Kochar (Director) and found that the said building / premises is fit for occupancy class "Assembly" Group D with effect from ______ o 8 1215 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 981.171.15. at New Delhi by.

Chief Fire Officer. Ph: 011 - 23414250.

Copy to:

1. Sh. Rohit Kochar (Director), M/s Mehak Banquets (A unit of Amour Banquets Pvt. Ltd.), 43/35, Rohtak road, West Punjabi Bagh, New Delhi – 26.

2. Dy. Health Officer, West Zone, South Delhi Municipal Corporation, Vishal Enclave, Rajouri Garden, New Delhi - 110027.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used strictly as per Building Bye Laws.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: Mehak Banquet, Upper Ground Floor & First Floor, 43, Road No. 35, Rohtak Road, West Punjabi Bagh, New Delhi – 110026.

2. Type of Occupancy

: Assembly (Basement + Stilt + Upper Ground + 3 Upper

Floors) Height = 14.75m.

3. Type of Case

: New

Area=464.503 sqm. Basement=Storage,

Stilt=Parking

4. Details of previous NOC

: Nil

UGF & FF = Banquet Hall

Second Floor = Vacant Third Floor = Rooms

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 05-11-2015

7. Name of the Inspecting Officer: Mukesh Verma ADO (MN)

8. Name and designation of Officer

from the building side

: Sh. Rohit Kochar (Owner)

9. Year of Construction

: 2014

10. Applicant's letter No.

: D-2131/HD/WZ Dated 15-10-2015

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR
1.	Access of building		10 1	
	 Road width 	12 m	Provided	MŘ
	Gate width	5 m	On Main Road	MR
	 Width of internal road 	NA	NA	NA
2.	Number, width, Type & Arrang	ements of exits		
	a. Number of staircases			
	Upper floors	2	3 Provided	MR
	Basements	NA	NA -	NA
	b. Width of staircases			
	• Upper floors	1X2m, 1X1.5m	1X205cm, 1X1m, 1X1.5 m	MR
	Basements	NA	150 cm, 156 cm	NA
	c. Protection of exits			
	 Fire check door 	Required	Provided	MR
	 Pressurization 	NR '	NR	NR
	d. No of continuous staircase to terrace		2 Provided	MR
	e. Width Of Corridor	NA	NA	NA
	f. Door Size	2X2m	UGF (3 exits) - 205 cm, 200 cm, 168 cm, FF (2 exits) - 200 cm, 200 cm	

3.	Compartmentation				
	 Fire check door 	NR	NR	NR	
	 Sealing of electrical shafts 	NR	NR	NR	
	 Fire Rating of shaft door 	NR	NR	NR	
	 Water Curtain 	NA	NA	NA	
	• Fire Dampers	NA	NA	NA NA	
4.	Smoke managements System	Appendix and the second	1 17 1		
	Basements	Required	Provided	MR	
	• Upper floors	Required	Provided	MR	
5.	Fire Extinguishers	100,000			
-/-	• Total numbers	08 nos.	Provided	MR	
		ABC & CO ₂	Provided	MR	
	A STATE OF THE STA	ISI marked	Provided	MR	
6.	IS marking First – Aid Hose Reels	1171 HIGHROG	Tiovided	19110	
0.		1	Provided	MR	
	 Total numbers on each floor 	3000		1	
	 Length of hose reel hose 	30 m	Provided	MR	
	 Nozzle diameter 	5 mm	Provided	MR	
7.	Automatic fire detection and	alarming system			
	• Type of detectors	Smoke & Heat	Provided	MR	
	 Location of Main Par 		Provided	MR	
	 Location of Repeater Panel 		Provided	MR	
	 Alternate source of 	Required	Provided	MR	
	power • Hooters' Location	Required	Provided	MR	
0		AND THE RESIDENCE OF THE PROPERTY OF THE PROPE		April 1	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	D ' 1	Descided	MD	
	• Busements	Required	Provided	MR	
	• Upper Floor	NR	Provided	MR	
	 Sprinkler above false ceiling 	NR	Provided	MR	
11.	Internal Hydrants				
	 Size of riser/down- comer 	100 mm	Provided	MR	1
	 Number of hydrants per floor 	1	Provided	MR	
	 Hose Box 	1	Provided	MR	
12.	Yard Hydrants				
	 Total number of hydrants 	NR	NR	NR:	
1.0	 Hose Box 	NR	NR	NR.	
13.	Pumping Arrangements .				
	 Ground Level 	110	2000		
	 Discharge of main pump 	NR	2280 lpm Provided	MR	-
	➤ Head of main pump	NR	70 m Provided	MR	
	Number of main pur	ips NR	1 Provided	MR	
	> Jockey pump out put		180 lpm Provided	MR	*
Service and relations and a service of			Provided		_

Mehal Banguet hall, 43, Rano 35, Rohlan Rocar, Jockey pump head NR 70 m Provided Standby Pump out put NR NR NR Standby Pump Head NR NR NR Auto Staring/Manual NR NR NR stopping Pump House Access NR NR NR Terrace level Discharge of pump Head of the pump Head of the pump Head of the pump Provided Provided MR	hr.
Standby Pump out put Standby Pump Head Standby Pump Head NR	
Standby Pump Head NR NR NR NR NR NR NR Stopping Pump House Access NR	
Standby Pump Head Auto Staring/Manual NR NR NR NR NR NR NR Stopping Pump House Access NR	
Auto Staring/Manual NR NR NR stopping Pump House Access NR NR NR Terrace level Discharge of pump 900 lpm Provided MR Head of the pump 40 m Provided MR Power supply Required Provided MR Auto starting of pump Required Provided MR Captive water Storage for fire fighting	
stopping Pump House Access NR NR NR Terrace level Discharge of pump Head of the pump Provided Provided NR Provided NR Provided NR Provided NR Auto starting of pump Required Provided NR Provided NR Auto starting of pump Required Provided NR 14. Captive water Storage for fire fighting	
Pump House Access Terrace level Discharge of pump Head of the pump Provided Provided Provided MR Provided MR Provided MR Provided MR Provided MR Provided MR Auto starting of pump Required Provided MR Provided MR Provided MR	
Terrace level Discharge of pump Head of the pump Provided Provided Required Provided Required Provided NR Provided NR Provided NR Captive water Storage for fire fighting	
Head of the pump Power supply Auto starting of pump Required Provided Provided NIR Required Provided NIR 14. Captive water Storage for fire fighting	
Power supply Required Provided MR Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting	
Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting	
14. Captive water Storage for fire fighting	
• Inder ground tank	
capacity	
Draw of connection Required Provided MR	
Fire service inlet Required Provided MR	
Access to tank Required Provided MR	
• Overhead Tank 15,000 litres Provided MR	
capacity	
15 Exit Signage Required Provided MR	
16. Provision of Lifts NR NR (as lift is	
17essurization of Litt	
Shaft stilt floor)	
N. I.	
Pressurzation of the	
Communication in lift Required Provided MR.	
Car Rectance 17 (180)	
Fireman's Grounding NR Provided NR	
Switch	
List Signage NR NR NR	
17. Standby power supply Required Provided MR	
18. Refuge Area	
Total area NA NA NA	
Location NA NA NA	
19 Fire control room	
Detector system panel NA NA NA	
Flow Switch Panel NA NA NA	
PA System Panel NA NA NA	
Battery backup NA NA NA	
Building Floor Plans NA NA NA	
20. Special Fire Protection NA NA NA	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Systems for Protection of special Risks, if any;

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Note: The premises was earlier mentioned as Basement + Stilt + Ground + Three Upper Floors now, FSC is now requested for Upper Ground Floor and First Floor as per DHO letter no. D-2131/HD/WZ dated 15-10-15. The ground floor is now upper ground floor. The height upto First Floor is 8.5 m. The rear spiral staircase as shown in the plan is now 1m wide normal staircase. The lift is now terminating at Stilt Floor.

Signature of the Inspecting Office 15
Name
Designation

ADO (MN)

Signature of the Inspecting Officer Name
Designation