## FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI** 

No. FE DFS MS 2015 2185

Dated: 15 12 2015

## FIRE SAFETY CERTIFICATE

Certified that the Punjabi Bagh Club located at Punjabi Bagh, Ring Road, New Delhi-110026 comprised of Basement + Ground + 2 Upper Floors was granted NOC by this department vide letter no. F6/DFS/MS/Club/2012/253 dated 27-01-2012. The premises was re inspected by the officers concerned of this department on 03-12-2015 in the presence of Mr. Madhup Wadhwa (General Manager) of the Club and found that the building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010. Hence the NOC is renewed and premises is fit for Class D (Assembly) occupancy with effect from ASIL DelS. for a period of three years subject to conditions printed below.

Issued on 15 12 2015... at New Delhi by.

(Santokh Singh) Chief Fire Officer Delhi Fire Service Tel. -011-23414250

Copy to:

 Sh. Gurinder Pal Singh (Raju), Hony. Gen. Sec. Punjabi Bagh Club, Punjabi Bagh, Ring Road, New Delhi-110026.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The basement shall be used strictly as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

## **INSPECTION REPORT**

1. Name & address of the building: Punjabi Bagh Club located at Punjabi Bagh, Ring Road, New Delhi-110026.

2. Type of Occupancy : Class D (Assembly)

3. Type of Case : Renewal

4. Details of previous NOC : Letter no. F6/DFS/MS/Club/2012/253 Dated 27-01-2012.

5. Fire Safety directives Letter No.: Letter no. F6/DFS/MS/2006/347 dated 08-02-2006

6. Date of inspection : 03-12-2015

7. Name of the Inspecting Officer: Do West & ADO (MN)

8. Name and designation of Officer

from the building side : Mr. Madhup Wadhwa (General Manager)

9. Year of Construction : 2006

10. Applicant's letter No. : Nil dated 14-11-2015

S	Minimum standards on fire	NBC	Provided at	Remarks MR/NMR			
No	prevention and fire safety U/R 33	Requriement	site				
1.	Access of building						
*	<ul> <li>Road width</li> </ul>	9 mtrs	Provided	MR			
	Gate width	5 mtr	Provided	MR			
	<ul> <li>Width of internal road</li> </ul>	NA	NA	NA			
2.	Number, width, Type & Arrangem	ents of exits					
	a. Number of staircases						
	<ul> <li>Upper floors</li> </ul>	2	Provided	MR			
	<ul> <li>Basements</li> </ul>	2	Provided	MR			
	b. Width of staircases						
	<ul> <li>Upper floors</li> </ul>	Old Case	Old Case	MR			
	<ul><li>Basements</li></ul>	Old Case	Old Case	MR			
	c. Protection of exits		* * * * * * * * * * * * * * * * * * * *				
	Fire check door	Required	Provided	MR			
	<ul> <li>Pressurization</li> </ul>	NA	NA	NA			
	d. No of continuous staircase	2	Provided	MR			
	to terrace	NA	NA	NA			
	e. Width Of Corridor f. Door Size	Old Case	Old Case	MR			
3.	Compartmentation	010 000	Old Case	IVIIX			
J.		D . 1					
	• Fire check door	Required	Provided	MR			
	Sealing of electrical shafts	NA	NA	NA			
	• Fire Rating of shaft door	NA	NA	NA			
	• Water Curtain	NA	NA	NA			
	• Fire Dampers	NA	NA	NA			
4.	Smoke managements System						
0	<ul> <li>Basements</li> </ul>	Required	Provided	MR			
	<ul> <li>Upper floors</li> </ul>	Natural ventilation	Provided	MR			

		ichors		Provided	MR	
	Fire	Extinguishers	20 nos.	Provided	MR	
		<ul> <li>Total numbers</li> </ul>	ABC & CO <sub>2</sub>	And the same of th	MR	
		• Types	ISI marked	Provided		
		• IS marking			MR	the second of the control of the second of t
	Firs	st – Aid Hose Reels	2	Provided	IVIIC	
	- production of the second	• Total numbers on each	had		MR	The state of the s
		floor	30m	Provided	The second secon	
		• Length of hose reel hose	5mm	Provided	MR	and the second section is the second second second second second second second second second
		i l' - ator				and the second s
	1	<ul> <li>Nozzle diameter</li> <li>utomatic fire detection and alarn</li> </ul>	ning system	Provided	MR	
	A	Type of detectors		Provided	MR	
		rtion of Main Panel	Ground floor	Provided	MR	
		restion of Repeater	Ground floor	1101101		
		Location of Repears		400 KVA	MR	
		Panel  Alternate source of power	Required	Provided	MR	
		• Alternate source of porter	Required	The second secon	MR	
		<ul> <li>Hooters' Location</li> </ul>	Required	Provided	MR	
8.	N	MOEFA	Required	Provided	IVIIX	
9.	I	Public Address System	100		MR	
10	).	Automatic Sprinkler System	Required	Provided		
		• Basements	NA	NA	NA	The second secon
		* Upper Floor	NA NA	NA	NA	
		• Sprinkler above false	17/7			
		ceiling				
	1	I-tomal Hydrants:	The second secon	Provided	MR	
1_1	1.	• Size of riser/down-com	ier 150 mm	Provided	MR	
		by ban of hydrants per	. 2	110 (104		
		floor		Provided	MR	
			2	TTOVICE		
		• Hose Box		D wided	MR	
	12.	Yard Hydrants  Total number of hydra	nts 6	Provided	MR	
			6	Provided	1111	
	Hose Box					
	13. Pumping Arrangements:					
					MR	
	THE PERSON NAMED IN	• Ground Level	mn NA	1620 lpm	TALLY	
		• Discharge of main pu	mp ,	Provided	MR	
			NA	40 mtr	A THE PARTY OF THE	
		> Head of main pump	and the same of th	Provided	MR	
		> Number of main pum	$\frac{1}{180 \text{ LPM}}$	Provided		
		> lockey pump out put	100 1111	Provided	MR	
		> Tockey pump head	40 1111	NA	NA	
		Standby Pump out p	at NA	NA	NA	
		Standby Pump Head	NA .	73 11-	d MR	
		> Auto Staring/Manua	1 Required	110		
		etonning		Provide	d MR	
		> Pump House Access	Required	1101100		
		• Terrace level		1 Provid	ed MR	S.
		<ul><li>Discharge of pump</li></ul>	900 LPM	Provid		
		> Head of the pump	40Mtr	D ide	200	
		> Power supply	Required	i Provide		

	> Auto starting of pump	Required	Provided	MR			
14.							
14.	<ul> <li>Under ground tank</li> </ul>	NA	Provided 50,000 ltr	MR			
	capacity  Draw off connection	NA	Provided	MR			
	<ul><li>Draw off connection</li><li>Fire service inlet</li></ul>	Required	Provided	MR			
	> Access to tank	Required	Provided	MR			
	0 1 170 1	10,000 litres	Provided	MR			
1 /		Required	Not Provided	NMR			
15	Exit Signage Provision of Lifts	required					
16.	> Pressurization of Lift Shaft	NA	NA	NA			
	> Pressurization of lift lobby	NA	NA	NA			
	Communication in lift Car	NA	NA	NA			
	Fireman's Grounding Switch	NA	NA	NA			
	➤ Lift Signage	NA	NA	NA			
17.	Standby power supply	Required	Provided	MR			
$\frac{17.}{18.}$	Refuge Area			THE TOTAL PROPERTY AND ADDRESS OF THE PROPERTY			
10.	> Total area	NA	NA	NA			
	> Location	NA	NA	NA			
19.	Fire control room						
17.	> Detector system panel	Required	Provided	MR			
	> Flow Switch Panel	Required	Provided	MR			
	PA System Panel	Required	Provided	MR			
	> Battery backup	Required	Provided	MR			
	<ul><li>Building Floor Plans</li></ul>	Required	Provided	MR			
20.		NA	NA	NA			

The fire protection systems provided in the building were test checked and found functional at

the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/Club/2012/253 Dated 27-01-2012 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name

Mullery Verms

Designation

Signature of the Inspecting Officer

Name

Designation