GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ ND2/2129

Dated: 03/12/15

FIRE SAFETY CERTIFICATE

Certified that the M/s Adarsh Atithi Niwas Pvt. Ltd. located at 483, Haveli Haider Quli, Chandni Chowk, Delhi. comprised of Ground, Mezzanine + 3 Upper Floors (Ground floor shops, Mezzanine floor office, 1st floor 08 guest rooms + reception, 2nd floor 08 guest rooms + kitchen, 3rd floor 09 guest rooms total 25 guest rooms) was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/2920 dated 09/08/2012. The premise was reinspected by the officer concerned of this department on 24/11/15 in the presence of Mr. Milan Sharma and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 25 guest rooms only as above with effect from 52-1/2-1/2------ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -03/12/15 --- at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to:- (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) M/s Adarsh Atithi Niwas Pvt. Ltd. 483, Haveli Haider Quli, Chandni Chowk, Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building: - M/s Adarsh Atithi Niwas Pvt. Ltd. located at 483, Haveli Haider Quli, Chandni Chowk,

2. Type of occupancy:-

Residential Group A-1 Ground ,Mezz.+ 3 Upper Floors (Total 25 Guest Rooms)

Renewal

3. Type of case:-

4. Details of previous FSC:-

No. F6/DFS/MS/GH/2012/2920 dated

09.08.2012

5. Fire safety directives No.-

N/A

6. Date of inspection:-

24/11/15

7. Name of the inspecting officer:- D.O. Gurmukh Singh

8. Name & designation of officer From the building side:-

Mr. Milan Sharma 1960

9. Year of construction:-

Nil- dated 03/10/15

10. Applicant's letter No:-

10. Applicant's letter No:-	Nil- dated 0	13/10/13	Old Case
No. Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR
Access to Building			MR
1) Road width	N/A	07 mtr.	N/A
2) Gate width	N/A	N/A	
2) Width of internal road	NA	NA	NA
. Number, Width Type & Arrar	ngement of Exits	3	
A. Number of staircases			MR
1. Upper floors	01 No	01 No.	N/A
2. Basements	N/A	N/A	IN/A
B. Width of staircase		07 + 106 om	MR
1. Upper floors	80 cm.	97 to 106 cm	N/A
2. Basements	N/A	N/A	IN/PL
C. Protection of exits		NT/A	N/A
1. Fire check door	N/A	N/A	N/A
2. Pressurization	N/A	N/A	N/A
D. No. of continuous	N/A	N/A	14/11
staircase to terrace	7.7/1	N/A	N/A
E. Width of corridor	N/A	1 Mtr.	MR
F. Door size	1 Mtr.	1 IVILL.	1722
3. Compartmentation		N/A	N/A
1) Fire check door	N/A	N/A N/A	N/A
2) Sealing of electrical shaft	s N/A	N/A N/A	N/A
3) Fire rating of shaft door	N/A	N/A N/A	N/A
4) Water curtain	N/A		N/A
5) Fire Dampers	N/A	N/A	14/11
4. Smoke Management System	n CDII	N/A	N/A
1) Basements	30 ACPH	Natural Natural	MR
2) Upper floors	12 ACPH	Inatural	IVIIC
5. Fire Extinguishers	00.37	09 Nos.	MR
1) Total numbers	09 Nos.	U9 NOS.	17112

7-55	2) Types	ABC & CO2	ABC, CO2 &	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1)Total number of each	01 no.	01 no.	MR		
	floor					
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR		
	3) Nozzle diameter	5 mm	5 mm	MR		
7.	Automatic Fire Detection & A	larming System		1		
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	N/A	N/A	N/A		
	/Intercom					
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling		11/12	11/11		
11.	Internal Hydrants					
	1) Size of riser/down-comer	NA	NA	NA		
	2) Number of hydrants per	NA	NA	NA		
	floor					
	3) Hose box	NA	NA	NA		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement		1 1/21	14/21		
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump	14/21	11/11	17/71		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump		N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A N/A		
	f) Stand by pump output	N/A	N/A N/A	N/A N/A		
	g) Stand by pump head	N/A	N/A N/A			
	h) Auto starting/Manual	N/A	N/A N/A	N/A		
	stopping	IN/A	IN/A	N/A		
	2) Terrace level			,		
	a) Discharge of pump	225 LPM	225 LPM	MD		
	b) Head of pump			MR		
	* * *	30 Mtr.	30 Mtr.	MR		
	c) Power supply	Required	Provided	MR		
1.4	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire		NI/A	DI/A		
	1) Under ground tank	N/A	N/A	N/A		

	capacity	-		27/1	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	2,500 Ltr.	2,500 ltrs.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
1	Total area location	N/A	N/A	N/A	
a) Detect b) Flow s c) PA sy d) Batter	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
		N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:				

The fire protection system provided in the guest house were tested, checked at random and

found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2012/2920 dated 09/08/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

30 Tr

Dy. C.F.O. (2007)