GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2015/ ND2/ 2/64

FIRE SAFETY CERTIFICATE

Certified that the Parkway Dx. Guest House located at 8591, Main Qutab Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (01 office + lobby + reception), 1st floor to 3rd floor (10 guest rooms at each floor), 4th floor (06 guest rooms + 02 store rooms) and terrace floor sealed with brick wall, total 36 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/3996 dated 25/10/12. The premises was re-inspected by the officer concerned of this department on 07/12/15 in the presence of Sh. Suresh (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 36 guest rooms only with effect from --44/12/43----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ----at New Delhi by.

(Dr. G. d. Misra) Chief Fire Officer Ph-011-23414333

Copy to:-

ofeme 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

2. Sh. Suresh (Manager),

Parkway Dx. Guest House, 8591, Main Qutab Road, Pahar Ganj, New Delhi Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

Parkway Dx. Guest House located at 8591, 1. Name & address of the building

Main Qutab Road, Pahar Ganj, New Delhi

Residential, Sub Division-A-1 2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Gr. + 04 Upper floors (total 36 Guest rooms)

Renewal

F6/DFS/MS/GH/2012/3996 dated 25/10/12

N/A 07/12/15

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Suresh (Manager)

2001

No. Nil date 09/11/15

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site PSS	Remarks MR/NMR			
1.	Access to Building						
	1) Road width	N/A	06 mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrangement of Exits						
	A. Number of staircases						
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase						
	1. Upper floors	0.80 mtr.	1.35 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits		1				
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	01	01	MR			
	staircase to terrace						
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1 mtr.	1 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	1) Basements	NA	N/A	N/A			
	2) Upper floors	12 a/c per	Natural Ventilation	MR			
		hour					
5.	Fire Extinguishers		10.37	MD			
	1) Total numbers	12 Nos.	12 Nos.	MR			

				100	e- CO2	MI	3	
1 - 12 - 12 - 12 - 12 - 12 - 12 - 12 -			-		& CO2	MI		
	2) Types 3 ISI marking I	Requi	ired	Prov	ided	TATI		
	First Aid Hose Reel			0.1		M	R	
6.	Total number of eachfloor	01		01	-4	M		
	2) Length of hose reel hose 30 m		tr.	30 n			IR .	
		05 m	m	05 n	nm	IV		
	A demotio Fire Detection & Alai ming System 1.1.1							
7.	1) Type of detectors	OILLO	124	Pro	Vided	-	IR IR	
	2) Location of main panel	Grou	and floor		Near Reception		N/A	
	3) Location of man panel 3) Location of repeater panel	N/A		N/A	11-1		MR	
	4) Alternate source of power	Req	uired	_	vided	-	MR	
	5) Hooter's Location	Gro	und floor	Ne	ar Reception		MR .	
~	5) Hooter's Location	Req	uired		ovided		MR	
8.	MOEFA Public Address System	Rec	juired	Pro	ovided		VIIV	
9.	Automatic Sprinkler System					-	N/A	
10.	Automatic Sprinker System	N/A	A N/A			N/A		
	1) Basement	N/A		N/			N/A N/A	
	2) Upper floors	N/A		N.	/A		IN/A	
	3) Sprinkler above false							
	ceiling						MR	
11.	11. Internal Hydrants 1) Size of riser/down-comer		100 mm		100 mm		MR	
2 2	Size of riser/down-comer Number of hydrants per	01		0	1		IVIIV	
-2							MR	
	floor		01 01		01	IVIIC		
	3) Hose box				7/4		N/A	
12.	12. Yard Hydrants 1) Total number of hydrants		N/A N/A			N/A		
	1) Total number of hydran	N	[/A	1	V/A	-	11/11	
	2) Hose box Pumping Arrangement						N/A	
13.	1) Ground level		N/A		N/A		N/A	
	- f mann		N/A		N/A		INITA	
						1	N/A	
	b) Head of main pump		N/A		N/A		N/A N/A	
	- 1 Congin nill				N/A		N/A	
	aut n	ut	1		N/A		N/A N/A	
hand			N/A		N/A		N/A N/A	
	1.1	put	N/A		N/A		N/A N/A	
g) Stand by pump bead			N/A		N/A		N/A	
h) Auto starting/Manus		ual	N/A		N/A		IVA	
stopping		and treatment and						
		7. 1			7771		MR	
	- Caumn		730 BI II		450 LPM		MR	
b) Head of pump			30 mtr. 30 mtr.			MR		
			Required Provided			MR		
1) A to starting of numb		Required Provided		-	TVIIC			
	Water Storage	for F	ire Fight	ing	127/4		N/A	
1	4. Captive water Storage 1) Under ground tar	ık	N/A		N/A		14/11	
	capacity	1000			7.7/1	-	N/A	
	CC	tion	N/A		N/A		TVIT	
	a) Draw-off confiec					. ,		

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	- 17		
10.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
10.	Total area location	N/A	N/A	N/A
10	Fire Control Room	N/A	N/A	N/A
19.	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
		N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Systems, if any:	stem for Prote	ection of special	NA



The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/GH/2012/3996 dated 25/10/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

20 (ch)

Lahrel Collection