GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ ND2/2/7/

FIRE SAFETY CERTIFICATE

Certified that the Ashoka Castle Guest House, located at 2954/3, Sangtrashan Bazar, Pahar Ganj, New Delhi. comprised of Ground + 4 Upper Floors (Ground floor - reception + office + store + shop, 1st floor - 14 guest rooms, 2nd floor - 07 guest rooms, 3rd floor - 07 guest rooms + 01 staff rooms & 4th floor found sealed total 28 guest rooms) was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/4114 dated 02/11/2012. The premise was re-inspected by the officer concerned of this department on 01/12/15 in the presence of Mr. Govind Singh Bisht and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 28 guest with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, prighted below.

Issued ----- at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service

Ph: - 011-23414333

The Joint Commissioner of Police (Lic.), 1st Floor, Copy to:- (1) Police Station, Defence Colony, New Delhi.

(2)Ashoka Castle Guest House, 2954/3, Sangtrashan Bazar, Pahar Ganj, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-M/18 -

INSPECTION REPORT

1. Name & address of the building:- Ashoka Castle Guest House, located at

2954/3, Sangtrashan Bazar, Pahar Ganj, New

Residential Group A-1 Ground, +3 Upper 2. Type of occupancy:-

Floors (Total 28 Guest Rooms)

Renewal 3. Type of case:-

No. F6/DFS/MS/GH/2012/4114 dated 4. Details of previous FSC:-

02/11/2012.

5. Fire safety directives No.-N/A

01/12/15 6. Date of inspection:-

D.O. Gurmukh Singh 7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

Sh. Govind Singh Bisht.

9. Year of construction:-

Nil. dated 13/11/15 10. Applicant's letter No:-

10.	Applicant's letter No:-	Nil. dated 13/	11/13	Old Case
.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR
•	Access to Building			MR
	1) Road width	N/A	6 Mtr.	N/A
	2) Gate width	N/A	N/A	
	2)Width of internal road	NA	NA	NA
)	Number, Width Type & Arrang	gement of Exits	5	
2.	A. Number of staircases			MR
	1. Upper floors	01 No	01 No.	N/A
	2. Basements	N/A	N/A	IN/A
	B. Width of staircase	-	112 cms. to	MR
	1. Upper floors	80 cms	112 cms. to	TVIIC
		>T/A	N/A	N/A
	2. Basements	N/A	IN/A	
	C. Protection of exits	DI/A	N/A	N/A
	1. Fire check door	N/A N/A	N/A	N/A
	2. Pressurization	N/A N/A	N/A	N/A
	D. No. of continuous	IN/A	14/12	
	staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	1 Mtr.	1 Mtr.	MR
	F. Door size	1 Witt.		
3.	Compartmentation	N/A	N/A	N/A
	1) Fire check door		N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers Superscript System			:
4.	Smoke Management System	30 ACPH	N/A	N/A
	1) Basements	12 ACPH	Natural	MR
	2) Upper floors			
5.	Fire Extinguishers			

-N/19-

		12 Nos.	12 Nos.	MR MR
	2/1/900	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
	First-Aid Hose Reel		01.31	MR
	1)Total number of each floor	01 no.	01 No.	
		30 Mtr.	30 Mtr.	MR
	3) Nozzle diameter	5 mm	5 mm	MR
	Automatic Fire Detection & Ala	arming System		
•	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
	MOEFA	N/A	N/	N/A
	Public Address System	Required	Provided	MR
).	/Intercom	1		
10	Automatic Sprinkler System			
0.	1) Basement	N/A	N/A	N/A
		N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	14/11	2	
	ceiling			
11.	Internal Hydrants	N/A	N/A	N/A
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	IN/A	14/21	
	floor	N/A	N/A	N/A
	3) Hose box	IN/A	14/11	
12.	Yard Hydrants	N/A	N/A	N/A
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	14/11	
13.	Pumping Arrangement	DT/A	N/A	N/A
11	1) Ground level	N/A		N/A
	a) Discharge of main	N/A	N/A	14/11
	pump	77/1	DI/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pum	p N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	
14.	f) Stand by pump outpu	t N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			
	2) Terrace level			100
	a) Discharge of pump	180 LPM	180 LPM	MR
	b) Head of pump	30 Mtr.	30 Mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pum		Provided	MR
	Captive Water Storage for F			

- (- 1	16	~ .			

	1) Under ground tank	N/A	N/A	N/A
	capacity a) Draw-off connection	N/A	N/A	N/A
		N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank d) Over head tank	2,500 Ltr.	2,500 Ltr.	MR
15.	capacity Exit Signage.	Required	Provided	MR
	Provision of Lifts.			
16.	a) Pressurization of lift	N/A	N/A	N/A
	b) Pressurization of lift	N/A	N/A	N/A
	c) Communication in	N/A	N/A	N/A
	lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area			N/A
ī	Total area location	N/A	N/A	IN/A
19.	Fire Control Room	N/A	N/A	N/A
17.	a) Detector system	N/A	N/A	N/A
	panelb) Flow switch panel	N/A	N/A	N/A
		N/A	N/A	N/A
	c) PA system panel d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst any:		n of special Risk, if	N/A

The shortcomings communicated vide letter dated 04/11/15 have been rectified.

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2012/4114 dated 02/11/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

Dycho (ADZ)

to 10:12:15 hary to 1981