## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ NO2/2/2/28

Dated: 03/12/15

## FIRE SAFETY CERTIFICATE

Certified that the Shailey Guest House, 4256, Tel Mandi, Pahar Ganj, New Delhi comprised of Ground, Mezzanine + 3Upper Floors (Ground floor reception + office +01 guest room, Mezzanine & 1<sup>st</sup> floor 03 guest rooms at each floor, 2<sup>nd</sup> floor & 3<sup>rd</sup> floor 04 guest rooms at each floor total 15 guest rooms) was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/3527 dated 25/09/2012. The premise was re-inspected by the officer concerned of this department on 20/11/15 in the presence of Mr. Krishan Kumar (Prop.) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 15 guest rooms only as above with effect from - 21-12-11------ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -03/12/12----at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to:- (1) The Joint Commissioner of Police (Lic.), 1<sup>st</sup> Floor, Police Station, Defence Colony, New Delhi.

(2) Shailey Guest House, 4256, Tel Mandi, Pahar Ganj, New Delhi.

## Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-N/28-

1.Name & address of the building:- Shailey Guest House,4256, Tel Mandi, Pahar Ganj, New Delhi.

2. Type of occupancy:- Residential Group A-1 Ground, Mezz.+ 3

Upper Floors (Total 15 Guest Rooms)

. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2012/3527 dated

25.09.2012

5. Fire safety directives No.- N/A
6. Date of inspection:- 20/11/15

6. Date of inspection:7. Name of the inspecting officer:D.O. Gurmukh Singh

8. Name & designation of officer

From the building side:- Sh. Krishan Kumar (Proprietor)

9. Year of construction:- 1982

10. Applicant's letter No:- 2329-30/ Joint CP/Lic(H) dated 02/11/15

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	NA	NA	NA	
2.	Number, Width Type & Arrange				
۷.	A. Number of staircases	5			
	1. Upper floors	01 No	01 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0. 80 mtr.	1.00 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits		ă .		
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace				
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 Mtr.	1 Mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC, CO2 &	MR	

-N/29-

	3) ISI marking	Required	Provided	MR			
6.	First-Aid Hose Reel						
	1)Total number of each floor	01 no.	01 no.	MR			
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR			
	3) Nozzle diameter	5 mm	5 mm	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System /Intercom	Required	Provided	MR			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false ceiling	N/A	N/A	N/A			
11.	Internal Hydrants			2			
	1) Size of riser/down-comer	NA	NA	NA			
	2) Number of hydrants per	NA	NA	NA			
	floor						
	3) Hose box	NA	NA	NA			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main pump	N/A	N/A	N/A			
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pump	N/A	N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump output		N/A	N/A			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual stopping	N/A	N/A	N/A			
	2) Terrace level						
	a) Discharge of pump	225 LPM	225 LPM	MR			
	b) Head of pump	30 Mtr.	30 Mtr.	MR			
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump	Required	Provided	MR			
14.	Captive Water Storage for Fire Fighting						
	1) Under ground tank capacity	N/A	N/A	N/A			

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2.500 Ltr.	2,500 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	N/A		

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2012/3527 dated 25/09/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

PIECTOR CE

Dy CFO (NDZ)

Solution

Solution