GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/Auditorium/2015/ MD2/2233

Dated: 23/12/15

FIRE SAFETY CERTIFICATE

Certified that the **Triveni Kala Auditorium** located at **205**, **Tansen Marg**, **New Delhi** comprised of **Basement** + **Ground** + **Mezzanine** + **02** Upper floors was granted FSC by this department vide letter No.F6/MS/DFS/Auditorium/2013/759 dated 21/02/13. The premises was re-inspected by the officer concerned of this department on **18/12/15** in the presence of **Sh. Suresh Gupta (Accounts officer)** and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class **Assembly Building (Auditorium) as above Basement** + **Ground** + **Mezzanine** + **02** Upper floors with effect from -2-3/-12-1-15--for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 23/12/15—at New Delhi by.

(**Dr. G.C. Misra**) Chief Fire Officer Ph-011-23414333

Copy to:-

 Sh. Suresh Gupta, (Accounts officer),
Tansen Marg, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

- 12/31-

INSPECTION REPORT

1. Name & address of the building:- Triveni Kala

2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Triveni Kala Auditorium located at 205,

Tansen Marg, New Delhi

Assembly Building

(Basement + Ground + Mezzanine + 02 Upper floors)

Renewal

No. F6/MS/DFS/Auditorium/2013/759

dated 21/02/13.

N/A

18/12/15

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Suresh Gupta (Accounts Officer)

1975

No. Nil dated 12/11/2015.

Old Case

				Old Case	
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks	
	Prevention and fire safety	Existing	PSS	MR/NMR	
	U/R 33				
1.	Access to Building				
	1) Road width	06 mtr.	12 mtr.	MR	
	2) Gate width	4.5 mtr.	4.5 mtr.	MR	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arr	angement of Ex	cits		
	A. Number of staircases				
	1. Upper floors	02 Nos.	02 Nos.	MR	
	2. Basements	02 Nos.	02 Nos.	MR	
	B. Width of staircase				
	1. Upper floors	0.77 & 1.40 mtr.	0.77 & 1.40 mtr.	MR	
	2. Basements	1.70 & 1.22 mtr.	1.70 & 1.22 mtr.	MR	
	C. Protection of exits		2 1		
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	01	01	MR	
	staircase to terrace				
	E. Width of corridor	1.5 mtr.	1.5 mtr.	MR	
	F. Door size	1.80 & 1.90 mtr.	1.80 & 1.90 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	Exhaust fans	MR	
	2) Upper floors	12 a/c per	Natural	MR	
	All Control of the Co	hour			
5.	Fire Extinguishers				
	1) Total numbers	35 Nos.	35 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1) Total number of eachfloor	03 Nos.	03 Nos. in auditorium	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	

- N/52-

	. Automatic Fire Detection & Alarming System				
7.		Smoke	Provided	MR	
	1) Type of detectors	Gr. floor	Provided	MR	
	2) Location of main panel			N/A	
	3) Location of repeater panel	N/A	N/A Provided	MR	
	4) Alternate source of power	Generator			
	5) Hooter's Location	Near gate	Provided	MR	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	•			
10.	1) Basement	Required	Provided	MR	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling	1471			
11					
11.	Internal Hydrants	100 mm	100 mm	MR	
	1) Size of riser/down-comer		01	MR	
	2) Number of hydrants per	01	01	IVIIX	
	floor	0.1	0.1	MD	
	3) Hose box	01	01	MR	
12.	Yard Hydrants	1	1 = =	27/4	
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement				
101	1) Ground level				
	a) Discharge of main	N/A	N/A	N/A	
	,	1 11 1 2			
	b) Head of main pump	N/A	N/A	N/A	
			N/A	N/A	
	c) Number of main pump		N/A	N/A	
	d) Jockey pump out put	N/A		N/A	
	e) Jockey pump head	N/A	N/A		
	f) Stand by pump output		N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping			14	
	2) Terrace level				
	a) Discharge of pump	01 Nos. 1630	01 Nos. 1630 LPM	MR	
	a) Disensing or party	LPM & 02 Nos. 1250 LPM	& 02 Nos. 1250 LPM		
	1) 11 -1 - 0		40 mtr.	MR	
	b) Head of pump	40 mtr.	Provided	MR	
	c) Power supply	Required		MR	
	d) Auto starting of pump	Required	Provided	IVIK	
14.	Captive Water Storage for	Fire Fighting	27/4	NT/A	
	1) Under ground tank	N/A	N/A	N/A	
	capacity			27//	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank	25,000 ltr.	25,000 ltr.	N/A	
	capacity	,			
15.	Exit Signage.	Required	Provided	MR	
	Provision of Lifts.	Required	1.011404		
16.		127/	27/4	NI/A	
	a) Pressurization of lift	N/A	N/A	N/A	
	shaft			27/1	
	b) Pressurization of lift	N/A	N/A	N/A	
	lobby		50		
			Provided	MR	

-N/53-

	lift car			
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room			
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	02 ABC fire extng. Near elect. panel		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/MS/DFS/Auditorium/2013/759 dated 21/02/2013 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation :- ADO (CC)

Diary No. 2065

Doles

John 37/17/15