## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ NO2/2230

Dated: 23/12/15

## FIRE SAFETY CERTIFICATE

Certified that the Hotel Aura Guest House located at 1185/31, Arakashan Road, Pahar Ganj, New Delhi. comprised of Basement, Ground + 3 Upper Floors (basement – hall, Ground floor – reception + 04 guest rooms & 1<sup>st</sup> floor to 3<sup>rd</sup> floor 07 guest rooms at each floor total 25 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/4195 dated 08/11/2012. The premise was re-inspected by the officer concerned of this department on 10/12/15 in the presence of Mr. Ajit (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 25 guest rooms only as above with effect from ----23/12415--- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, mentioned below.

Issued 21/12/15—at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to:- (1) The Joint Commissioner of Police (Lic.), 1<sup>st</sup> Floor, Police Station, Defence Colony, New Delhi.

(2) Hotel Aura Guest House, 1185/31, Arakashan Road, Pahar Ganj, New Delhi.

## Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

## **INSPECTION REPORT**

1. Name & address of the building:- Hotel Aura Guest House locked at 1185/31,

Arakashan Road, Pahar Ganj, New Delhi.

2. Type of occupancy:- Residential Group A-1 Basement, Ground +

3 Upper Floors (Total 25 Guest Rooms)

3. Type of case:- Renewal

4. Details of previous FSC: - No. F6/DFS/MS/GH/2012/4195 dated

08/11/2012.

5. Fire safety directives No.-

6. Date of inspection:-

Pate of inspection:-

7. Name of the inspecting officer:8. Name & designation of officer

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

N/A

10/12/15

D.O. Gurmukh Singh

Mr. Ajit (Manager)

2007

Diary dated 26/11/15

10.	Applicant's letter No:-	Diary dated 2	26/11/15	014 0		
S.No.	Minimum Standards on fire	Requirement	Provided at site	Old Case Remarks		
b.1NO.	Prevention and fire safety U/R 33	Requirement	Trovided at site	MR/NMR		
1.	Access to Building					
	1) Road width	N/A	6 mtrs.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	NA	NA	NA		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 No	01 No.	MR		
	2. Basements	01 No.	01 No.	MR		
	B. Width of staircase		8 9	Sec. 1		
	1. Upper floors	80 cms	130 cms.	MR		
	2. Basements	80 cms.	130 cms.	MR		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 Mtr.	1 Mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	Exhaust fan	MR		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	08 Nos.	10 Nos.	MR		
	2) Types	ABC & CO2	ABC, CO2 &	MR		

-	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel		21011404	IVIIX
	1)Total number of each	01 no.	01 no.	MR
	floor		01 110.	IVIK
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR
	3) Nozzle diameter	5 mm	5 1222	
7.	Automatic Fire Detection & A	Alarming Syste	em	MR
	1) Type of detectors	N/A	N/A	NT/A
	2) Location of main panel	N/A	N/A	N/A N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	120
	5) Hooter's Location	N/A	N/A	N/A
3.	MOEFA	Required	Provided	N/A
9.	Public Address System	Required	Provided	MR
	/Intercom	required	Tiovided	MR
10.	Automatic Sprinkler System			
	1) Basement	Required	Provided	1.00
	2) Upper floors	N/A		MR
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	11///	N/A	N/A
11.	Internal Hydrants			
41	1) Size of riser/down-comer	100 mm.	100	
	2) Number of hydrants per		100 mm.	MR
	floor	01 no.	01 no.	MR
	3) Hose box	01	0.1	
2.	Yard Hydrants	01 no.	01 no.	MR
2.	1) Total number of hydrants	NT/A		
	2) Hose box	N/A	N/A	N/A
3.		N/A	N/A	N/A
•	Pumping Arrangement  1) Ground level		2.1	
	) === 0 trace 10 v O1	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	100		11//1
	2) Terrace level			ni ni
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	40 Mtr.	40 Mtr.	
	c) Power supply	Required	Provided Provided	MR
	d) Auto starting of pump	Required	Provided	MR
,	Captive Water Storage for Fire	Fighting	Trovided	MR
		N/A	NT/A	27/1
	capacity	11/11	N/A	N/A

-re/11-

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A N/A
	c) Access to tank	N/A	N/A	N/A N/A
15.	d) Over head tank capacity	10,000 Ltr.	10,000 Ltr.	MR
	Exit Signage.	Required	Provided	1.00
16.	Provision of Lifts.	1	TTOVIGEG	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
7.	e) Lift signage	N/A	N/A	N/A
	Stand by Power Supply	Required	Provided	MR
8.	Refuge Area	N/A	N/A	
	Total area location	N/A	N/A	N/A N/A
9.	Fine C 1 P.			IN/A
<i>)</i> .	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	NI/A	
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	•	11/11	N/A	N/A
).	e) Building floor plan	N/A	N/A	N/A
•	Special Fire Protection System any:	for Protection of	special Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. rules 2010, is recommended

Gurmukh Singh Divisional Officer

Dycro (NDZ)